


automotive
systems

FESTOOL

Festool GmbH
Export Department
Wertstrasse 20
D-73240 Wendlingen
Phone +49 (0)70 24/804-0
Fax +49 (0)70 24/804-120724
E-Mail SalesSupport@festool.com

www.festool.com

automotive
systems | **FESTOOL**



Catalogue | **2018**

automotive
systems

FESTOOL

Art. no. 067 280 IMP/en




4 014549 318560

Automotive Catalogue 2018
Date: September 2017; supersedes all previous catalogues.

Vibration and emission values can be found in the operating instructions manuals online at www.festool.com/vibration
Subject to modifications and errors. Products may differ from those pictured.
Created for the Festool GmbH, 73240 Wendlingen

2018

**YOU CAN
TELL
A PRO
BY THEIR
TOOLS.**





| | |
|--------------------------------|-----------|
| Safe investment | 02 |
| Profit Zone | 06 |
| SERVICE all-inclusive | 08 |
| Festool automotive systems app | 10 |
| Quality System Partner | 12 |

| | |
|---------------------------|-----------|
| Sets and processes | 14 |
| Spot repair | 16 |
| Sanding | 20 |
| Dust extraction | 30 |
| Polishing | 34 |
| Body work | 40 |

| | |
|---------------------------|-----------|
| Tools | 46 |
| Drilling and screwdriving | 48 |
| Surface Preparation | 58 |
| Dust extraction | 106 |
| Workplace organisation | 122 |

| | |
|----------------------------|------------|
| General information | 146 |
|----------------------------|------------|

QUALITY IS THE GREATEST ASSET.

Quality is not only evident on the surface. It goes deeper and is the result of perfected processes, which are managed by a high level of expertise and the best tools.

It results from uncompromising professionalism that is always one step ahead and acts as a smart investment to support your progress. With Festool by your side, you have a partner that can benefit you in all areas through its spirit of invention and knowledge of the industry.



Scan the page to discover hidden 3D graphics, videos and images.



SUCCESS IS THE BEST REWARD.



Scan the page to discover hidden 3D graphics, videos and images.



1. POTENTIAL ANALYSIS

PROFIT ZONE

Here is where you can save time and money, protect your health and, ultimately, ensure maximum efficiency.

2. BODYSHOP OPTIMISATION

3. STANDARD WORK PROCESSES

PROFIT ZONE

A MASTER PLAN FOR SUCCESS.

Work at the highest level in your technical and corporate operations with Festool tools and standard work processes to take you to the Profit Zone. Festool's special area for corporate success. All of our products, along with our customised service, are designed to provide you with whatever you need in order to gain a competitive advantage and secure the profits which you can then use to get ahead of the competition.

1**POTENTIAL ANALYSIS**

- ▶ Examination of the actual condition of your bodyshop and the work processes
- ▶ Simple measures can enable you to work in a healthy environment and save time and money

2**BODYSHOP OPTIMISATION**

- ▶ During implementation, you can decide which solution works best.
- ▶ Familiarise yourself with new work processes and systems with training sessions, tips and tricks.

3**STANDARD WORK PROCESSES**

- ▶ Optimise your workflows with Festool standard work processes, including simple instructions and the right combination of machines, accessories and consumables.



Scan the page to discover hidden 3D graphics, videos and images.

SERVICE all-inclusive

YOUR INVESTMENT IN SAFE HANDS.



Concentrate on what's important: Your work!

Every day, we consider how we can make life easier for you. With highly sophisticated tools – and services which are tailored to the demands of your daily work and provide optimum protection for your investment.

Register the tool online up to 30 days after purchase to benefit from all services!

www.festool.com/register

THREE-YEAR WARRANTY

10 YEAR SPARE PART AVAILABILITY

REPAIR SERVICE

DIRECT CONTACT FOR YOUR QUESTIONS

SERVICE all-inclusive applies to all machines registered within 30 days of purchase and purchased on or after 2nd April 2013. More information and the service terms and conditions can be found at www.festool.com/service

The warranty does not apply to damage to consumables and accessories, misuse, damage caused by the use of non-original accessories or spare parts, or in the case of devices which you have dismantled yourself or which have been subjected to constant, hard-wearing use.

FESTOOL AUTOMOTIVE SYSTEMS APP

VIRTUAL WORKSHOP.

See more with augmented reality.

More information on many Festool products and processes can be found in our catalogue. Complex connections are illustrated and explained using hidden images, videos and 3D graphics.

Our app now also features virtual reality.

Look out for Festool's fascinating parallel world.

1. DOWNLOAD




Install the free-of-charge Festool automotive systems app on your mobile device.

2. CHOOSE



Launch the app and choose between virtual reality and augmented reality.



3. EXPERIENCE



OR



Virtual reality:

Place your smartphone in the headset and experience virtual reality for yourself.

Augmented reality:

Point the camera at a page where you can see the augmented reality icon.

QUALITY SYSTEM PARTNER

SUSTAINABLE ADDED VALUE FOR YOUR INVESTMENT.

**Tailored, professional system consultation with bodyshop
optimisation on your premises – and much more!***

Why not become a Quality System Partner too?

For more information, go to www.festool.com

**We want to make a significant contribution to their success and are continually
supporting and taking these partners forwards with regard to cost reduction,
efficient work processes, improved operating capacity, innovations and trends.**

* Services may vary from country to country



Saskia Bauer, CEO of John Bauer GmbH (Hamburg, GER)

“We have relied on the Festool premium brand for over 15 years...”

“We have relied on the Festool premium brand for over 15 years because we have the same quality requirements. The service life of the machines is an important factor. And when we do need a repair, our order is prioritized by the QSP partnership. Overall, the arrangement has made us more productive. Festool has always proven to be a successful partner for us.”



Festool employee Yuri Shupa on site at Alizia LLC (part of the Avtomir group) with bodyshop painter Konstantin Maslak (Moscow, RUS)

„When a service technician makes an on-site visit, comprehensive servicing of the whole equipment base can take place directly on site...”

To provide the best-quality maintenance service for hand tools, particularly pneumatic ones, it is important to assess the conditions in which they are actually used, such as the quality of the compressed air and the quality of the supply line. Not only does this help us to eliminate knock-on effects such as equipment breakdowns or malfunctions, it also makes it easier to discover the root causes, which we and the user can rectify together. When a service technician makes an on-site visit, comprehensive servicing of the whole equipment base can take place directly on site, i.e. without interrupting work.



Wang Rui, Technical Manager, Sichuan Jingdian Rongxin Auto Repair & Paint Center (Chengdu, CHN)

“My impression of Festool is of its being ‘highly efficient, outstanding in quality, and offering a good service’.”

“My impression of Festool is of its being „highly efficient, outstanding in quality, and offering a good service“. Sichuan Jingdian Rongxin Auto Repair and Paint Center began operating at the beginning of 2016. The Festool training executives worked with us to help us grow so that one by one we were able to master each “dry sanding” technical point until we are now using purely “dry sanding”. The efficiency with which we now work in our workshop has significantly improved, and we are at the same time able to guarantee the quality of our work, to the point where we have to handle very few reworking problems arising from substandard work.

PROFESSIONAL PROCESSES AND SETS

VISION THAT PAYS OFF.





Quality at the highest level is only as good as its consistency. Only then does it become a driving force for efficiency. An investment in Festool products and standard processes not only sets the course for long-term top performance and results. It also breaks new ground in increasing efficiency, which inevitably leads to higher profits.

Sets and processes

| | |
|-----------------|----|
| Spot repair | 16 |
| Sanding | 20 |
| Dust extraction | 30 |
| Polishing | 34 |
| Body work | 40 |

SPOT REPAIR AT A PROFESSIONAL LEVEL


FROM INVESTMENT TO RETURN IN 90 MINUTES.

- ▶ Finished in 90 minutes
- ▶ Maximum efficiency achieved by using one machine for the entire process
- ▶ Easy way of generating additional business

1

CLEAN THE AREA AROUND PAINT ZONE

MPA 5010, orange polishing pad, microfibre cloth, ROTEX RO 90 DX


 Polishing | 75 mm diameter*



2

REMOVE THE DAMAGED MATERIAL

GRANAT P120, ROTEX RO 90 DX

 Sanding | 90 mm diameter*




3

REDUCE THE SURFACE

GRANAT P180, P280, P400, ROTEX RO 90 DX

Spray the filler in the direction of the damaged area**

 Sanding | 90 mm diameter*



* Switch position on the ROTEX RO 90

** Apply filler and clear coat to the damaged area as accurately as possible. Otherwise, there will be a larger area to polish and edges may form along the transition point, thus creating the need for additional reworking.



Scan the page to discover hidden 3D graphics, videos and images.

4

SAND THE FILLER

GRANAT P400, ROTEX RO 90 DX

⚙️ Sanding | 90 mm diameter*



5

SAND THE AREA AROUND THE PAINT ZONE

PLATIN 2 S1000, PLATIN 2 S2000, ROTEX RO 90 DX

Spray the clear coat in the direction of the damaged area**

⚙️ Sanding | 90 mm diameter*



6

POLISH THE AREA AROUND THE PAINT ZONE

MPA 5010, orange polishing pad, microfibre cloth, ROTEX RO 90 DX

⚙️ Polishing | 75 mm diameter*



SPOT REPAIR SET

YOUR CUSTOMERS WILL THANK YOU. AND SO WILL YOUR WALLET.

Eliminating even the smallest scratches has the potential to further increase customer satisfaction and increase sales. Offer your customers a service at a fixed price when receiving the vehicle and benefit from a competitive advantage. Repair defects, boost sales. That is what spot repair is all about.

Included in the spot repair set

(A detailed list can be found on page 124)



Geared eccentric sander
ROTEX RO 90 DX + suction hose with plug-it



Mobile dust extractor
CTM 26 E + WCR 1000 Workcenter



Consumables
Abrasives Systainer including abrasive, polishing pad, polish, foam pad



- ▶ Finished in 90 minutes
- ▶ Maximum efficiency achieved by using one machine for the entire process
- ▶ Easy way of generating additional business

System accessories
Page 78



Abrasives
Page 93





2 in 1

...

Two applications.
One machine.

SANDING AT A PROFESSIONAL LEVEL


HOW TO INCREASE VALUE IN FOUR STEPS.

- ▶ Faster surface preparation in four steps only
- ▶ The same top-quality results guaranteed for optimally prepared paintwork

1

COARSE SANDING OF BODY FILLER/PUTTY

GRANAT P80 + LEX 3 150/5
or ETS EC 150/5



2

FIRST INTERMEDIATE SANDING OF BODY FILLER/PUTTY

GRANAT P180 + LEX 3 150/5
or ETS EC 150/5





Scan the page to discover hidden 3D graphics, videos and images.

3

SECOND INTERMEDIATE SANDING OF BODY FILLER/PUTTY

GRANAT P280 + LEX 3 150/5
or ETS EC 150/5

4

FINAL SANDING OF PRIMER

GRANAT P400 + LEX 3 150/3
or ETS EC 150/3



EC ELECTRIC SANDING SET

POWERING AHEAD WITH EXCELLENCE.

The quality has to be right. As does the quality of the air we breathe in. Two priorities for which Festool makes no compromises. The automatic dust extraction control on the ETS EC electric eccentric sander guarantees that the workplace is completely safe, while the four-step sanding process ensures perfect results.

Included in the EC electric sanding set

(A detailed list can be found on page 125)



Electric eccentric sander

ETS EC 150/5 + ETS EC 150/3 + suction hose with plug-it



Mobile dust extractor

CTM 48 E LE EC + WCR 1000 Workcenter



Consumables

Abrasives Systainer including abrasive, dry guide coat powder set, SELFCLEAN filter bags, etc.

Electric sanding set

(A detailed list can be found on page 125)

Our alternative with the CTM 36 E LE mobile dust extractor.

- ▶ Durable machine including functions designed with health in mind, such as dust extraction control and vibration control
- ▶ EC-TEC mobile dust extractor for maintenance-free work and a service life up to five times longer
- ▶ The most flexible complete set for efficient processes

System accessories
Page 82



Abrasives
Page 95





+30%
...
faster processing when
fully equipped.

The sets required for the Festool sanding process

- Hand-sanding block set
- **Electric sanding set**
- Compressed air set
- Safety set

EC COMPRESSED AIR SET

LOWER AIR CONSUMPTION FOR YOUR WALLET.

Working with compressed air is a must. As is using the LEX 3 Generation with long-life motor technology. This compressed air solution for an even faster sanding process can save you money and keep energy costs to a minimum.

Included in the EC compressed air set

(A detailed list can be found on page 126)



Compressed air eccentric sander

LEX 3 150/5 + LEX 3 150/3 + IAS 3 light suction hose



Mobile dust extractor

CTM 48 E LE EC + Workcenter WRC 1000



Consumables

Abrasives Systainer including abrasive, dry guide coat powder set, SELFCLEAN filter bags, and much more.

Compressed air set

(A detailed list can be found on page 126)

Our alternative with the CTM 36 E LE mobile dust extractor.

- ▶ Up to 30% faster sanding thanks to sanding process and full range of equipment
- ▶ LEX 3 Generation with long-life motor technology
- ▶ EC-TEC mobile dust extractor for maintenance-free work and a service life up to five times longer

System accessories
Page 86



Abrasives
Page 95





-30%
...
lower energy costs thanks
to low compressed air
consumption – 290 l/min.

The sets required for the Festool sanding process



SAFETY SET

SAFETY WILL NEVER BE AN OUTDATED PROBLEM.

The increased use of aluminium, carbon and fibreglass in vehicles requires extra care when dealing with these materials – or a safety concept which complies with the ATEX Directive 94/9/EC for Zone 22 and simply extracts all dry and flammable dust and collects it in a flame-resistant plastic container.

Included in the safety set

(A detailed list can be found on page 127)



Compressed air eccentric sander

LEX 3 150/5 + LEX 3 150/3 + IAS 3 light suction hose



Mobile dust extractor

CTM 48 E LE EC/B22 + WCR 1000 Workcenter



Consumables

Abrasives Systainer including abrasive, dry guide coat powder set, SELFCLEAN filter bags, etc.



- ▶ Up to 30% faster sanding thanks to the 4-step sanding process and full range of equipment
- ▶ Reliable extraction of dry, flammable dust in Zone 22 protects health and prevents accidents
- ▶ Special extractor with flame-retardant 48-litre plastic container and a service life up to five times longer

System accessories
Page 86



Abrasives
Page 95





ATEX
...
Mobile dust extractor complies
with ATEX Directive 94/9/EC
for Zone 22.

The sets required for the Festool sanding process



HAND-SANDING BLOCK SET

FINISHING TOUCHES FOR YOUR MANUAL WORK.

Quality and health are never compromised – even when we have to use our own hands. The hand-sanding block set with dust extraction leaves no dust or dust marks behind – just optimum sanding results for every user.

Please order the following components

(A detailed list of all items can be found from page 90 onwards)



Hand-sanding block set

HSK-A 80 x 130, HSK-A 80 x 200,
HSK-A 80 x 400, HSK-A 115 x 226

Order no.

497101



Suction hose

D21,5 x 5 m HSK

495019




- ▶ No time-consuming reworking: Cleaner sanding – even by hand
- ▶ Wider sanding area results in a perfect surface

System accessories
Page 90



Abrasives
Page 96





DUST EXTRACTION
...
The hand-sanding block set with dust extraction.

The sets required for the Festool sanding process



-80%

...

Energy savings of up to 80%
throughout the entire system,
including EAA and ASA.



Scan the page to discover hidden 3D graphics,
videos and images.



A TIDY PROFIT.

TURBO II DC-TEC EXHAUST TURBINE

- ▶ The central extraction solution for up to 14 workstations is worthwhile for more than 3 stations operating in parallel
- ▶ Its automatic system always ensures an optimum ratio between the suction power required and the power needed to achieve it
- ▶ 100% capacity with up to 80% reduced power consumption
- ▶ Offers maximum freedom, noticeable comfort and comprehensive protection thanks to the following system components: Flexible pipe system, long, movable boom arm and a sophisticated energy box

The best solution to meet your requirements

[A detailed list of all items can be found from page 114 onwards]

TURBO II M-8WP*

Suitable for up to 8 workplaces.

Items included:

2× main filter, 1× disposal bag

TURBO II M-8WP ATEX R1 with dust extraction in accordance with ATEX Directive 94/9/EC for Zone B22

Order no.

M-8WP ATEX R1

583886

TURBO II M-14WP*

Suitable for up to 14 workplaces.

Items included:

3× main filter, 1× disposal bag

TURBO II M-14WP ATEX R1 with dust extraction in accordance with ATEX Directive 94/9/EC for Zone B22

Order no.

M-14WP ATEX R1

583887

* The pipe system is not included in the package.



Components for your perfect system solution

[A detailed list of all items can be found from page 114 onwards]

EAA ENERGY BOX



Order no.

EAA EW/DW TURBO/A-EU

583831

ASA BOOM ARM



Order no.


ASA 5000 TURBO-EU

583856

ASA 6000 TURBO-EU

583857

ASA system accessories
Page 121, 130



EAA system accessories
Page 121, 131



POLISHING AT A PROFESSIONAL LEVEL

PROFIT THAT YOU CAN SEE YOUR REFLECTION IN.

- ▶ High gloss finish in just two steps = up to 30% faster using the Premium polishing process from Festool
- ▶ Ideal results with maximum control in three steps using the Professional polishing process
- ▶ Uses up to 50% less abrasive and boasts up to three times longer service life

PREMIUM

Efficient polishing for true professionals.

1

SANDING

GRANAT P1500 abrasive +
LEX 3 77/2.5 set

For sanding out flaws to achieve a fine sanding finish with minimum surface roughness on all clear coats.



2

POLISHING

Premium sheepskin pad + MPA 5010
one-step sanding polish + SHINEX RAP 150

Remove sanding scratches while simultaneously achieving the perfect shine in one single working step.



- ▶ Also for removing extremely fine swirl marks from dark and delicate clear coats:
White waffle face pad, 150 mm and MPA 11010 high-gloss polish + ROTEX RO 150



Scan the page to discover hidden 3D graphics, videos and images.

PROFESSIONAL

The most reliable way to optimum polishing results.

1

SANDING

GRANAT P3000 abrasive +
D 36 disc

2

FIRST POLISHING STEP

MPA 5010 (orange) +
orange polishing sponge

3

SECOND POLISHING STEP

MPA 9010 (blue) +
blue polishing sponge



► Also for removing extremely fine swirl marks from dark and delicate clear coats:
White waffle face pad, 150 mm and MPA 11010 high-gloss polish + ROTEX RO 150

HIGH-GLOSS SET I

ON THE POLE POSITION IN POLISHING.

Achieve high gloss at high speed in two extremely short steps as part of the standard work process. Work using the Festool set versions is finished in a flash and means that you can have the largely unpaid polishing work done in no time.

Included in high-gloss set I

(A detailed list can be found on page 128)



Rotary polisher
SHINEX RAP 150-14 FE



Starter set
LEX 3 77 compressed air eccentric sander including connection system + SYSTAINER



Consumables
Abrasive, polish, deNibber, sheepskin pad, etc. in UCR 1000 Universalcenter

- ▶ 1, 2, and you're done – in just two work steps, you can remove flaws and achieve a high-gloss finish on non-sensitive paints
- ▶ Consumables made of top-quality materials mean that up to 50% fewer materials need to be used and result in a service life up to three times longer

Polishing accessories
Page 100



System accessories
Page 99





+30%

• • •
faster processing when
fully equipped.

The sets required for the Festool polishing process



High-gloss set

Swirl mark set

SWIRL MARK SET

DARK SURFACE? MAKE IT SPARKLE!

Microfine grooves in dark clear coats need special handling after polishing. Thanks to the ROTEX rotary motion, these swirl marks smooth out to form a perfect shine across the entire surface in no time at all.

Included in the swirl mark set

(A detailed list can be found on page 129)



Eccentric sander
ROTEX RO 150 FEQ



Consumables
Polishing pad, high-gloss polish, microfibre cloth,
and much more



- ▶ The synergy between the system components produces the perfect gloss effect:
White waffle face pad and high-gloss polish
- ▶ Low speed and waffle face pad keep the surface cooler and ensure reliable results

Polishing accessories
Page 100



System accessories
Page 80



1



All in a single step.



The sets required for the Festool polishing process



High-gloss set

Swirl mark set



MORE TIME AND MONEY FROM THE VERY OUTSET.

TOOLS THAT LAST, RETURNS THAT LAST.



All Festool products are based on quality and efficiency. Whether it's a cordless drill or eccentric sander. The long-term success of your company is always our priority. An investment that rewards trust in the company's own aspirations.

Quality makes the difference. That is why Festool is the tool for anyone wanting to stand out from the competition. This has led us to develop solutions for painters with greater expertise, stricter requirements, a stronger desire for success and a broader outlook. For everyone who knows how to achieve the best results. Those produced by your own work and those produced by your own company. Festool is proud to be the tool of professionals who strive to achieve top performance.

ASSEMBLY SET

WORKING WITH SCREWS HAS NEVER BEEN THAT EASY.

It's like working in the pit lane. Carry out disassembly and assembly work easily in record-breaking time. With the handy CXS cordless drill, you can access even the most difficult corners and angles of bodywork, thus achieving maximum efficiency.

Please order the following components

(A detailed list of all items can be found from page 49 onwards)



Cordless drill
CXS Li 2,6-set

Order no.

564532



Ratchet set
1/4"-CE RA-set 37

497881



Work light
SYSLITE, KAL II-set

499815




- ▶ Efficient disassembly/assembly, e.g. on recessed grips, wheel housings or door panels, with the lightweight CXS cordless drill and ratchet set
- ▶ 12 LEDs on the SYSLITE working light ensure a perfect view of dark and inaccessible spots

Drilling and screwdriving
Page 49



System accessories
Page 53



50%

...
faster than any
screwdriver.



OLD PAINT SET

ON WITH EFFICIENCY. AND OFF WITH PAINT.

There is no quicker, cleaner or more efficient way to remove old paint. The high material removal capacity achieved through the sanding movement provided by the ROTEX rotary motion ensures that you can work quickly, while the accurate dust extraction system guarantees high-quality results and contributes to safety in the workplace.

Please order the following components

(A detailed list of all items can be found from page 59 onwards)



Geared eccentric sander
ROTEX RO 150 FEQ

Order no.

571761



Mobile dust extractor
CTM 36 E

584000



Workcenter
WCR 1000

497471



Suction hose
D27/22 smooth suction hose with
plug-it, 3.50 m, anti-static

500269



- ▶ Cleaner air thanks to perfectly designed dust extraction system
- ▶ Coarse sanding: ROTEX rotary motion for efficient material removal
- ▶ Fine sanding: Eccentric motion for a refined sanding finish

System accessories
Page 80



Abrasives
Page 95



PERFECT
...
Creates the perfect surface for
all subsequent paintwork
preparation tasks.





QUALITY AS A FACTOR IN SUCCESS.

MONEY-SAVING INVESTMENTS.



True professionals invest in the best staff and the best tools. After all, quality is and will remain the most reliable factor in ensuring success. Both come at a price, but in the long term, they reward the trust held in them and considerably increase the efficiency, profits and value of the work and of the company.

Tools

Drilling and screwdriving 48

Surface Preparation 58

Dust extraction 106

Workplace organisation 122



DRILLING AND SCREWDRIVING

PROFESSIONALS IN SCREWDRIVING.

Cordless drills 50
CXS, TXS, C 18, T 18+3

Accessories and consumables 53

The Festool system

CXS / TXS

CXS, TXS cordless drills



Scan the page to discover hidden 3D graphics, videos and images.

Genuine power pack.

The extra small 10.8 V cordless drills possess a remarkable torque, even in hard-to-reach places. Thanks to FastFix and the CENTROTEC rapid tool change system, they are convincingly flexible.

When it comes to performance, size really isn't that important.

- ▶ Impressive ergonomics and low weight (0.9 kg) for convenient drilling and fastening
- ▶ The compact, handy shape makes work easier, even in cramped spaces
- ▶ FastFix interface and CENTROTEC quick tool-change system
- ▶ Practical – integrated LED light and battery charge indicator

| Technical data | CXS | TXS |
|--|-------------------|-------------------|
| Battery voltage (V) | 10,8 | 10,8 |
| Gears | 2 | 2 |
| Idling speed, 1st gear/2nd gear (min ⁻¹) | 0 – 430/0 – 1.300 | 0 – 430/0 – 1.300 |
| Drilling diameter, wood/steel (mm) | 12/8 | 12/8 |
| Torque adjustment 1st/2nd gear (Nm) | 0,3 – 3,4 | 0,3 – 3,4 |
| Max. torque, wood/steel (Nm) | 10/16 | 10/16 |
| Chuck range (mm) | 1 – 10 | 1 – 10 |
| Li-ion battery capacity (Ah) | 2,6 | 2,6 |
| Li-ion charging time (min) | 45 | 45 |
| Weight with Li-ion (kg) | 0,9 | 0,9 |



= Electronic

| Items included | Order no. |
|---|---------------|
| 2 x battery pack BP-XS, charger MXC, CENTROTEC tool chuck, CENTROTEC bit holder, FastFix keyless chuck 10 mm, bit PZ 2, belt clip, in SYSTAINER SYS 1 T-LOC | |
| CXS Li 2,6-Plus | 564531 |
| CXS Li 2,6-Set XS elbow adapter | 564532 |
| TXS Li 2,6-Plus | 564509 |
| TXS Li 2,6-Set XS elbow adapter | 564510 |

System accessories from page 53



Bits and drills from page 55



C 18

C 18 cordless drill

product
design
award

2010


Brushless EC-TEC motor for
a long service life and a high
level of efficiency

The perfect shape.

- ▶ Brushless EC-TEC motor with integrated motor management for long service life and the highest output
- ▶ Fully electronic torque setting and switch-off for precise screwdriving
- ▶ FastFix interface for all FastFix attachments and CENTROTEC rapid tool-change system
- ▶ Switchover from screwdriving to drilling without changing the set torque

| Technical data | C 18 Plus/Set | C 18 Compact |
|--|-------------------|-------------------|
| Battery voltage (V) | 18 | 18 |
| Gears | 2 | 2 |
| Idling speed, 1st gear/2nd gear (min ⁻¹) | 0 - 450/0 - 1.500 | 0 - 450/0 - 1.500 |
| Drilling diameter, wood/steel (mm) | 40/13 | 40/13 |
| Torque adjustment 1st/2nd gear (Nm) | 0,8 - 8/0,5 - 6 | 0,8 - 8/0,5 - 6 |
| Max. torque, wood/steel (Nm) | 27/45 | 27/45 |
| Chuck range (mm) | 1,5 - 13 | 1,5 - 13 |
| Li-ion battery capacity (Ah) | 5,2 | 3,1 |
| Weight with Li-ion (kg) | 1,8 | 1,5 |



 = Electronic


| Items included | Order no. |
|---|---------------|
| CENTROTEC tool chuck, CENTROTEC bit holder, FastFix keyless chuck 13 mm, bit PZ 2, belt clip, in SYSTAINER SYS 2 T-LOC | |
| C 18 Li 5,2-Plus 2 x BP 18 Li 5.2 AS battery pack, rapid charger TCL 6 | 574738 |
| C 18 Li 5,2-Set 2 x BP 18 Li 5.2 AS battery pack, SCA 8 rapid charger, FastFix angle attachment, FastFix eccentric attachment | 574739 |

Distinctive stirrup shape.

The C 18 has won many awards for outstanding design with a proven brushless drive concept. The combination of lithium-ion battery packs and EC-TEC motor makes the C 18 even lighter and gives it even more power and battery life – making the C-series the most powerful ever.



System accessories
from page 53



Bits and drills
from page 55



Battery and charging
technology from page 53
onwards



T 18+3

T18+3 cordless drills



Brushless EC-TEC motor for a long service life and a high level of efficiency



Brains meet brawn.

The powerhouse of the T-series, featuring an 18-volt power supply, a brushless EC-TEC motor and a comfortable, lightweight design for excellent handling. The T 18+3 provides significantly better performance for the most challenging applications.



Brains meet brawn.

- ▶ FastFix interface for all FastFix attachments and CENTROTEC rapid tool-change system
- ▶ Impressive ergonomics: compact, lightweight and perfectly balanced
- ▶ Fully electronic torque setting and switch-off for precise screwdriving
- ▶ Switchover from screwdriving to drilling without changing the set torque


| Technical data | T 18+3 Plus/Set | T 18+3 Compact |
|--|-------------------|-------------------|
| Battery voltage (V) | 18 | 18 |
| Gears | 2 | 2 |
| Idling speed, 1st gear/2nd gear (min ⁻¹) | 0 - 450/0 - 1.500 | 0 - 450/0 - 1.500 |
| Drilling diameter, wood/steel (mm) | 45/13 | 45/13 |
| Torque adjustment 1st/2nd gear (Nm) | 0,8 - 8/0,5 - 6 | 0,8 - 8/0,5 - 6 |
| Max. torque, wood/steel (Nm) | 35/50 | 35/50 |
| Chuck range (mm) | 1,5 - 13 | 1,5 - 13 |
| Li-ion battery capacity (Ah) | 5,2 | 3,1 |
| Weight with Li-ion (kg) | 1,8 | 1,5 |



■ = Electronic

| Items included | Order no. |
|---|---------------|
| CENTROTEC tool chuck, CENTROTEC bit holder, FastFix keyless chuck 13 mm, belt clip | |
| T 18+3 Li-Basic without battery pack, without charger, bit PZ 2, in SYSTAINER SYS 2 T-LOC | 574763 |
| T 18+3 Li 3,1-Compact 2 x BP 18 Li 3.1 C battery pack, rapid charger TCL 6, bit PZ 2, in SYSTAINER SYS 2 T-LOC | 574908 |
| T 18+3 Li 5,2-Plus 2 x BP 18 Li 5.2 AS battery pack, rapid charger TCL 6, bit PZ 2, in SYSTAINER SYS 2 T-LOC | 574756 |
| T 18+3 Li 5,2-Set 2 x BP 18 Li 5.2 AS battery pack, SCA 8 rapid charger, bit PZ 2, FastFix angle attachment, FastFix eccentric attachment, in SYSTAINER SYS 2 T-LOC | 574758 |

System accessories from page 54




Bits and drills from page 55



Battery and charging technology from page 54 onwards




System accessories



Accessories for CXS and TXS cordless drills

| Denomination | Explanation | Order no. |
|------------------------------------|---|-----------|
| 1 Tool chuck WH-CE CENTROTEC | for all Festool cordless and mains-operated drills (except DR 20/DRP 20) with CENTROTEC interface, in self-service display pack | 492135 |
| 2 Keyless chuck BF-FX 10 | for Festool cordless drills CXS and TXS, clamping range 1 – 10 mm, in self-service display pack | 499949 |
| 3 Angle attachment XS-AS | for CXS and TXS cordless drills, for working in tight spaces, in self-service display pack | 497951 |
| 4 Battery pack BP-XS 2.6 Ah Li-Ion | lithium-ion spare battery for cordless drills CXS and TXS, tensioner 10,8 V, capacity 2,6 Ah, weight 0,2 kg, in self-service display pack | 500184 |
| 5 Charger MXC | for BP-XS battery packs, for CXS and TXS cordless drills, charging current 2,8 A, input voltage 220 – 240 V, in carton | 497495 |

System accessories



Accessories for C 18, T 18+3 cordless drills

| Denomination | Explanation | Order no. |
|--------------------------------------|---|-----------|
| 1 Tool chuck WH-CE CENTROTEC | for all Festool cordless and mains-operated drills (except DR 20/DRP 20) with CENTROTEC interface, in self-service display pack | 492135 |
| 2 Keyless chuck KC 13-1/2-K-FFP | for all Festool cordless drills, cordless impact drills, drills (except DR 20/DRP 20) and impact drills with CENTROTEC interface, impact resistant, plastic ring, with locking device, holder FastFix, clamping range 1,5 – 13 mm, in self-service display pack | 769067 |
| 3 FastFix eccentric attachment DD-ES | for all Festool C and T cordless drills with FastFix interface (except CXS/TXS), in self-service display pack | 490294 |
| 4 FastFix angle attachment DD-AS | for all Festool C and T cordless drills with FastFix interface (except CXS/TXS), in self-service display pack | 490293 |
| 5 Battery pack BP 18 Li 5,2 AS | with AIRSTREAM function, lithium-ion (Li-ion) replacement battery pack for all Festool 18 V cordless tools (except CXS/TXS/RTSC/DTSC/ETSC), tensioner 18 V, capacity 5,2 Ah, weight 0,7 kg, in self-service display pack | 200181 |
| Battery pack BP 18 Li 3,1 C | compact, lightweight design, lithium-ion (Li-ion) replacement battery pack for all Festool 18 V cordless tools (except TSC 55, CXS/TXS/RTSC/DTSC/ETSC), tensioner 18 V, capacity 3,1 Ah, weight 0,4 kg, in self-service display pack | 201789 |
| 6 Rapid charger TCL 6 | for all Li-ion battery packs (except for CXS/TXS), Lithium-ion (Li-ion) replacement charger for all 10.8 – 18 V battery packs, charging current 6 A, input voltage 220 – 240 V, weight 0,8 kg, in self-service display pack | 201135 |
| Rapid charger SCA 8 | for all Li-ion battery packs (except for CXS/TXS), with AIRSTREAM function, Lithium-ion (Li-ion) replacement charger for all 10.8 – 18 V battery packs, charging current 8 A, input voltage 220 – 240 V, weight 1,1 kg, in self-service display pack | 200178 |

System accessories

25 mm bits



| | Type | Order no. |
|--|--------|---------------|
| twinBOX content 10 pieces, in self-service display pack 3 x PZ 1 bit, 4 x bit PZ 2, 3 x PZ 3 bit | BB-PZ | 496934 |
| TX 10 bit, 2 x TX 15 bit, 3 x TX 20 bit, 3 x TX 25 bit, TX 30 bit | BB-TX | 496935 |
| PH 1 bit, PH 2 bit, PZ 1 bit, bit PZ 2, PZ 3 bit, SZ 0.8 x 5.5 bit, TX 15 bit, TX 20 bit, TX 25 bit, TX 30 bit | BB-MIX | 496936 |

100 mm bits



| | Type | Order no. |
|--|---------------|---------------|
| Bits length 100 mm, qty. in pack 2 piece(s), in self-service display pack size PZ 1 | PZ 1-100 CE/2 | 500841 |
| size PZ 2 | PZ 2-100 CE/2 | 500842 |
| size PZ 3 | PZ 3-100 CE/2 | 500843 |



| | | |
|--|---------------|---------------|
| Bits length 100 mm, qty. in pack 2 piece(s), in self-service display pack size PH 1 | PH 1-100 CE/2 | 500844 |
| size PH 2 | PH 2-100 CE/2 | 500845 |
| size PH 3 | PH 3-100 CE/2 | 500846 |











| | | |
|--|---------------------|---------------|
| Bits length 100 mm, qty. in pack 2 piece(s), in self-service display pack size SZ 0,8 x 5,5 | SZ 0,8x5,5-100 CE/2 | 500852 |
| size SZ 1,2 x 6,5 | SZ 1,2x6,5-100 CE/2 | 500851 |





| | | |
|---|----------------|---------------|
| Bits length 100 mm, qty. in pack 2 piece(s), in self-service display pack size TX 15 | TX 15-100 CE/2 | 500847 |
| size TX 20 | TX 20-100 CE/2 | 500848 |
| size TX 25 | TX 25-100 CE/2 | 500849 |
| size TX 30 | TX 30-100 CE/2 | 500850 |

System accessories

| Bits and bit holders | | Type | Order no. |
|---|--|----------------------------|-----------|
|  | Bit box for all Festool cordless drills with FastFix interface, CENTROTEC magnetic bit fastener BH 60 CE, content 10 pieces, in self-service display pack | | |
| | 2 x PZ 1 bit, 5 x bit PZ 2, 2 x PZ 3 bit | PZ + BH 60-CE | 493260 |
| | TX 10 bit, 2 x TX 15 bit, 3 x TX 20 bit, 2 x TX 25 bit, TX 30 bit | TX + BH 60-CE | 493261 |
| | PH 1 bit, PH 2 bit, PZ 1 bit, bit PZ 2, PZ 3 bit, SZ 0.8 x 5.5 bit, TX 15 bit, TX 20 bit, TX 25 bit | MIX + BH 60-CE | 493262 |
|  | Bit holder for all Festool cordless drills with FastFix interface, qty. in pack 1 piece(s), in self-service display pack | BHS 65 CE | 492648 |
|  | Bit holder for all Festool cordless drills with FastFix interface, also suitable for use with impact screwdriver T115 Impact, qty. in pack 1 piece(s), in self-service display pack | BH 60 CE-Imp | 498974 |
|  | Bit holder for all Festool cordless drills with FastFix interface, extra-long, qty. in pack 1 piece(s), in self-service display pack | BV 150 CE | 492540 |
| | Adapter for all Festool cordless drills with FastFix interface, for plug-in bits, with ball lock for manual operation, qty. in pack 1 piece(s), in self-service display pack | | |
|  | holder 1/4", length 50 mm | 1/4"-50 CE/KG CENTROTEC | 495131 |
|  | holder 3/8", length 70 mm | 3/8"-70 CE/KG CENTROTEC | 495133 |
|  | Screwdriver for CENTROTEC tools for drilling and screwdriving, in self-service display pack | SD-CE-DRIVE-UNI | 200140 |
| Bit cassette | | Type | Order no. |
|  | Ratchet set 1/4" socket set from 4.0 to 13 mm, 19 different bit inserts and 2 bit extensions, ratchet and CENTROTEC handle plus various adapters and extensions, in SYSTAINER SYS MINI | 1/4"-CE RA-Set 36 | 497881 |

System accessories

CENTROTEC HSS twist drill bit

| | Type | Order no. |
|--|------------------------|---------------|
|  Twist drill bit in self-service display pack | | |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 3 mm, qty. in pack 1 piece(s) | HSS D 3/33 CE/M-Set | 493421 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 3,5 mm, qty. in pack 1 piece(s) | HSS D 3,5/39 CE/M-Set | 493422 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 4 mm, qty. in pack 1 piece(s) | HSS D 4/43 CE/M-Set | 493423 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 4,5 mm, qty. in pack 1 piece(s) | HSS D 4,5/47 CE/M-Set | 493424 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 5 mm, qty. in pack 1 piece(s) | HSS D 5/52 CE/M-Set | 493425 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 5,5 mm, qty. in pack 1 piece(s) | HSS D 5,5/57 CE/M-Set | 493426 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 6 mm, qty. in pack 1 piece(s) | HSS D 6/57 CE/M-Set | 493427 |
| complete drill bit with bit holder and 2 replacement drill bits, hexagon socket wrench, diameter 6,5 mm, qty. in pack 1 piece(s) | HSS D 6,5/63 CE/M-Set | 493428 |
| complete drill bit with bit holder and 1 replacement drill bit, hexagon socket wrench, diameter 8 mm, qty. in pack 1 piece(s) | HSS D 8,0/75 CE/M-Set | 495308 |
| complete drill bit with bit holder and 1 replacement drill bit, hexagon socket wrench, diameter 10 mm, qty. in pack 1 piece(s) | HSS D 10,0/75 CE/M-Set | 495309 |
|  Drill bit case, diameter 3 – 10 mm, qty. in pack 10 piece(s) | HSS D3-10 CE/10 | 495128 |



SURFACE PREPARATION

PROFESSIONALS IN SURFACE PREPARATION.

Sanding

Geared eccentric sander 60

ROTEX RO 90 DX, RO 125, RO 150

Eccentric sander 63

ETSC 125, ETS EC 125, ETS EC 150

Orbital sander 66

RS 100, RTSC 400

Rotary sanders 68

RAS 180

Sanding with compressed air

Compressed air eccentric sander 70

LEX 3

Compressed air orbital sander 73

LRS 93, LRS 400

Polishing

Rotary polisher 76

SHINEX RAP 150, POLLUX 180

Accessories and consumables 78

The Festool system

ROTEX RO 90 DX

Geared eccentric sander ROTEX RO 90 DX



Scan the page to discover hidden 3D graphics, videos and images.

Four tools in one.

One machine that can be used for coarse sanding, fine sanding, polishing and delta sanding. Low initial costs, maximum flexibility and a wide range of applications. More efficient and saves more time.

Round tool that also sands in corners.

- ▶ Four tools in one: for coarse sanding, fine sanding, delta sanding and polishing. Resulting in low investment costs and savings on working time
- ▶ Durable eccentric bearings, a double-sealed gear unit and a dustproof switch extend the service life of the machine
- ▶ ROTEX rotary motion for convenient polishing – the reduced speed keeps the temperature low and prevents the polish from clouding or spraying off
- ▶ FastFix sanding pad system, tool-less

Technical data

| | |
|--|---------------|
| Power consumption (W) | 400 |
| ROTEX rotary motion speed (min ⁻¹) | 260 – 520 |
| Eccentric motion speed (min ⁻¹) | 3.500 – 7.000 |
| Sanding stroke (mm) | 3 |
| FastFix sanding pad dia. (mm) | 90 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 1,5 |



■ = MMC Multi Material Control electronics

Items included

RO 90 DX FEQ-Plus
FastFix sanding pad, Ø 90 mm (soft-HT), StickFix sanding pad V93, Festool PROTECTOR, in SYSTAINER SYS 2 T-LOC

Order no.

571819

System accessories from page 78



Abrasives from page 93



ROTEX RO 125

Geared eccentric sander ROTEX RO 125



design award
winner
2004

Handy all-rounder.

- ▶ A powerful motor and combination of eccentric and orbital motion removes material three times faster than conventional eccentric sanders
- ▶ Three tools in one for coarse sanding, fine sanding and polishing
- ▶ Healthy, efficient dust extraction with the Jetstream principle
- ▶ FastFix sanding pad system, tool-less



Extremely durable.

With robust eccentric bearings, a double-sealed housing and dustproof switches, the ROTEX can even withstand long periods of continuous use.

Technical data

| | |
|--|---------------|
| Power consumption (W) | 500 |
| ROTEX rotary motion speed (min ⁻¹) | 300 – 600 |
| Eccentric motion speed (min ⁻¹) | 3.000 – 6.000 |
| Sanding stroke (mm) | 3,6 |
| FastFix sanding pad dia. (mm) | 125 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 1,9 |



■ = MMC Multi Material Control electronics

Items included

RO 125 FEQ-Plus
FastFix sanding pad Ø 125 mm (soft-HT), Festool PROTECTOR,
in SYSTEMER SYS 2 T-LOC

Order no.

571779

System accessories from page 79



Abrasives from page 94



ROTEX RO 150

Geared eccentric sander ROTEX RO 150



Short tooling times thanks to FastFix pad change.

Simple, quick and safe. You don't need any other tools for changes apart from your hands. Simply remove the pad, replace and carry on working...

The original 3-in-1 principle with powerful machine concept.

- ▶ Three tools in one for coarse sanding, fine sanding and polishing
- ▶ ROTEX rotary motion for convenient polishing – reduced speed keeps the temperature low, even on the powerful RO 150, prevents the polish from smearing or spraying off
- ▶ FastFix sanding pad system, tool-less
- ▶ MULTI-JETSTREAM 2 principle for efficient dust extraction at maximum sanding capacity

Technical data

| | |
|--|---------------|
| Power consumption (W) | 720 |
| ROTEX rotary motion speed (min ⁻¹) | 320 – 660 |
| Eccentric motion speed (min ⁻¹) | 3.300 – 6.800 |
| Sanding stroke (mm) | 5 |
| FastFix sanding pad dia. (mm) | 150 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 2,3 |




■ = MMC Multi Material Control electronics

| Items included | Order no. |
|---|---------------|
| FastFix sanding pad Ø 150 mm (soft HT), Festool PROTECTOR | |
| RO 150 FEQ in carton | 575066 |
| RO 150 FEQ-Plus in SYSTEMAINER SYS 3 T-LOC | 575069 |

System accessories
from page 80



Abrasives
from page 95



ETSC 125

ETSC 125 cordless random orbital sander



NEW

Brushless EC-TEC motor for a long service life and a high level of efficiency



The ergonomic cordless one-handed sander.

- ▶ Mobile and effortless: Without cable and hose, with perfect ergonomics, low height and a weight of just 1.4 kg
- ▶ Powerful: The 18 V battery pack in combination with the brushless EC-TEC motor ensures power similar to that of a mains-powered tool
- ▶ No interruptions: Thanks to battery packs with a capacity of 3.1 Ah which run for longer than their charge time
- ▶ Unlimited running time: For continuous electrical operation, the battery pack can be replaced with the plug-in mains adapter (included in the set and available as an accessory)



Maximum mobility.

Work effortlessly overhead, vertically or in hard-to-reach areas – without power cable and hose, with perfect ergonomics and a weight of just 1.4 kg (including battery), perfectly balanced weight distribution and low height.

Technical data

| | |
|--|----------------|
| Battery voltage (V) | 18 |
| Li-ion battery capacity (Ah) | 3,1 |
| Idle engine speed (min ⁻¹) | 6.000 – 10.000 |
| Sanding stroke (mm) | 2 |
| Interchangeable sanding pad dia. (mm) | 125 |
| Dust extraction connection dia. (mm) | 27 |
| Weight with Li-ion (kg) | 1,4 |



■ = MMC Multi Material Control electronics

Items included

StickFix sanding pad Ø 125 mm (soft-HT), Festool PROTECTOR, long-life chip collection bag

Order no.

ETSC 125 Li 3,1-Plus

2 x BP 18 Li 3.1 ERGO battery pack, rapid charger TCL 6, in SYSTAINER SYS 2 T-LOC

576899

ETSC 125 Li 3,1-Set

2 x BP 18 Li 3.1 ERGO battery pack, rapid charger TCL 6, ACA 18 V ERGO mains adapter, in SYSTAINER SYS-Combi 2

201527


System accessories from page 81



Abrasives from page 94



Battery and charging technology from page 81 onwards



ETS EC 125

ETS EC 125 eccentric sander



Brushless EC-TEC motor for a long service life and a high level of efficiency



Compact exterior, clever interior.

The ETS EC 125/3 is a favourite for fine sanding and extra-fine sanding in the compact class. As a one-handed sander with an excellent power to weight ratio, it produces an excellent surface quality with a 3 mm sanding stroke.

The perfect finishing sander in the compact class.

- ▶ Longlife thanks to EC technology and sanding pad brake with carbide tip
- ▶ Continuously variable speed and constant speed control under load
- ▶ Ideally positioned push-button prevents inadvertent switching on and off
- ▶ With Jetstream sanding pad for optimum dust extraction

Technical data

| | |
|---|----------------|
| Power consumption (W) | 400 |
| Eccentric motion speed (min ⁻¹) | 6.000 – 10.000 |
| Sanding stroke (mm) | 3 |
| Interchangeable sanding pad dia. (mm) | 125 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 1,2 |



☐ = MMC Multi Material Control electronics

| Items included | Order no. |
|---|---------------|
| StickFix sanding pad Ø 125 mm (soft-HT), operation tool | |
| ETS EC 125/3 EQ in carton | 571895 |
| ETS EC 125/3 EQ-Plus in SYSTAINER SYS 2 T-LOC | 571894 |
| ETS EC 125/3 EQ-Plus-GQ suction hose D27/22x3.5 m AS-GQ (in a SYS 3 T-LOC SYSTAINER), in SYSTAINER SYS 2 T-LOC | 574641 |

System accessories
from page 81



Abrasives
from page 94



ETS EC 150

Random orbit sander ETS EC 150



Brushless EC-TEC motor for a long service life and a high level of efficiency



The perfect finishing sander in the compact class.

- ▶ Stepless speed preselection, constant speed even under load
- ▶ Optimal work protection thanks to vibration and extraction detection
- ▶ Longlife thanks to EC technology and sanding pad brake with carbide tip
- ▶ Compact design and weighing only 1.2 kg for optimal ergonomic work conditions

| Technical data | ETS EC 150/3 | ETS EC 150/5 |
|---|----------------|----------------|
| Power consumption (W) | 400 | 400 |
| Eccentric motion speed (min ⁻¹) | 6.000 – 10.000 | 6.000 – 10.000 |
| Sanding stroke (mm) | 3 | 5 |
| Interchangeable sanding pad dia. (mm) | 150 | 150 |
| Dust extraction connection dia. (mm) | 27 | 27 |
| Weight (kg) | 1,2 | 1,2 |



■ = MMC Multi Material Control electronics

| Items included | Order no. |
|---|---------------|
| operation tool | |
| ETS EC 150/3 EQ StickFix sanding pad Ø 150 mm MULTI-JETSTREAM 2 (extra-soft), in carton | 575032 |
| ETS EC 150/5 EQ StickFix sanding pad Ø 150 mm MULTI-JETSTREAM 2 (soft HT), in carton | 575043 |

Scan the page to discover hidden 3D graphics, videos and images.

Sanding has many sides. We've thought of them all.

At vertical areas or narrow edges – the new ETS EC 150 takes up position in all circumstances: Perfection with handling and sanding result. Thanks to the high-performance and brushless EC-TEC motor, the compact ETS EC 150 is ideal for one-handed and effortless work with simultaneously high demands for smooth running and surface quality.

System accessories
from page 82



Abrasives
from page 95



RUTSCHER RS 100

Orbital sander RUTSCHER RS 100



2001



High material removal rate.

Festool gear-drive sanders with reduction gearing are always designed for heavy-duty material removal and are therefore suitable for sanding old, thick and stubborn coatings over large surfaces.

An ergonomic legend.

- ▶ Reduction gearing for consistently efficient material removal – perfect for sanding off stubborn coatings
- ▶ Vibration stop for smooth operation and safe working conditions
- ▶ Clean working environment – efficient dust extraction for a clear view of the working area and a workplace free from dust
- ▶ Well-balanced centre of gravity for outstanding results and non-tiring work

Technical data

| | |
|--|-----------|
| Power consumption (W) | 520 |
| Idle engine speed (min ⁻¹) | 7.000 |
| No. of strokes (min ⁻¹) | 14.000 |
| Sanding stroke (mm) | 5 |
| Interchangeable sanding pad (mm) | 115 x 221 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 3 |




Items included

RS 100 CQ
StickFix sanding pad 115 x 221 mm, in carton


Order no.

567759

System accessories
from page 83



Abrasives
from page 96



RTSC 400

RTSC 400 cordless orbital sander

NEW

Brushless EC-TEC motor for a long service life and a high level of efficiency



The ergonomic one-handed cordless orbital sander.

- ▶ Mobile and effortless: Without cable and hose, with perfect ergonomics, low height and a weight of just 1.4 kg
- ▶ Powerful: The 18 V battery pack in combination with the brushless EC-TEC motor ensures power similar to that of a mains-powered tool
- ▶ No interruptions: Thanks to battery packs with a capacity of 3.1 Ah which run for longer than their charge time
- ▶ Unlimited running time: For continuous electrical operation, the battery pack can be replaced with the plug-in mains adapter (included in the set and available as an accessory)

Technical data

| | |
|--|----------------|
| Battery voltage (V) | 18 |
| Li-ion battery capacity (Ah) | 3,1 |
| Idle engine speed (min ⁻¹) | 6.000 – 10.000 |
| Sanding stroke (mm) | 2 |
| Interchangeable sanding pad (mm) | 80 x 130 |
| Dust extraction connection dia. (mm) | 27 |
| Weight with Li-ion (kg) | 1,4 |




■ = MMC Multi Material Control electronics

Unique: With battery or cable.


For all applications which require an even longer operating performance, the 18 V battery pack can be replaced with the plug it mains adapter (included in the set and available as an accessory). This creates a mains-powered machine with an unlimited running time for continuous electrical operation in combination with the plug it cable – ideal in conjunction with a Festool mobile dust extractor.

| Items included | Order no. |
|--|---------------|
| StickFix sanding pad 80 x 130 mm, Festool PROTECTOR, long-life chip collection bag | |
| RTSC 400 Li 3,1-Plus 2 x BP 18 Li 3.1 ERGO battery pack, rapid charger TCL 6, in SYSTAINER SYS 2 T-LOC | 576897 |
| RTSC 400 Li 3,1-Set 2 x BP 18 Li 3.1 ERGO battery pack, rapid charger TCL 6, ACA 18 V ERGO mains adapter, in SYSTAINER SYS-Combi 2 | 201513 |

System accessories
from page 84



Abrasives
from page 96



Battery and charging
technology from page 84
onwards



RAS 180

Rotary sander RAS 180



MMC electronics.

Smooth start-up, controlled speed and a temperature control to protect against overload make the RAS ideal for demanding, continuous use.

Large heavy-duty sander.

- ▶ Particularly economical when used over large areas, as the machine is designed for high material removal rates and fast work progress
- ▶ Optimum dust extraction ensures a clean workspace, a clear view and a healthy working environment
- ▶ Health-friendly – anti-static equipment for the reliable removal of clear coats on metal, extraction hood for the perfect extraction of fine dust particles and chips
- ▶ Tool-less sanding pad change

Technical data

| | |
|--|-------------|
| Power consumption (W) | 1.500 |
| Idle engine speed (min ⁻¹) | 800 – 4.000 |
| Interchangeable sanding pad dia. (mm) | 180 |
| Spindle | M14 |
| Dust extraction connection dia. (mm) | 27 |
| Weight (kg) | 4,2 |



= MMC Multi Material Control electronics

Items included

RAS 180 E

StickFix sanding pad Ø 180, extraction hood, StickFix abrasive discs, operation tool, in carton

Order no.

570774

System accessories
from page 85



Abrasives
from page 96





Designed for continuous operation.

- ▶ Extremely robust, durable and reliable
- ▶ Ideal for heavy duty applications
- ▶ Perfect dust extraction
- ▶ Low vibrations levels

The extremely robust design provides durability, the innovative IAS 3 system ensures perfect dust extraction and low vibration levels and lower operating noises for a healthy working environment.

Three times the benefits – the Festool IAS 3 system.

The unique IAS 3 system combines three functions in one hose: compressed air supply, exhaust air extraction and dust extraction. Sanding dust and exhaust air are kept away from the working area, the surface remains clean and the resulting surface finish is excellent. The compressed air tool operates more quietly due to sound absorption elements in the hose. An intelligently designed exhaust air system prevents the discharge of cold air onto the hands and wrists and makes your work more enjoyable and healthier.



- 1 – Compressed air supply
- 2 – Exhaust air extraction
- 3 – Dust extraction

LEX 3 77

Compressed air eccentric sander LEX 3 77



For extreme durability.

For smooth processes free of machine failures and maintenance.

For surface finishing.

- ▶ Extremely sturdy design ensures a long service life, minimal servicing requirements and high cost savings
- ▶ Pleasant operating noise, low vibration levels and safe dispersion of exhaust air through a compressed air hose protects the health of the user
- ▶ Sanding pad brake reduces sanding errors when setting down the machine, thereby avoiding rework and additional costs
- ▶ Low compressed air consumption ensures high cost savings

Technical data

| | |
|---|--------|
| Operating pressure (flow pressure) (bar) | 6 |
| No. of strokes (min ⁻¹) | 21.000 |
| Eccentric motion speed (min ⁻¹) | 10.500 |
| Sanding stroke (mm) | 2,5 |
| Vibration emission value Ah (single-axle) (m/s ²) | 0,8 |
| Vibration emissions value Ah (three-axle) (m/s ²) | 1,9 |
| Air consumption at rated load (l/min) | 270 |
| Sanding pad dia. (mm) | 77 |
| Sound pressure level (dB(A)) | 72 |
| Weight (kg) | 0,8 |



Items included

LEX 3 77/2,5
StickFix sanding pad Ø 77 mm W-HT (soft), operation tool, in carton

Order no.

691131

The IAS 3 connection system is required to operate the compressed air sanders.

System accessories from page 86



Abrasives from page 93



LEX 3 125

Compressed air eccentric sander LEX 3 125



Saves compressed air without affecting results.

- ▶ Low compressed air consumption ensures high cost savings
- ▶ Low vibration levels and a pleasant operating noise protect the user's health
- ▶ Simplifies permanent dust extraction, guarantees the best working results and protects the user's health when combined with the IAS 3 light hose

| Technical data | LEX 3 125/3 | LEX 3 125/5 |
|---|-------------|-------------|
| Operating pressure (flow pressure) (bar) | 6 | 6 |
| No. of strokes (min ⁻¹) | 19.000 | 19.000 |
| Eccentric motion speed (min ⁻¹) | 9.500 | 9.500 |
| Sanding stroke (mm) | 3 | 5 |
| Vibration emission value Ah (single-axle) (m/s ²) | 1,1 | 1,1 |
| Vibration emissions value Ah (three-axle) (m/s ²) | 3,6 | 4,2 |
| Air consumption at rated load (l/min) | 290 | 290 |
| Sound pressure level (dB[A]) | 70 | 70 |
| Sanding pad dia. (mm) | 125 | 125 |
| Weight (kg) | 1 | 1 |



No possibility of confusion.

Clearly visible stroke indicator on the dead-man switch of all LEX 3 models makes it easy to select the correct machine.

| Items included | Order no. |
|--|-----------|
| operation tool, in carton | |
| LEX 3 125/3 StickFix sanding pad Ø 125 mm (extra soft) | 691140 |
| LEX 3 125/5 StickFix sanding pad Ø 125 mm (soft-HT) | 691141 |

The IAS 3 connection system is required to operate the compressed air sanders.

System accessories
from page 86



Abrasives
from page 94



LEX 3 150

Compressed air eccentric sander LEX 3 150



Scan the page to discover hidden 3D graphics, videos and images.

Safe and healthy.

The non-slip soft grip cap on the LEX 3 provides a secure hold. Dust extraction with the MULTI-JETSTREAM 2 principle keeps the air and workpiece clean.

Stops vibrations. Increases efficiency.

- ▶ Precise – sanding pad brake ensures a clean pattern
- ▶ Low compressed air consumption ensures high cost savings
- ▶ Perfect dust extraction and economic abrasive consumption – thanks to the high-quality sanding pad with MULTI-JETSTREAM 2 principle
- ▶ Low vibration levels and a pleasant operating noise protect the user's health

| Technical data | LEX 3 150/3 | LEX 3 150/5 | LEX 3 150/7 |
|---|-------------|-------------|-------------|
| Operating pressure (flow pressure) (bar) | 6 | 6 | 6 |
| No. of strokes (min ⁻¹) | 20.000 | 20.000 | 20.000 |
| Eccentric motion speed (min ⁻¹) | 10.000 | 10.000 | 10.000 |
| Sanding stroke (mm) | 3 | 5 | 7 |
| Vibration emission value Ah (single-axle) (m/s ²) | 2,1 | 2,7 | 3,2 |
| Vibration emissions value Ah (three-axle) (m/s ²) | 3,7 | 3,9 | 5,8 |
| Air consumption at rated load (l/min) | 290 | 290 | 310 |
| Sound pressure level (dB[A]) | 72 | 72 | 76 |
| Sanding pad dia. (mm) | 150 | 150 | 150 |
| Weight (kg) | 1 | 1 | 1 |




| Items included | Order no. |
|--|---------------|
| operation tool, in carton | |
| LEX 3 150/3 StickFix sanding pad Ø 150 mm MULTI-JETSTREAM 2 (extra-soft) | 574996 |
| LEX 3 150/5 StickFix sanding pad Ø 150 mm MULTI-JETSTREAM 2 (soft HT) | 575081 |
| LEX 3 150/7 StickFix sanding pad Ø 150 mm MULTI-JETSTREAM 2 (soft HT) | 575077 |

The IAS 3 connection system is required to operate the compressed air sanders.

System accessories
from page 86



Abrasives
from page 95



LRS 93

Compressed air orbital sander LRS 93



Perfect for flat surfaces.

- ▶ Machine is easy to guide
- ▶ Variable speed preselection
- ▶ Reduced vibrations for maximum working comfort
- ▶ Robust motor for a longer lifespan

Technical data

| | |
|--|----------|
| Operating pressure (flow pressure) (bar) | 6 |
| No. of strokes (min ⁻¹) | 14.000 |
| Sanding stroke (mm) | 4 |
| Air consumption at rated load (l/min) | 310 |
| Sanding pad StickFix (mm) | 93 x 175 |
| Weight (kg) | 1,5 |



Items included

LRS 93M
StickFix sanding pad 93 x 175 mm, bottle of cleaning and lubricating oil LFC 9022 (50 ml), in carton

Order no.

574811




Vibration stop


Less stress on your hands and wrists. VS balancing reduces vibrations and oscillations, and is kind to both you and your machine.

The IAS 3 connection system is required to operate the compressed air sanders.

System accessories from page 88



Abrasives from page 96



LRS 400

Compressed air orbital sander LRS 400



Long sander for large surfaces.

- ▶ Lightweight and handy despite its size
- ▶ High material removal rate on large, flat surfaces
- ▶ Highly effective dust extraction
- ▶ Softgrip handle

Easy guidance.

All compressed air orbital sanders are easy to guide, both with one or two hands. The Softgrip and the additional handle on the LRS 400 give you complete control of the machine.

Technical data

| | |
|--|----------|
| Operating pressure (flow pressure) (bar) | 6 |
| No. of strokes (min ⁻¹) | 14.000 |
| Sanding stroke (mm) | 4 |
| Air consumption at rated load (l/min) | 390 |
| Sanding pad StickFix (mm) | 80 x 400 |
| Weight (kg) | 2,1 |



Items included


LRS 400
StickFix sanding pad 80 x 400 mm (soft), bottle of cleaning and lubricating oil LFC 9022 (50 ml), in carton

Order no.


574813

The IAS 3 connection system is required to operate the compressed air sanders.

System accessories
from page 88



Abrasives
from page 97



Detail of success.

Festool creates a perfect interaction between machine, polishing pad, foam pad and abrasive: for sensitive working and gleaming results on different materials from the word go, without any rework. For high-gloss paints, UV clear coats, clear coats.



SHINEX RAP 150

Rotary polisher SHINEX RAP 150



Scan the page to discover hidden 3D graphics, videos and images.

Precise application of power.

Perfect power transfer thanks to the minimum distance between the tool and pad and the various grip positions of the SHINEX RAP 150.

All-purpose genius.

- ▶ Variable speed trigger for sensitive starting and acceleration
- ▶ 2-speed gear unit is powerful, sturdy and durable across the entire speed range
- ▶ Long service life – a temperature-dependent overload protection and filter catcher protect the machine
- ▶ Work for longer periods – only weighs 2.1 kg, ergonomic design and perfectly balanced


| Technical data | RAP 150-14 FE | RAP 150-21 FE |
|--|---------------|---------------|
| Power consumption (W) | 1.200 | 1.200 |
| Idle engine speed (min ⁻¹) | 600 – 1.400 | 900 – 2.100 |
| Max. polishing pad dia. (mm) | 150 | 150 |
| Spindle | M14 | M14 |
| Weight (kg) | 2,1 | 2,1 |




= MMC Multi Material Control electronics

| Items included | Order no. |
|---|---------------|
| additional side-mounted hand grip, StickFix polishing pad Ø 150 mm | |
| RAP 150-14 FE in carton | 570809 |
| RAP 150-21 FE in carton | 570811 |
| RAP 150-14 FE-Set Automotive spot sander, polish MPA 5010/1, additional side-mounted hand grip StickFix polishing pad Ø 150 mm, 2 x PoliStick Ø 150 mm premium sheep- skin, microfibre polish drapery, MPA 11010/1 polish 0.5l, PoliStick foam polishing pad, Ø 150 mm, white, fine, honeycombed, Finish cleaner (500 ml), Mixed pack of self-adhesive sanding discs, in SYSTAINER SYS MAXI | 570827 |
| RAP 150-21 FE-Set Automotive spot sander, polish MPA 5010/1, additional side-mounted hand grip StickFix polishing pad Ø 150 mm, 2 x PoliStick Ø 150 mm premium sheep- skin, microfibre polish drapery, MPA 11010/1 polish 0.5l, PoliStick foam polishing pad, Ø 150 mm, white, fine, honeycombed, Finish cleaner (500 ml), Mixed pack of self-adhesive sanding discs, in SYSTAINER SYS MAXI | 570828 |

System accessories from page 99



Polishing accessories from page 102



POLLUX 180

Rotary polisher POLLUX 180



Powerhouse with high coverage capacity.

- ▶ Exceptional cooling in lower speed range – allows work under heavy loads
- ▶ Controlled speed, stepless speed preselection and smooth start-up for adaptation to the working surface
- ▶ Accelerator switch, speed preselection, controlled speed, smooth start-up
- ▶ Ergonomic dome grip and perfect weight distribution for relaxed work

Technical data

| | |
|--|-------------|
| Power consumption (W) | 1.500 |
| Idle engine speed (min ⁻¹) | 800 – 2.400 |
| Max. polishing pad dia. (mm) | 180 |
| Spindle | M14 |
| Weight (kg) | 3,6 |



= MMC Multi Material Control electronics

When faced with demanding tasks.

The POLLUX 180 E enables perfect adaptation to different materials and surfaces. The motor speed always remains constant thanks to the MMC electronics and allows you to work evenly without damaging the workpiece and avoid time-consuming reworking.

Items included

POLLUX 180 E

StickFix polishing pad Ø 180 mm, additional side-mounted hand grip, in carton

Order no.

570734

System accessories from page 99




Polishing accessories from page 102



System accessories




ROTEX RO 90 DX



Accessories for geared eccentric sander ROTEX RO 90 DX

| Denomination | Explanation | Order no. |
|--|---|-----------|
| 1 Sanding pad SSH-GE-STF-R090 DX | suitable for abrasive 93 V, delta sanding pad, plate without interchangeable sanding pad, for attaching StickFix sanding pad, soft and hard, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 496802 |
| 2 Sanding pad StickFix, soft SSH-STF-V93/6-W/2 | for DX 93 and RO 90 DX, with snap stud, StickFix, qty. in pack 2 piece(s), in self-service display pack | 488715 |
| Sanding pad StickFix, hard SSH-STF-V93/6-H/2 | for DX 93 and RO 90 DX, with snap stud, StickFix, qty. in pack 2 piece(s), in self-service display pack | 488716 |
| 3 FastFix sanding pad dia ST-STF D90/7 FX H-HT | hard version, Fastener resistant to high temperatures, for plain surfaces and narrow edges, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 495623 |
| 4 FastFix sanding pad dia ST-STF D90/7 FX W-HT | soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 496804 |
| 5 Protector FESTOOL 90FX | for RO 90 DX, for protecting the sanding pad and workpiece, in self-service display pack | 496801 |
| 6 Interface pad IP-STF-D90/6 | as damping element between sanding disc and sanding pad, Interface pad D 90 mm, height 15 mm, qty. in pack 1 piece(s), diameter 90 mm, in self-service display pack | 497481 |
| 7 Abrasives | from page 93 | |
| 8 SYSTAINER T-LOC SYS-STF-D77/D90/93V | with insert for Ø 90 mm abrasives and 93V abrasives, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 8, SYSTAINER size SYS 1 T-LOC | 497687 |
| 9 FastFix polishing pad PT-STF-D90 FX-R090 | for RO 90 DX, for holding polishing accessories with dia. 80 mm, Polishing edges, Polishing small surfaces, diameter 75 mm, in self-service display pack | 495625 |
| 10 Polishing agents | from page 100 | |


System accessories



Accessories for geared eccentric sander ROTEX RO 125

| Denomination | Explanation | Order no. |
|--|---|---------------|
| 1 FastFix sanding pad dia ST-STF D125/8 FX-H-HT | hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 492127 |
| 2 FastFix sanding pad dia ST-STF D125/8 FX-W-HT | soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 492125 |
| 3 FastFix sanding pad dia ST-STF D125/8 FX-SW | ultra-soft version, elastic structure, for heavy roundings and cambers, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 492126 |
| 4 Protector FESTOOL 125FX | for RO 125 FEQ, for protecting the sanding pad and workpiece, in self-service display pack | 493912 |
| 5 Interface pad IP-STF-D120/8-J | for sanding contoured parts and fine-sanding parts with eccentric sander Ø 125 mm, as damping element between sanding disc and sanding pad, JETSTREAM, height 15 mm, diameter 120 mm, hole circle diameter 90 mm, qty. in pack 1 piece(s), in self-service display pack | 492271 |
| 6 Abrasives | from page 93 | |
| 7 SYSTAINER T-LOC SYS-STF D125 | with insert for abrasives Ø 125 mm, dimensions [L x W x H] 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | 497685 |
| 8 FastFix polishing pad PT-STF-D125 FX-RO125 | for RO 125 FEQ, fits polishing accessories, diameter 115 mm, height 10 mm, in self-service display pack | 492128 |
| 9 Polishing agents | from page 100 | |


System accessories



Accessories for geared eccentric sander ROTEX RO 150

| Denomination | Explanation | Order no. |
|--|---|-----------|
| 1 FastFix sanding pad dia ST-STF D150/MJ2-FX-H-HT | for RO 150, hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 202463 |
| 2 FastFix sanding pad dia ST-STF D150/MJ2-FX-W-HT | for RO 150, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 202461 |
| 3 FastFix sanding pad dia ST-STF D150/MJ2-FX-SW | for RO 150, ultra-soft version, elastic structure, for heavy roundings and cambers, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread FastFix, qty. in pack 1 piece(s), in self-service display pack | 202462 |
| 4 Protector FESTOOL 150FX | for RO 150 FEQ, for protecting the sanding pad and workpiece, in self-service display pack | 493913 |
| 5 Interface pad IP-STF D150/MJ2-5/2 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on bodies and similarly shaped components, diameter 145 mm, height 5 mm, qty. in pack 2 piece(s), in self-service display pack | 203348 |
| Interface pad IP-STF D150/MJ2-15/1 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on curved components, diameter 145 mm, height 15 mm, in self-service display pack | 203351 |
| 6 Abrasives | from page 93 | |
| 7 SYSTAINER T-LOC SYS-STF D150 | with insert for abrasives Ø 150 mm, dimensions [L x W x H] 396 x 296 x 210 mm, number of compartments 10, SYSTAINER size SYS 3 T-LOC | 497690 |
| 8 FastFix polishing pad PT-STF-D150 FX | for RO 150 FEQ, fits polishing accessories, diameter 135 mm, height 10 mm, in self-service display pack | 496151 |
| 9 Additional hand grip ZG-RAS/RO | for RO 150, RAS, WTS 150, in carton | 487865 |
| Handle BG-RO 150 | for RO 150 FEQ, in self-service display pack | 495188 |
| 10 Polishing agents | from page 100 | |

System accessories



Accessories for ETSC 125, ETS EC 125 random orbit sanders

| Denomination | Explanation | Order no. |
|--|---|---------------|
| 1 Sanding pad ST-STF 125/8-M4-J W-HT | for ES 125, ETS 125, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, for robust use with grit up to P220, JETSTREAM, connecting thread M4, hole circle diameter 90 mm, qty. in pack 1 piece(s), in self-service display pack | 492280 |
| Sanding pad ST-STF 125/8-M4-J SW | for ES 125, ETS 125, ultra-soft version, elastic structure, for heavy roundings and cambers, JETSTREAM, connecting thread M4, hole circle diameter 90 mm, qty. in pack 1 piece(s), in self-service display pack | 492282 |
| 2 Sanding pad ST-STF 125/8-M8-J H | for ETS EC 125, LEX 125, hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492284 |
| Sanding pad ST-STF 125/8-M8-J W-HT | for ETS EC 125, LEX 125, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492286 |
| Sanding pad ST-STF 125/8-M8-J SW | for ETS EC 125, LEX 125, ultra-soft version, elastic structure, for heavy roundings and cambers, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492288 |
| 3 Interface pad IP-STF-D120/8-J | for sanding contoured parts and fine-sanding parts with eccentric sander Ø 125 mm, as damping element between sanding disc and sanding pad, JETSTREAM, height 15 mm, diameter 120 mm, hole circle diameter 90 mm, qty. in pack 1 piece(s), in self-service display pack | 492271 |
| 4 Abrasives | from page 93 | |
| 5 SYSTAINER T-LOC SYS-STF D125 | with insert for abrasives Ø 125 mm, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | 497685 |
| 6 Long-life chip collection bag SB-Longlife RTS/DTS/ETS | for ETS 125, ETSC 125, RTS 400, RTSC 400, DTS 400, DTSC 400, for holding dust and for dust-free disposal of the extracted product, can be discharged multiple times and is wear resistant thanks to high-strength, durable nonwoven polyester, in self-service display pack | 201693 |
| 7 Battery pack BP 18 Li 3,1 Ergo | for RTSC 400, DTSC 400, ETSC 125 cordless sanders, not suitable for all other cordless machines, ergonomic, lightweight design, tensioner 18 V, capacity 3,1 Ah, weight 0,4 kg, in self-service display pack | 202499 |
| Mains adapter ACA 220-240/18V Ergo | for RTSC 400, DTSC 400, ETSC 125 cordless sanders, not suitable for all other cordless machines, for continuous electrical operation of the RTSC 400, DTSC 400, ETSC 125 cordless sanders, ergonomic, lightweight design, plug it power cable (4 m), input voltage 220 – 240 V, tensioner 18 – 20 V, rated power 150 W, weight 0,3 kg, in self-service display pack | 202501 |

System accessories



Accessories for ETS EC 150 eccentric sanders

| Denomination | Explanation | Order no. |
|---|---|---------------|
| 1 Sanding pad ST-STF D150/MJ2-M8-H-HT | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202460 |
| Sanding pad ST-STF D150/MJ2-M8-W-HT | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202458 |
| Sanding pad ST-STF D150/MJ2-M8-SW | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, ultra-soft version, elastic structure, for heavy roundings and cambers, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202459 |
| 2 Interface pad IP-STF D150/MJ2-5/2 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on bodies and similarly shaped components, diameter 145 mm, height 5 mm, qty. in pack 2 piece(s), in self-service display pack | 203348 |
| Interface pad IP-STF D150/MJ2-15/1 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on curved components, diameter 145 mm, height 15 mm, in self-service display pack | 203351 |
| 3 Abrasives | from page 93 | |
| 4 SYSTAINER T-LOC SYS-STF D150 | with insert for abrasives Ø 150 mm, number of compartments 10, SYSTAINER size SYS 3 T-LOC | 497690 |
| SYSTAINER T-LOC SYS-STF D150 4S | with insert for abrasives Ø 150 mm, number of compartments 8, abrasives are stored for sanding in 4 steps system | 497821 |

System accessories




RUTSCHER RS 100



Accessories for RUTSCHER RS 100

| Denomination | Explanation | Order no. |
|---|--|-----------|
| 1 Sanding pad StickFix SSH-STF-115x221/10 RS 1 C | for RS 100 C, RS 1 C, StickFix adhesive layer for quick change of sanding pad, min. length 115 mm, width 221 mm, dimensions 115 x 221 mm, in self-service display pack | 488226 |
| 2 Abrasives | from page 93 | |

System accessories



Accessories for RTSC 400 orbital sander

| Denomination | Explanation | Order no. |
|--|---|---------------|
| 1 Sanding pad StickFix SSH-STF-80x130/8 | for RS 4, perforated with eight suction holes, min. length 80 mm, width 130 mm, dimensions 80 x 130 mm, in self-service display pack | 483906 |
| Sanding pad SSH-80x130/8 | for RS 4, for abrasives for clamping, width 130 mm, min. length 80 mm, dimensions 80 x 130 mm, in self-service display pack | 491366 |
| Sanding pad StickFix SSH-STF-80x130/12 | for RTS 400, RS 400, RTSC 400, perforated with 12 suction holes, width 130 mm, min. length 80 mm, dimensions 80 x 130 mm, in self-service display pack | 489252 |
| Sanding pad SSH-STF-Delta100x150/7 | for DTS 400, DS 400, DTSC 400, for sanding even in corners, width 150 mm, min. length 100 mm, dimensions 100 x 150 mm, in self-service display pack | 493723 |
| 2 Abrasives | from page 93 | |
| 3 SYSTAINER T-LOC SYS-STF 80x133 | with insert for abrasives 80x133 mm, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 6, SYSTAINER size SYS 1 T-LOC | 497684 |
| SYSTAINER T-LOC SYS-STF Delta 100x150 | with insert for abrasives STF Delta 100x150, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | 497686 |
| SYSTAINER T-LOC SYS-STF-D77/D90/93V | with insert for Ø 90 mm abrasives and 93V abrasives, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 8, SYSTAINER size SYS 1 T-LOC | 497687 |
| 4 Long-life chip collection bag SB-Longlife RTS/DTS/ETS | for ETS 125, ETSC 125, RTS 400, RTSC 400, DTS 400, DTSC 400, for holding dust and for dust-free disposal of the extracted product, can be discharged multiple times and is wear resistant thanks to high-strength, durable nonwoven polyester, in self-service display pack | 201693 |
| 5 Protector PR RTS-R 80x133 | for RTS 400 REQ, RTSC 400, for smooth sanding along window panes, frames and panelling, for protecting the sanding pad and workpiece, in self-service display pack | 201691 |
| 6 Battery pack BP 18 Li 3,1 Ergo | for RTSC 400, DTSC 400, ETSC 125 cordless sanders, not suitable for all other cordless machines, ergonomic, lightweight design, tensioner 18 V, capacity 3,1 Ah, weight 0,4 kg, in self-service display pack | 202499 |
| Mains adapter ACA 220-240/18V Ergo | for RTSC 400, DTSC 400, ETSC 125 cordless sanders, not suitable for all other cordless machines, for continuous electrical operation of the RTSC 400, DTSC 400, ETSC 125 cordless sanders, ergonomic, lightweight design, plug it power cable (4 m), input voltage 220 – 240 V, tensioner 18 – 20 V, rated power 150 W, weight 0,3 kg, in self-service display pack | 202501 |

System accessories




Accessories for rotary sander RAS 180

| Denomination | Explanation | Order no. |
|-----------------------------------|---|-----------|
| 1 Sanding pad ST-STF-D180/0-M14 W | for RAS 180, soft version, for universal use on plain and arced surfaces, connecting thread M14, in self-service display pack | 485253 |
| Sanding pad ST-D180/0-M14/2F | for RAS 180, for fibre discs Ø 180 mm, connecting thread M14, in self-service display pack | 485296 |
| 2 Abrasives | from page 93 | |
| 3 Additional hand grip ZG-RAS/RO | for RO 150, RAS, WTS 150, in carton | 487865 |

Accessories for rotary sander RAS 115

| Denomination | Explanation | Order no. |
|-------------------------------------|---|-----------|
| Sanding pad ST-STF-D115/0-M14 W | for RAS 115, soft version, for universal use on plain and arced surfaces, connecting thread M14, in self-service display pack | 484173 |
| Sanding pad ST-STF-D115/0-M14 H | for RAS 115 hard version, high edge solidity, for plain surfaces and narrow edges, connecting thread M14, in self-service display pack | 484172 |
| Sanding pad ST-D115/0-M14/2F | for RAS 115, for fibre discs and Longlife fibre discs Ø 115 mm, clamping nut, connecting thread M14, in self-service display pack | 485298 |
| Flexible sanding pad ST-D115/0-EL | for RAS 115, for fibre discs and Longlife fibre discs Ø 115 mm, without clamping nut, connecting thread M14, in self-service display pack | 439580 |
| Clamping nut SM-M14/D115 | for RAS 115, for securing Fiberfix sanding discs, in a bag | 439581 |
| Brush insert for RAS AHP-RAS D115/2 | for RAS 115, with plastic bristles, qty. in pack 2 piece(s), in a bag | 484727 |
| Brush insert for RAS AHM-RAS D115 | for RAS 115, with metal bristles, qty. in pack 1 piece(s), in a bag | 484728 |
| Circular brush RB-D115/M14 RAS 115 | for RAS 115, braided, for removal of paint and rust and cleaning surfaces, in self-service display pack | 485096 |
| Cup brush TB-D80/M14 RAS 115 | for RAS 115, for removal of rust and slag to obtain a metallically pure surface, in self-service display pack | 485097 |
| Cup brush TB-D65/M14 RAS 115 | for RAS 115, braided, for removal of paint and rust and cleaning surfaces, in self-service display pack | 485099 |
| Abrasives | from page 93 | |


System accessories



Accessories for LEX 3 77, LEX 3 125, LEX 3 150 compressed air eccentric sanders

| Denomination | Explanation | Order no. |
|--|---|-----------|
| 1 Interface pad IP-STF-D77/6 | for LEX 3 77, as damping element between sanding disc and sanding pad, height 10 mm, diameter 77 mm, qty. in pack 2 piece(s), in self-service display pack | 498818 |
| Interface pad IP-STF-D120/8-J | for sanding contoured parts and fine-sanding parts with eccentric sander Ø 125 mm, as damping element between sanding disc and sanding pad, JETSTREAM, height 15 mm, diameter 120 mm, hole circle diameter 90 mm, qty. in pack 1 piece(s), in self-service display pack | 492271 |
| Interface pad IP-STF D150/MJ2-5/2 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on bodies and similarly shaped components, diameter 145 mm, height 5 mm, qty. in pack 2 piece(s), in self-service display pack | 203348 |
| Interface pad IP-STF D150/MJ2-15/1 | for eccentric sander with diameter of 150 mm, as damping element between sanding disc and sanding pad, MULTI-JETSTREAM 2, optimal thickness for sanding work on curved components, diameter 145 mm, height 15 mm, in self-service display pack | 203351 |
| 2 Sanding pad ST-STF-D77/6-M5 W | for LEX 3 77, soft version, for tough and universal use, diameter 77 mm, connecting thread M5, qty. in pack 1 piece(s), in self-service display pack | 498694 |
| Sanding pad ST-STF 125/8-M8-J H | for ETS EC 125, LEX 125, hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492284 |
| Sanding pad ST-STF 125/8-M8-J W-HT | for ETS EC 125, LEX 125, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492286 |
| Sanding pad ST-STF 125/8-M8-J SW | for ETS EC 125, LEX 125, ultra-soft version, elastic structure, for heavy roundings and cambers, JETSTREAM, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 492288 |
| Sanding pad ST-STF D150/MJ2-M8-SW | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, ultra-soft version, elastic structure, for heavy roundings and cambers, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202459 |
| Sanding pad ST-STF D150/MJ2-M8-W-HT | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, soft version, Fastener resistant to high temperatures, for universal use on plain and arced surfaces, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202458 |
| Sanding pad ST-STF D150/MJ2-M8-H-HT | for ETS 150, ETS EC 150, LEX 150 and WTS 150/7, hard version, Fastener resistant to high temperatures, high edge solidity, for plain surfaces and narrow edges, MULTI-JETSTREAM 2, diameter 150 mm, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 202460 |
| Sanding pad ST-STF-D185/16-M8 W | soft version, for universal use on plain and arced surfaces, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 490514 |
| Sanding pad ST-STF-D185/16-M8 SW | ultra-soft version, elastic structure, for heavy roundings and cambers, connecting thread M8, qty. in pack 1 piece(s), in self-service display pack | 490526 |
| 3 Abrasives | from page 93 | |


System accessories



Accessories for LEX 3 77, LEX 3 125, LEX 3 150 compressed air eccentric sanders

| Denomination | Explanation | Order no. |
|---|---|-----------|
| 4 SYSTAINER T-LOC SYS-STF-D77/D90/93V | with insert for Ø 90 mm abrasives and 93V abrasives, dimensions [L x W x H] 396 x 296 x 105 mm, number of compartments 8, SYSTAINER size SYS 1 T-LOC | 497687 |
| SYSTAINER T-LOC SYS-STF D125 | with insert for abrasives Ø 125 mm, dimensions [L x W x H] 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | 497685 |
| SYSTAINER T-LOC SYS-STF D150 | with insert for abrasives Ø 150 mm, dimensions [L x W x H] 396 x 296 x 210 mm, number of compartments 10, SYSTAINER size SYS 3 T-LOC | 497690 |
| 5 Guide control black powder HB-Set | for visibly checking surfaces to be sanded, hand sanding block, 2 guide control black powder cartridges (each 30 g), in carton | 495939 |
| Refillable cartridge 2 x 30 g | refill for the guide control black powder HB set (2 x 30 g), in carton | 495940 |
| 6 IAS hoses IAS 3 | from page 89 | |
| IAS adapter IAS 3-SD | for LEX 3, LEX 2, LRS, for connecting a Festool compressed air sander directly to a compressed air line (without dust extraction), length 90 mm, in carton | 497214 |
| Compressed air hose D 12,4 x 5 m | for LEX 3, LEX 2, LRS, IAS 3-SD, the IAS 3-SD adapter is necessary for connection to the machine, length 5 m, in carton | 497215 |
| IAS double adapter IAS 3-DA-CT | for LEX 3, LEX 2, LRS, CT extractor (not CT 11/MINI/MIDI), for simultaneously connecting two air tools with IAS 2 and/or IAS 3 adapter to a Festool dust extractor, Not suitable for M dust extractor, in carton | 497284 |
| Adapter AD-IAS/D 36 | note: if IAS 2/IAS 3 hoses are used without this adapter to extract dirt directly, the hoses and air tools may be damaged by dirt deposits in connecting parts, for use with D 36 suction nozzles with IAS 2/IAS 3 hoses, in bag | 488418 |
| Adapter IAS-ZA | for central extraction units, boom arms manufactured by Rupes, IVO and Herkules, and Rupes power boxes, rubber bushing for connection of IAS 2/IAS 3 air tools via an IAS 2/IAS 3 connection, exterior Ø 59/75 mm, interior Ø 49/57 mm, in carton | 489222 |
| Connecting sleeve IAS 3-B1 | for LEX 3, LEX 2, LRS, for connecting an IAS 3 or IAS 3 light hose to an SRM 70/SRM 312 B1 extractor, in self-service display pack | 499024 |
| Adapter IAS 3-FA | for LEX 3, LEX 2, LRS, for connecting an IAS 3 or IAS 3 light hose to an EAA power box or Herkules exhaust turbine, sleeve diameter 47,5 – 51,8 mm, in self-service display pack | 499025 |
| IAS adapter IAS-S-ZA/Herkules | for connection of IAS 2/IAS 3 suction hoses to Herkules central suction system, with closing slide, in carton | 490605 |
| Cleaning and lubricating oil LFC 9022/50 | for LEX, LRS, special oil for compressed air preparation, 50 ml, in plastic bottle | 201077 |
| Cleaning and lubricating oil LFC 9022/1000 | for LEX, LRS, special oil for compressed air preparation, in plastic bottle | 201076 |
| 7 CT mobile dust extractors | from page 106 | |

System accessories



Accessories for compressed air orbital sanders LRS 93, LRS 400


| Denomination | Explanation | Order no. |
|---|---|---------------|
| 1 Sanding pad StickFix SSH-STF-93x175/8 | for RS 300, RS 3, LRS 93, StickFix adhesive layer for quick change of sanding pad, width 175 mm, min. length 93 mm, dimensions 93 x 175 mm, in self-service display pack | 483905 |
| Sanding pad SSH-93x175/8 | for RS 300, RS 3, LRS 93, for abrasives for clamping, width 175 mm, min. length 93 mm, dimensions 93 x 175 mm, in self-service display pack | 489630 |
| StickFix iron sanding pad SSH-STF-V93x266/14 | for RS 300, RS 3, LRS 93, pressing iron sanding pad version, width 266 mm, min. length 93 mm, dimensions 93 x 266 mm, in self-service display pack | 486418 |
| Sanding pad SSH-STF-80x400/17 | for LRS 400, HSK 80 x 400, HSK 80 x 200, soft, dimensions 80 x 400 mm, qty. in pack 1 piece(s), in self-service display pack | 493140 |
| 2 Abrasives | from page 93 | |
| 3 IAS hoses IAS 3 | from page 89 | |
| IAS adapter IAS 3-SD | for LEX 3, LEX 2, LRS, for connecting a Festool compressed air sander directly to a compressed air line (without dust extraction), length 90 mm, in carton | 497214 |
| Compressed air hose D 12,4 x 5 m | for LEX 3, LEX 2, LRS, IAS 3-SD, the IAS 3-SD adapter is necessary for connection to the machine, length 5 m, in carton | 497215 |
| IAS double adapter IAS 3-DA-CT | for LEX 3, LEX 2, LRS, CT extractor (not CT 11/MINI/MIDI), for simultaneously connecting two air tools with IAS 2 and/or IAS 3 adapter to a Festool dust extractor, Not suitable for M dust extractor, in carton | 497284 |
| Adapter AD-IAS/D 36 | note: if IAS 2/IAS 3 hoses are used without this adapter to extract dirt directly, the hoses and air tools may be damaged by dirt deposits in connecting parts, for use with D 36 suction nozzles with IAS 2/IAS 3 hoses, in bag | 488418 |
| Adapter IAS-ZA | for central extraction units, boom arms manufactured by Rupes, IVO and Herkules, and Rupes power boxes, rubber bushing for connection of IAS 2/IAS 3 air tools via an IAS 2/IAS 3 connection, exterior Ø 59/75 mm, interior Ø 49/57 mm, in carton | 489222 |
| Connecting sleeve IAS 3-B1 | for LEX 3, LEX 2, LRS, for connecting an IAS 3 or IAS 3 light hose to an SRM 70/SRM 312 B1 extractor, in self-service display pack | 499024 |
| Adapter IAS 3-FA | for LEX 3, LEX 2, LRS, for connecting an IAS 3 or IAS 3 light hose to an EAA power box or Herkules exhaust turbine, sleeve diameter 47,5 – 51,8 mm, in self-service display pack | 499025 |
| IAS adapter IAS-S-ZA/Herkules | for connection of IAS 2/IAS 3 suction hoses to Herkules central suction system, with closing slide, in carton | 490605 |
| Cleaning and lubricating oil LFC 9022/50 | for LEX, LRS, special oil for compressed air preparation, 50 ml, in plastic bottle | 201077 |
| Cleaning and lubricating oil LFC 9022/1000 | for LEX, LRS, special oil for compressed air preparation, in plastic bottle | 201076 |
| 4 CT mobile dust extractors | from page 106 | |

System accessories

IAS 3 hoses

| | | Type | Order no. |
|---|---|----------------------|---------------|
|  | IAS hose for LEX 3, LEX 2, LRS, antistatic, in accordance with DIN IEC 312, bleeder resistor (DIN IEC 312) <1 mΩ/m, temperature-resistant up to + 70°C, hose dia. 44 mm, in carton | | |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 3,5 m | IAS 3-3500 AS | 497208 |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 5 m | IAS 3-5000 AS | 497209 |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 7 m | IAS 3-7000 AS | 497210 |
| | for connecting a Festool compressed air sander to a Festool energy box, length 10 m | IAS 3-10000 AS | 497211 |
|  | IAS hose for LEX 3, LEX 2, LRS, antistatic, in accordance with DIN IEC 312, bleeder resistor (DIN IEC 312) <1 mΩ/m, temperature-resistant up to + 70°C, hose dia. 37 mm, in carton | | |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 3,5 m | IAS 3 light 3500 AS | 497478 |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 5 m | IAS 3 light 5000 AS | 497213 |
| | for connecting a Festool compressed air sander to a Festool mobile dust extractor or energy box, length 7 m | IAS 3 light 7000 AS | 497479 |
| | note: not with combination of CT/SR and ASA, for connecting a Festool compressed air sander to a Festool energy box, length 10 m | IAS 3 light 10000 AS | 497480 |

System accessories



Accessories for manual sanding

| Denomination | Explanation | Order no. |
|-------------------------------|--|-----------|
| 1 Sanding block HSK-A 80x130 | compatible abrasive 80 x 133 mm, adapter for Festool hose, bypass adapter, weight 0,19 kg, in carton | 496962 |
| 2 Sanding block HSK-A 115x226 | compatible abrasive 115 x 228 mm, adapter for Festool hose, bypass adapter, weight 0,28 kg, in carton | 496963 |
| 3 Sanding block HSK-A 80x400 | compatible abrasive 80 x 400 mm, adapter for Festool hose, bypass adapter, weight 0,52 kg, in carton | 496964 |
| 4 Sanding block HSK-A 80x200 | compatible abrasive 80 x 400 mm (halved), adapter for Festool hose, bypass adapter, weight 0,2 kg, in carton | 496965 |
| Sanding block HSK-A-Set | compatible abrasive 80 x 133 mm, 115 x 228 mm, 80 x 400 mm, adapter for Festool hose, HSK-A 80x130, bypass adapter, HSK-A 80x200, HSK-A 80x400, HSK-A 115x226, in carton | 497101 |
| 5 Sanding block HSK-D 150 W | soft, for attaching StickFix Ø 150 mm sanding discs, in self-service display pack | 495965 |
| Sanding block HSK-D 150 H | hard, for attaching StickFix Ø 150 mm sanding discs, in self-service display pack | 495966 |
| 6 Sanding block HSK 80x133 H | hard, for attaching StickFix 80 x 133 mm abrasive sheets, in self-service display pack | 495967 |
| 7 Abrasives | from page 93 | |
| 8 Suction hose D21,5 x 5m HSK | for direct connection (without reducing ring) to hand sanding block with extraction, Diameter 21,5 mm, Length 5 m, in a bag | 495019 |

Impressive not just on paper, but also in the workshop.

You can rely on Festool for the right abrasive for every tool and every application. A single rule applies: the more compatible the abrasive and sanding pad are with the tool, the more efficient and economical the working results will be.

No disc disintegration.

A combination of extremely tear-resistant and flexible synthetic resin bonds the two layers of abrasive grit. This prevents the discs from disintegrating prematurely.

Wear-resistant grit.

The abrasive grain is very hard but also durable. Each grain therefore retains its shape even under the toughest conditions, guaranteeing outstanding material removal.

Extended useful life.

The special combination of abrasive grain, bonding and surface geometry delays clogging of the abrasive. Festool Platin 2, Titan 2 and Granat abrasives have a dust-repellent coating for an even longer useful life.

Even sanding.

The uniform grains ensure a consistent depth of roughness across the abrasive. Resulting in a clean sanding finish, less reworking and, therefore, a considerable time-saving.

Flexible and stable backing material.


Festool uses flexible backing material made from paper, cotton fabric or synthetic fibres, depending on requirements. The backing adheres extremely well to both the paper and the bonding. The material remains extremely flexible and transitions are sanded smooth.

Quick changes with the StickFix system.

Festool abrasives are changed without gluing or clamping: just pull one off and attach the next one. The Velcro system is reliable, does not slip and the discs are easy to peel off.

Improved dust extraction.

Intensive dust extraction by the patented Jetstream and MULTI-JETSTREAM 2 principle increases the service life of the sanding discs.




Abrasives

Achieving the perfect surface finish depends on the smallest of details. All Festool abrasives and sanding pads are adapted perfectly to the relevant sander as well as the overall system.

Abrasives

Granat

P40-3000



Universal for coarse to fine sanding

Sanding:

- Paint systems compliant with VOC regulations
- Water-dilutable clear coats
- Hard clear coats, undercoats such as GRP
- Also suitable for conventional clear coats, filler, paints

Granat Net

P40-220



Perfect for materials that produce a large quantity of dust

Sanding:

- Repair compound
- Filler
- Paint
- Clear coat
- Plaster filler and dispersion filler

Platin 2

S400-4000



For perfect preparation for polishing

Finishing/matting:

- High-gloss paints in preparation for polishing
- Plastics

Vlies


100-1000



For light sanding, cleaning, oiling, waxing

Matting/light sanding of paints and clear coats:

- Lightly sanding old coats of paint before repainting
- Polishing metal



With active dust conveying system – the patented MULTI-JETSTREAM 2 principle*

The MULTI-JETSTREAM 2 principle is defined by the unique interaction between intake air and exhaust air – with optimum dust extraction right up to the edge. An air flow is created which actively transports the sanding dust to the nearest extraction channel. The result: Virtually 100% dust extraction for a consistently high material removal rate, top surface quality and a healthy working environment.

Active dust conveying concept

The 48 suction holes collect the dust and transport it actively to the exhaust air channels. Dust is extracted from every point on the pad – right up to the edge.

Best extraction effect with maximum sanding performance

Effective dust extraction ensures that the fastener and abrasive remain dust-free for longer. The sanding effect remains high and the abrasive can therefore be used for longer.

Fastener resistant to high temperatures


On the MULTI-JETSTREAM 2 sanding pad, the fastener consists of material that is resistant to high temperatures and is therefore particularly durable. The special hooks in the fastener ensure perfect adhesion of the abrasive.


* For all sanding pads 150 mm in diameter


Abrasives


LRS 93
DX 93
LEX 3 77
RO 90 DX




| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|-------|--------------|-----------|
| Ø 77 mm | | | | | | |
| Granat | P80 | 50 | 497405 | P400 | 50 | 497412 |
|  | P120 | 50 | 497406 | P500 | 50 | 497413 |
| | P150 | 50 | 497407 | P800 | 50 | 498929 |
| | P180 | 50 | 497408 | P1000 | 50 | 498930 |
| | P240 | 50 | 497409 | P1200 | 50 | 498931 |
| | P280 | 50 | 497410 | P1500 | 50 | 498932 |
| | P320 | 50 | 497411 | | | |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|-------|--------------|-----------|
| Ø 90 mm | | | | | | |
| Granat | P40 | 50 | 497363 | P280 | 100 | 497850 |
|  | P60 | 50 | 497364 | P320 | 100 | 497372 |
| | P80 | 50 | 497365 | P400 | 100 | 497373 |
| | P100 | 100 | 497366 | P500 | 100 | 498326 |
| | P120 | 100 | 497367 | P800 | 50 | 498327 |
| | P150 | 100 | 497368 | P1000 | 50 | 498328 |
| | P180 | 100 | 497369 | P1200 | 50 | 498329 |
| | P220 | 100 | 497370 | P1500 | 50 | 498330 |
| | P240 | 100 | 497371 | | | |



| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|-------|--------------|-----------|-------|--------------|-----------|
| Ø 90 mm | | | | | | |
| Platin 2 | S500 | 15 | 498322 | S2000 | 15 | 498324 |
|  | S1000 | 15 | 498323 | S4000 | 15 | 498325 |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| 93V | | | | | | |
| Granat | P40 | 50 | 497390 | P180 | 100 | 497396 |
|  | P60 | 50 | 497391 | P220 | 100 | 497397 |
| | P80 | 50 | 497392 | P240 | 100 | 497398 |
| | P100 | 100 | 497393 | P280 | 100 | 499644 |
| | P120 | 100 | 497394 | P320 | 100 | 497399 |
| | P150 | 100 | 497395 | P400 | 100 | 497400 |



Abrasives



| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Ø 115 mm | | | | | | |
| Saphir | P24 | 25 | 484151 | P50 | 25 | 485245 |
|  | P36 | 25 | 484152 | P80 | 25 | 485246 |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|-------|--------------|-----------|
| Ø 125 mm | | | | | | |
| Granat | P40 | 10 | 497145 | P180 | 100 | 497171 |
|  | P60 | 10 | 497146 | P220 | 100 | 497172 |
| | P80 | 10 | 497147 | P240 | 100 | 497173 |
| | P120 | 10 | 497148 | P280 | 100 | 497174 |
| | P180 | 10 | 497149 | P320 | 100 | 497175 |
| | P320 | 10 | 497150 | P360 | 100 | 497176 |
| | P40 | 50 | 497165 | P400 | 100 | 497177 |
| | P60 | 50 | 497166 | P500 | 100 | 497178 |
| | P80 | 50 | 497167 | P800 | 50 | 497179 |
| | P100 | 100 | 497168 | P1000 | 50 | 497180 |
| | P120 | 100 | 497169 | P1200 | 50 | 497181 |
| | P150 | 100 | 497170 | P1500 | 50 | 497182 |
| Granat Net | P80 | 50 | 203294 | P220 | 50 | 203299 |
|  | P100 | 50 | 203295 | P240 | 50 | 203300 |
| | P120 | 50 | 203296 | P320 | 50 | 203301 |
| | P150 | 50 | 203297 | P400 | 50 | 203302 |
| | P180 | 50 | 203298 | | | |

| | | | | | | |
|---|--|---|--------|--|--|--|
| Protection Pad | | 2 | 203344 | | | |
|  | | | | | | |

| | | | | | | |
|---|-------|----|--------|-------|----|--------|
| Ø 125 mm | | | | | | |
| Platin 2 | S400 | 15 | 492373 | S2000 | 15 | 492376 |
|  | S500 | 15 | 492374 | S4000 | 15 | 492377 |
| | S1000 | 15 | 492375 | | | |
| Vlies | 100 | 10 | 201131 | green | 10 | 496510 |
|  | 320 | 10 | 201132 | white | 10 | 496511 |
| | 800 | 10 | 201133 | | | |







Abrasives



RO 150


ETS EC 150


LEX 3 150



| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|-------|--------------|-----------|-------|--------------|-----------|
| Ø 150 mm | | | | | | |
| Granat | P40 | 10 | 575154 | P180 | 100 | 575166 |
|  | P60 | 10 | 575155 | P220 | 100 | 575167 |
| | P80 | 10 | 575156 | P240 | 100 | 575168 |
| | P120 | 10 | 575157 | P280 | 100 | 575169 |
| | P180 | 10 | 575158 | P320 | 100 | 575170 |
| | P320 | 10 | 575159 | P360 | 100 | 575171 |
| | P40 | 50 | 575160 | P400 | 100 | 575172 |
| | P60 | 50 | 575161 | P500 | 100 | 575173 |
| | P80 | 50 | 575162 | P800 | 50 | 575174 |
| | P100 | 100 | 575163 | P1000 | 50 | 575175 |
| | P120 | 100 | 575164 | P1200 | 50 | 575176 |
| | P150 | 100 | 575165 | P1500 | 50 | 575177 |
| Granat Net | P80 | 50 | 203303 | P220 | 50 | 203308 |
|  | P100 | 50 | 203304 | P240 | 50 | 203309 |
| | P120 | 50 | 203305 | P320 | 50 | 203310 |
| | P150 | 50 | 203306 | P400 | 50 | 203311 |
| | P180 | 50 | 203307 | | | |
| Protection Pad | | 2 | 203343 | | | |
|  | | | | | | |
| Ø 150 mm | | | | | | |
| Platin 2 | S400 | 15 | 492368 | S2000 | 15 | 492371 |
|  | S500 | 15 | 492369 | S4000 | 15 | 492372 |
| | S1000 | 15 | 492370 | | | |
| Saphir | P24 | 25 | 575194 | P50 | 25 | 575196 |
|  | P36 | 25 | 575195 | P80 | 25 | 575197 |
| Vlies | 100 | 10 | 201126 | 800 | 10 | 201128 |
|  | 320 | 10 | 201127 | | | |


Abrasives

RAS 180
LEX 2 185/7
HSK-A 80x130

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|--|------|--------------|-----------|------|--------------|-----------|
| Ø 180 mm | | | | | | |
| Saphir  | P24 | 25 | 485239 | P50 | 25 | 485241 |
| | P36 | 25 | 485240 | P80 | 25 | 485242 |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|--|------|--------------|-----------|------|--------------|-----------|
| Ø 185 mm | | | | | | |
| Granat  | P40 | 50 | 497183 | P150 | 100 | 497187 |
| | P60 | 50 | 497184 | P180 | 100 | 497188 |
| | P80 | 50 | 497185 | P240 | 100 | 497189 |
| | P100 | 100 | 499629 | P320 | 100 | 497190 |
| | P120 | 100 | 497186 | P400 | 100 | 497191 |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|--|--|--------------|-----------|--------|--------------|-----------|
| 80 x 133 mm | | | | | | |
| Granat  | P40 | 10 | 497127 | P120 | 100 | 497120 |
| | P80 | 10 | 497128 | P150 | 100 | 497121 |
| | P120 | 10 | 497129 | P180 | 100 | 497122 |
| | P180 | 10 | 497130 | P220 | 100 | 497123 |
| | P40 | 50 | 497117 | P240 | 100 | 497124 |
| | P60 | 50 | 497118 | P280 | 100 | 497204 |
| | P80 | 50 | 497119 | P320 | 100 | 497125 |
| | P100 | 100 | 499628 | P400 | 100 | 497126 |
| | Granat Net  | P80 | 50 | 203285 | P220 | 50 |
| P100 | | 50 | 203286 | P240 | 50 | 203291 |
| P120 | | 50 | 203287 | P320 | 50 | 203292 |
| P150 | | 50 | 203288 | P400 | 50 | 203293 |
| P180 | | 50 | 203289 | | | |


| | | | | | | |
|--|--|---|--------|--|--|--|
| Protection Pad  | | 2 | 203346 | | | |
|--|--|---|--------|--|--|--|


Abrasives

LRS 400
 HSK-A 80 x 400/80 x 200
 LRS 93
 RS 100





| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|---------------|--------------|-----------|------|--------------|-----------|
| 80 x 400 mm | | | | | | |
|  | Granat | | | | | |
| | P40 | 50 | 497157 | P150 | 50 | 497161 |
| | P60 | 50 | 497158 | P180 | 50 | 497162 |
| | P80 | 50 | 497159 | P240 | 50 | 497163 |
| | P100 | 50 | 499631 | P280 | 50 | 497203 |
| | P120 | 50 | 497160 | P320 | 50 | 497164 |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|--|---------------|--------------|-----------|------|--------------|-----------|
| 93 x 178 mm | | | | | | |
|  | Granat | | | | | |
| | P40 | 50 | 498933 | P180 | 100 | 498938 |
| | P60 | 50 | 498934 | P220 | 100 | 498939 |
| | P80 | 50 | 498935 | P240 | 100 | 498940 |
| | P100 | 100 | 499633 | P280 | 100 | 498941 |
| | P120 | 100 | 498936 | P320 | 100 | 498942 |
| P150 | 100 | 498937 | P400 | 100 | 498943 | |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|---------------|--------------|-----------|------|--------------|-----------|
| 115 x 228 mm | | | | | | |
|  | Granat | | | | | |
| | P40 | 50 | 498944 | P180 | 100 | 498949 |
| | P60 | 50 | 498945 | P220 | 100 | 498950 |
| | P80 | 50 | 498946 | P240 | 100 | 498951 |
| | P100 | 100 | 499632 | P280 | 100 | 498952 |
| | P120 | 100 | 498947 | P320 | 100 | 498953 |
| P150 | 100 | 498948 | P400 | 100 | 498954 | |


Abrasives


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|-------|--------------|-----------|-------|--------------|-----------|
| Self-adhesive sanding discs Ø 36 mm | | | | | | |
| Granat | P2000 | 500 | 500445 | P3000 | 500 | 500447 |
|  | P2500 | 500 | 500446 | | | |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Hand abrasive Granat soft 115 mm x 25 m | | | | | | |
| Granat soft | P120 | 1 | 497091 | P400 | 1 | 497096 |
|  | P150 | 1 | 497092 | P500 | 1 | 497097 |
| | P180 | 1 | 497093 | P600 | 1 | 497098 |
| | P240 | 1 | 497094 | P800 | 1 | 497964 |
| | P320 | 1 | 497095 | | | |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Granat sanding block manual abrasive 69 x 98 x 26 mm (four-sided) | | | | | | |
| Granat | 120 | 6 | 201082 | 220 | 6 | 201083 |
|  | | | | | | |

| | Grit | Qty. in pack | Order no. |
|--|------|--------------|-----------|
| Granat sanding block manual abrasive 69 x 98 x 26 mm (four-sided) combi block | | | |
| Granat | 120 | 6 | 201084 |
|  | | | |


| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Hand abrasive Granat abrasive sponge 98 x 120 x 13 mm (2-sided) | | | | | | |
| Granat | 120 | 6 | 201113 | 800 | 6 | 201507 |
|  | 220 | 6 | 201114 | | | |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Granat abrasive pad manual abrasive 115 x 140 x 5 mm (one-sided) | | | | | | |
| Granat | 280 | 20 | 201769 | 1000 | 20 | 201101 |
|  | 500 | 20 | 201099 | 1500 | 20 | 201102 |
| | 800 | 20 | 201100 | | | |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Hand abrasive Vlies 115 x 152 mm | | | | | | |
| Vlies | 100 | 25 | 201115 | 800 | 30 | 497089 |
|  | 320 | 30 | 497088 | 1000 | 30 | 497090 |

| | Grit | Qty. in pack | Order no. | Grit | Qty. in pack | Order no. |
|---|------|--------------|-----------|------|--------------|-----------|
| Hand abrasive Vlies abrasive roll 115 mm x 10 m | | | | | | |
| Vlies | 100 | 1 | 201116 | 800 | 1 | 201118 |
|  | 320 | 1 | 201117 | 1000 | 1 | 201119 |








System accessories



Accessories for SHINEX RAP 150, POLLUX 180 rotary polishers




| Denomination | Explanation | Order no. |
|----------------------------------|--|-----------|
| 1 Polishing pad PT-STF-D150-M14 | for RAP 150, with integrated shock absorber for optimum distribution of pressure during polishing, fits polishing accessories, diameter 125 mm, height 25 mm, in self-service display pack | 488342 |
| Polishing pad PT-STF-D180-M14 | for RAP 180, with integrated shock absorber for optimum distribution of pressure during polishing, fits polishing accessories, diameter 165 mm, height 30 mm, in self-service display pack | 488349 |
| 2 Foam polishing pads | from page 102 | |
| 3 Polishing agent | from page 100 | |
| 4 Additional hand grip ZG-RAS/RO | for RO 150, RAS, WTS 150, in carton | 487865 |

Polishing accessories

| Polishing agent | | | |
|---|--|---------------------------|-----------|
| | | Type | Order no. |
|  | Polishing agent Speed Cut 1-step sanding polish, does not contain silicone, water-based, perfect in combination with a sheepskin pad or polishing pad (ORANGE), volume 500 ml, in plastic bottle | MPA 5010 OR/0,5L | 202048 |
|  | Polishing agent Speed Gloss fine sanding polish, does not contain silicone, water-based, perfect in combination with a polishing pad (BLUE), volume 500 ml, in plastic bottle | MPA 9010 BL/0,5L | 202050 |
|  | Polishing agent anti-swirl-mark high-gloss polish, does not contain silicone, water-based, perfect in combination with a polishing pad (WHITE), volume 500 ml, in plastic bottle | MPA 11010 WH/0,5L | 202051 |
|  | Sealing spray for sealing painted surfaces, does not contain silicone, water-based, volume 500 ml, in plastic bottle | MPA SV+/0,5L | 202052 |
|  | Finish-Cleaner for removing polish residues and grease marks, does not contain silicone, water-based, volume 500 ml, in plastic bottle | MPA F+/0,5L | 202053 |
| Microfibre cloth, cleaning cloth | | | |
| | | Type | Order no. |
|  | Microfibre cloth for excellent finish of new paints, for removing polish residues and grease marks, qty. in pack 2 piece(s), in self-service display pack | MPA-Microfibre/2 | 493068 |
|  | Cleaning cloth roller with 200 sheets, fibre-reinforced, tear-proof and extremely absorbent, in dispenser box, in carton | RT PREMIUM 240x380/200 | 498071 |

Polishing accessories

Self-adhesive sanding discs, spot sander and spot repair scraper

| | | Type | Order no. |
|---|--|-----------------------------|---------------|
|  | Self-adhesive sanding disc for spot sander RH-SK D 32-36, self-adhesive, in a roll, Granat version, qty. in pack 500 piece(s), in bag | | |
| | grit P2000 | SK D32-36/0 P2000 GR/500 | 500445 |
| | grit P2500 | SK D32-36/0 P2500 GR/500 | 500446 |
| | grit P3000 | SK D32-36/0 P3000 GR/500 | 500447 |
|  | Spot sander for self-adhesive sanding discs D 32-36, used for holding self-adhesive sanding discs with diameter of 36 mm, for eliminating flaws, in bag | RH-SK D32-36 | 493069 |
|  | Spot repair scraper with cord, for the accurate removal of trapped particles and unevenness, manufactured from carbide, with hollow grinding, dimensions 25 x 30 mm, in self-service display pack | LZK-HM | 497525 |


Polishing accessories



| | | Diameter | Height in mm | Qty. in pack | Order no. |
|--|---|----------|--------------|--------------|-----------|
| PoliStick polishing sponge for dia. 80 mm | | | | | |
| | yellow, Coarse, for polishing heavily weathered surfaces (preparation for painting) | 80 mm | 20 mm | 5 | 201989 |
| | orange, Mid, for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 80 mm | 20 mm | 5 | 201993 |
| | orange, medium (waffle face), for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 80 mm | 20 mm | 5 | 201994 |
| | blue, medium-fine, for removing microscratches in clear coats, ideal together with the MPA 9010 | 80 mm | 20 mm | 5 | 202001 |
| | blue, medium-fine (waffle face), for removing microscratches in clear coats, ideal together with the MPA 9010 | 80 mm | 20 mm | 5 | 202002 |
| | white, Fine, for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 80 mm | 20 mm | 5 | 202009 |
| | white, fine (honeycombed), for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 80 mm | 20 mm | 5 | 202010 |
| | black, very fine (honeycombed), for removing polish residues on the painted surface | 80 mm | 20 mm | 5 | 202017 |
| Sheepskin and polishing felt for dia. 80 mm | | | | | |
| | real hair sheepskin for high abrasiveness and an excellent polishing finish, ideal together with the MPA 5010, Suitable for UV paints, scratch-resistant paints, optimum adhesion thanks to full covering with adhesive velour and edge seams | 80 mm | 18 mm | 5 | 202044 |
| | Polishing felt, hard, For preliminary polishing of mineral materials, acrylic glass and gloss paints, white | 80 mm | 6 mm | 5 | 488339 |
| | Polishing felt, soft, for re-polishing mineral materials, acrylic glass and gloss paints, white | 80 mm | 6 mm | 5 | 488341 |

Polishing accessories

RO 125

| | | Diameter | Height in mm | Qty. in pack | Order no. |
|---|---|----------|--------------|--------------|-----------|
| PoliStick polishing sponge for dia. 125 mm | | | | | |
|  | yellow, Coarse, for polishing heavily weathered surfaces (preparation for painting) | 125 mm | 20 mm | 5 | 201990 |
|  | orange, Mid, for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 125 mm | 20 mm | 1 | 202367 |
| | | 125 mm | 20 mm | 5 | 201995 |
|  | orange, medium (waffle face), for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 125 mm | 20 mm | 1 | 202368 |
| | | 125 mm | 20 mm | 5 | 201996 |
|  | blue, medium-fine, for removing microscratches in clear coats, ideal together with the MPA 9010 | 125 mm | 20 mm | 1 | 202371 |
| | | 125 mm | 20 mm | 5 | 202003 |
|  | blue, medium-fine (waffle face), for removing microscratches in clear coats, ideal together with the MPA 9010 | 125 mm | 20 mm | 1 | 202372 |
| | | 125 mm | 20 mm | 5 | 202004 |
|  | white, Fine, for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 125 mm | 20 mm | 1 | 202375 |
| | | 125 mm | 20 mm | 5 | 202011 |
|  | white, fine (honeycombed), for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 125 mm | 20 mm | 1 | 202376 |
| | | 125 mm | 20 mm | 5 | 202012 |
|  | black, very fine (honeycombed), for removing polish residues on the painted surface | 125 mm | 20 mm | 1 | 202379 |
| | | 125 mm | 20 mm | 5 | 202018 |
| Sheepskin and polishing felt for dia. 125 mm | | | | | |
|  | real hair sheepskin for high abrasiveness and an excellent polishing finish, ideal together with the MPA 5010, Suitable for UV paints, scratch-resistant paints, optimum adhesion thanks to full covering with adhesive velour and edge seams | 125 mm | 18 mm | 1 | 202045 |
|  | Polishing felt, hard, For preliminary polishing of mineral materials, acrylic glass and gloss paints, white | 125 mm | 6 mm | 5 | 493078 |
| | Polishing felt, soft, For re-polishing mineral materials, acrylic glass and gloss paints, white | 125 mm | 6 mm | 5 | 493077 |

Polishing accessories

RAP 150



RO 150



PoliStick polishing sponge for dia. 150 mm

| | | Diameter | Height in mm | Qty. in pack | Order no. |
|---|--|----------|--------------|--------------|-----------|
|  | yellow, Coarse, for polishing heavily weathered surfaces (preparation for painting) | 150 mm | 30 mm | 5 | 201991 |
|  | orange, Mid, for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 150 mm | 30 mm | 1 | 202369 |
| | | 150 mm | 30 mm | 5 | 201997 |
|  | orange, medium (waffle face), for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 150 mm | 30 mm | 1 | 202370 |
| | | 150 mm | 30 mm | 5 | 201998 |
|  | blue, medium-fine, for removing microscratches in clear coats, ideal together with the MPA 9010 | 150 mm | 30 mm | 1 | 202373 |
| | | 150 mm | 30 mm | 5 | 202005 |
|  | blue, medium-fine (waffle face), for removing microscratches in clear coats, ideal together with the MPA 9010 | 150 mm | 30 mm | 1 | 202374 |
| | | 150 mm | 30 mm | 5 | 202006 |
|  | white, Fine, for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 150 mm | 30 mm | 1 | 202377 |
| | | 150 mm | 30 mm | 5 | 202013 |
|  | white, fine (honeycombed), for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 150 mm | 30 mm | 1 | 202378 |
| | | 150 mm | 30 mm | 5 | 202014 |
|  | black, very fine (honeycombed), for removing polish residues on the painted surface | 150 mm | 30 mm | 1 | 202380 |
| | | 150 mm | 30 mm | 5 | 202019 |

Sheepskin and polishing felt for dia. 150 mm

| | | | | | |
|---|---|--------|-------|---|--------|
|  | real hair sheepskin for high abrasiveness and an excellent polishing finish, ideal together with the MPA 5010, Suitable for UV paints, scratch-resistant paints, optimum adhesion thanks to full covering with adhesive velour and edge seams | 150 mm | 18 mm | 1 | 202046 |
|  | Polishing felt, hard, For preliminary polishing of mineral materials, acrylic glass and gloss paints, white | 150 mm | 6 mm | 1 | 485970 |
| | | 150 mm | 6 mm | 5 | 488348 |
| | Polishing felt, soft, For re-polishing mineral materials, acrylic glass and gloss paints, white | 150 mm | 6 mm | 1 | 485972 |
| | | 150 mm | 6 mm | 5 | 488347 |

Polishing accessories

POLLUX 180

RAP 180



| | | Diameter | Height in mm | Qty. in pack | Order no. |
|---|---|----------|--------------|--------------|-----------|
| PoliStick polishing sponge for dia. 180 mm | | | | | |
|  | yellow, Coarse, for polishing heavily weathered surfaces (preparation for painting) | 180 mm | 30 mm | 5 | 201992 |
|  | orange, Mid, for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 180 mm | 30 mm | 5 | 201999 |
|  | orange, medium (waffle face), for preliminary polishing when repairing paint flaws, ideal together with the MPA 5010 | 180 mm | 30 mm | 5 | 202000 |
|  | blue, medium-fine, for removing microscratches in clear coats, ideal together with the MPA 9010 | 180 mm | 30 mm | 5 | 202007 |
|  | blue, medium-fine (waffle face), for removing microscratches in clear coats, ideal together with the MPA 9010 | 180 mm | 30 mm | 5 | 202008 |
|  | white, Fine, for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 180 mm | 30 mm | 5 | 202015 |
|  | white, fine (honeycombed), for polishing out swirl marks and producing a deep shine, for high-gloss polish (deep shine), ideal together with the MPA 11010 | 180 mm | 30 mm | 5 | 202016 |
|  | black, very fine (honeycombed), for removing polish residues on the painted surface | 180 mm | 30 mm | 5 | 202020 |
| Sheepskin and polishing felt for dia. 180 mm | | | | | |
|  | real hair sheepskin for high abrasiveness and an excellent polishing finish, ideal together with the MPA 5010, Suitable for UV paints, scratch-resistant paints, optimum adhesion thanks to full covering with adhesive velour and edge seams | 180 mm | 18 mm | 1 | 202047 |
|  | Polishing felt, hard, For preliminary polishing of mineral materials, acrylic glass and gloss paints, white | 180 mm | 6 mm | 5 | 488355 |
|  | Polishing felt, soft, for re-polishing mineral materials, acrylic glass and gloss paints, white | 180 mm | 6 mm | 5 | 488354 |




FESTOOL
HSK 115 x 226

DUST EXTRACTION

PROFESSIONALS IN DUST CONTROL TECHNOLOGY.

| | |
|---|------------|
| CLEANTEC compact mobile dust extractor | 109 |
| CTL MIDI | |
| CLEANTEC mobile dust extractor | 110 |
| CT 26/36/48 | |
| CLEANTEC special extractor | 112 |
| CT 48 EC, CT 48 EC/B22 | |
| Exhaust turbines | 114 |
| TURBO II | |
| Accessories and consumables | 115 |

The Festool system



Full utilisation of the container volume

The sophisticated container geometry, compatible SELFCLEAN filter bag and space-saving flat filter combine to produce a net volume that corresponds almost exactly to the gross volume of the container.



New and now even better: SYS DOCK

Simple transportation, better organisation and endless flexibility. The SYS-Dock with T-LOC for the safe connection of SYSTEMAINER, SORTAINER and SYS-ToolBox units.




Cable holder.

The cord can be wound up quickly and neatly thanks to the new cord holder. And – thanks to the sophisticated folding mechanism – can be easily removed from the holder without complex unwinding.



Hose garage

The integral hose holder eliminates the need for external hooks and protects the suction hose and mains cable from damage. The suction hose winds around the holder for clean, compact transportation.



Smooth suction hose with CLEANTEC sleeve

The new suction hose: Smooth and flexible – with a smooth exterior for perfect sliding over surfaces, a longer service life and greater suction power. The new CLEANTEC extraction sleeve ensures a secure fit on the tool.



CLEANTEC CTL MIDI

Mobile dust extractor CLEANTEC CTL MIDI



The compact extractor with 15 l container volume.

- ▶ Extremely compact and lightweight, for simple transport
- ▶ Better organisation thanks to hose depot for safe storage of hose and cable
- ▶ Strong suction power thanks to compact high-performance turbine and smooth, conical suction hose
- ▶ SYSTEMERS are secured to SYS-Dock in an instant

Technical data

| | |
|--|-----------------|
| Power consumption (W) | 400 – 1.200 |
| Max. volume flow (l/min) | 3.700 |
| Max. vacuum (Pa) | 24.000 |
| Filter surface area (cm ²) | 5.000 |
| Rubber-insulated mains cable (m) | 7,5 |
| Container/filter bag capacity (l) | 15/12,5 |
| Dimensions (L x W x H) (mm) | 430 x 330 x 470 |
| Max. appliance socket connected load (W) | 2.400 |
| Weight (kg) | 9,1 |



■ = Electronic

| Items included | Order no. |
|--|---------------|
| CTL MIDI fitted filter bag, smooth suction hose dia. 27/32 x 3.5 m AS/CT with rotating angle adapter on the extractor side, hose holder, Sys-Dock with T-LOC function, in carton | 575261 |



Small on the outside, large on the inside.

The CTL MIDI is the ideal companion for cleaning purposes. The compact wet/dry extractor with 15 l container volume is perfect for extracting small to medium volumes of dust and dirt. For class L dust.

System accessories
from page 120



CLEANTEC CT 26 / CT 36

CLEANTEC CT 26 / CT 36 mobile dust extractors

NEW



The true size can be found inside.

- ▶ Maximum utilisation of the container volume – the gross volume is the same as the net volume
- ▶ Can be individually retrofitted with an additional socket or compressed air module with automatic switch on/off
- ▶ Constantly high suction because of the compact high performance turbine
- ▶ Smooth suction hose and optimised SYS-Dock with cord holder and T-LOC function for conveniently connecting SYSTAINERS to the mobile dust extractor

All-rounder in the perfect size.

Compact yet effective. Lightweight yet powerful. The perfected container geometry of the CLEANTEC CT 26/36 offers a significantly larger capacity with minimal external dimensions.

Dust categories in accordance with EN 60335-2-69, Appendix AA

| | Appropriate | Max. permeability (test) |
|-------------------|---|---|
| L (Low) | - dust with OEL > 1 mg/m ³ | 1% (filter material) |
| M (Medium) | - dust with OEL ≥ 0.1 mg/m ³ - mineral dust | 0.1% (complete tool incl. upholstery nail test) |

| Technical data | CT 26 | CT 36 |
|--|-----------------|-----------------|
| Power consumption (W) | 350 – 1.200 | 350 – 1.200 |
| Max. volume flow (l/min) | 3.900 | 3.900 |
| Max. vacuum (Pa) | 24.000 | 24.000 |
| Filter surface area (cm ²) | 6.318 | 6.318 |
| Rubber-insulated mains cable (m) | 7,5 | 7,5 |
| Container/filter bag capacity (l) | 26/24 | 36/34 |
| Dimensions (L x W x H) (mm) | 630 x 365 x 540 | 630 x 365 x 596 |
| Max. appliance socket connected load (W) | 2.400 | 2.400 |
| Weight (kg) | 13,9 | 14,4 |




■ = Electronic

| Items included | Order no. |
|---|---------------|
| SELF-CLEAN filter bag, smooth suction hose dia. 27/32 x 3.5 m AS/CT, hose holder, Sys-Dock with T-LOC function, cable holder, in carton | |
| CTL 26 E | 574947 |
| CTL 26 E SD with second socket with continuous current | 574955 |
| CTL 36 E | 574965 |
| CTL 36 E LE compressed air module | 574972 |
| CTM 26 E end cap for intake adapter | 574981 |
| CTM 36 E end cap for intake adapter | 574988 |
| CTM 36 E LE end cap for intake adapter, compressed air module | 574990 |

System accessories from page 116



Workcenter WCR 1000 from page 132





CLEANTEC CT 48

Mobile dust extractor CLEANTEC CT 48

NEW



There's more to it than meets the eye.

- ▶ Large capacity for large volumes of dust
- ▶ Constantly high suction because of the compact high performance turbine
- ▶ Can be individually retrofitted with an additional socket or compressed air module
- ▶ Smooth suction hose and optimised SYS-Dock with cord holder and T-LOC function for conveniently connecting SYSTAINERS to the mobile dust extractor

Technical data

| | |
|--|-------------------|
| Power consumption (W) | 350 - 1.200 |
| Max. volume flow (l/min) | 3.900 |
| Max. vacuum (Pa) | 24.000 |
| Filter surface area (cm ²) | 6.318 |
| Rubber-insulated mains cable (m) | 7,5 |
| Container/filter bag capacity (l) | 48/46 |
| Dimensions (L x W x H) (mm) | 740 x 406 x 1.005 |
| Max. appliance socket connected load (W) | 2.400 |
| Weight (kg) | 18,8 |



■ = Electronic

Items included

SELF-CLEAN filter bag, smooth suction hose dia. 27/32 x 3,5 m AS/CT, hose holder, Sys-Dock with T-LOC function, cable holder, handle, in carton

CTL 48 E 574975

CTM 48 E 574992
end cap for intake adapter

Order no.

For use in the workshop.

The CT 48 has a container volume of 48 litres, which is ideal for extracting large quantities of dust in the bodyshop. As CTL and CTM it is suitable for dust classes L and M.


Dust categories in accordance with EN 60335-2-69, Appendix AA

| | Appropriate | Max. permeability (test) |
|-------------------|---|---|
| L (Low) | - dust with OEL > 1 mg/m ³ | 1% (filter material) |
| M (Medium) | - dust with OEL ≥ 0.1 mg/m ³ - mineral dust | 0.1% (complete tool incl. upholstery nail test) |

System accessories from page 116



Workcenter WCR 1000 from page 132



CLEANTEC CT 48 EC

Mobile dust extractor CLEANTEC CT 48 EC



Brushless EC-TEC motor for a long service life and a high level of efficiency



Reliable. Durable. Powerful.

Tough continuous operation is its speciality and the EC-TEC drive concept guarantees greater reliability and a longer life. For relentless suction power.

Dust categories in accordance with EN 60335-2-69, Appendix AA

| | Appropriate | Max. permeability (test) |
|-------------------|---|---|
| L (Low) | - dust with OEL > 1 mg/m ³ | 1% [filter material] |
| M (Medium) | - dust with OEL ≥ 0.1 mg/m ³ - mineral dust | 0.1% [complete tool incl. upholstery nail test] |

Designed for continuous industrial use.

- ▶ Constant power from the EC-TEC drive with a service life several times longer than a universal motor
- ▶ With suction power adjustment, flexible adaptation to any working situation
- ▶ Antistatic function prevents static developing during work
- ▶ With integrated connection for EAA and compressed air tools

Technical data

| | |
|--|-----------------|
| Power consumption (W) | 150 – 1.100 |
| Max. volume flow (l/min) | 3.400 |
| Max. vacuum (Pa) | 23.000 |
| Filter surface area (cm ²) | 6.318 |
| Rubber-insulated mains cable (m) | 7,5 |
| Container/filter bag capacity (l) | 48/46 |
| Dimensions (L x W x H) (mm) | 630 x 406 x 640 |
| Max. appliance socket connected load (W) | 2.400 |
| Weight (kg) | 17,9 |



■ = Electronic

Items included


SELF CLEAN filter bag, smooth suction hose dia. 27/32 x 3.5 m AS/CT, cable holder, compressed air module, in carton

| | Order no. |
|-----------------------|---------------|
| CTL 48 E LE EC | 575300 |
| CTM 48 E LE EC | 575298 |

System accessories from page 116



Workcenter WCR 1000 from page 132





CLEANTEC CT 48 EC/B22

Mobile dust extractor CLEANTEC CT 48 EC/B22



Brushless EC-TEC motor for a long service life and a high level of efficiency



For maximum safety.

- ▶ Conforms with ATEX Directive 94/9/EC for Zone 22
- ▶ Constant power from the EC-TEC drive with a service life several times longer than a universal motor
- ▶ With a new suction hose: Smooth and flexible – with a smooth exterior which allows it to slide over surfaces perfectly
- ▶ With integrated connection for EAA and compressed air tools



For dry and flammable dust.

The CT 48 EC/B22 special extractor with EC-TEC drive is designed for continuous use. The robust ABS plastic container is fitted with additional flame protection and is therefore suitable for the safe extraction of everything from aluminium, paper, soot and powder coating dust to glass-fibre and carbon-fibre reinforced plastics.

Dust categories in accordance with EN 60335-2-69, Appendix AA

| | Appropriate | Max. permeability (test) |
|-------------------|---|---|
| L (Low) | - dust with OEL > 1 mg/m ³ | 1% (filter material) |
| M (Medium) | - dust with OEL ≥ 0.1 mg/m ³ - mineral dust | 0.1% [complete tool incl. upholstery nail test] |

Technical data

| | |
|--|-----------------|
| Power consumption (W) | 150 – 1.100 |
| Max. volume flow (l/min) | 3.400 |
| Max. vacuum (Pa) | 23.000 |
| Filter surface area (cm ²) | 6.318 |
| Rubber-insulated mains cable (m) | 7,5 |
| Container/filter bag capacity (l) | 48/46 |
| Dimensions (L x W x H) (mm) | 630 x 406 x 640 |
| Max. appliance socket connected load (W) | 2.400 |
| Weight (kg) | 18,6 |



■ = Electronic

Items included

SELF-CLEAN filter bag, smooth suction hose dia. 27/32 x 3.5 m AS/CT, cable holder, compressed air module, in carton


Order no.

| | |
|------------------------------|---------------|
| CTL 48 E LE EC/B22 R1 | 575275 |
| CTM 48 E LE EC B22 R1 | 575286 |

System accessories from page 116



Workcenter WCR 1000 from page 132



TURBO II

TURBO II exhaust turbines



Scan the page to discover hidden 3D graphics, videos and images.

Optimal dust extraction for quick processes.


The TURBO II with DC TEC, Dynamic Control Technology, provides constant suction power for up to 14 workstations (depending on the version). The patented and dynamic control unit (DC-TEC) automatically reduces the energy consumption to the absolute minimum, depending on the number of workstations in operation. This intelligent system controls the relationship between the requested suction power and the required energy. In addition, automatic filter cleaning cycles are continuously performed, in order to guarantee 100% suction power.

Exceptional power, maximum energy efficiency!

- ▶ Simultaneous extraction from a maximum of 8 workplaces with a single turbine
- ▶ Only one machine for reduced maintenance and repair work
- ▶ Dynamic suction power regulated to suit requirements reduces energy consumption
- ▶ Possible to connect a discharge flap for automatic pipe cleaning

| Technical data | TURBO II M-8WP R1 | TURBO II M-14WP R1 |
|---|---------------------|---------------------|
| Power consumption at 50 Hz (TURBO) (W) | 5.500 | 7.500 |
| Power consumption at 60 Hz (TURBO) (W) | 7.500 | 11.000 |
| Max. number of work stations | 8 | 14 |
| Controlled motor frequency (Hz) | 20 – 65 | 20 – 65 |
| Max. volume flow (l/min) | 14.100 | 20.500 |
| Max. vacuum, working area (mbar) | 140 | 140 |
| Noise generation at 40 Hz (dB(A)) | 65 | 71 |
| Dimensions (L x W x H) (mm) | 805 x 1.048 x 1.740 | 805 x 1.045 x 1.740 |
| Filter surface area (cm ²) | 50.000 | 75.000 |
| Pipe connection [supply air/exhaust] (mm) | 100/125 | 100/125 |
| Max. cable length (mm) | 100 | 100 |



 = Electronic





| Items included | Order no. |
|--|---------------|
| 2 x main filter, disposal bag, in carton | |
| TURBO II M-8WP R1 ATEX | 583886 |
| TURBO II M-14WP R1 ATEX | 583887 |

TURBO II only available in selected countries.

System accessories
from page 121

System accessories




CLEANTEC cleaning sets

| | | Type | Order no. |
|---|---|---------------------|-----------|
|  | Cleaning set crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, suction brush D 36 SP, in self-service display pack | D 27 / D 36 D-RS | 492392 |
|  | Standard cleaning set curved hand tube D 36 HR-K AS, extension pipes D 36 VR-K AS, 4-piece floor nozzle D 36 BD270, crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, in carton | D 27/D 36 S-RS | 203428 |
|  | Professional cleaning set curved hand tube D 36 HR-K AS, extension tube, special steel 3-piece D 36 VR-M3x, carpet nozzle, D 36 TD, crevice nozzle D 36 FD-210, in carton | D 27/36 P-RS | 203429 |
|  | Compact cleaning set curved hand tube D 36 HR-K AS, extension pipes D 36 VR-K AS, 4-piece floor nozzle D 36 BD270, crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, in SYSTAINER SYS 1 T-LOC | D 27/D 36 K-RS-Plus | 203430 |
|  | Cleaning set for tradesmen smooth suction hose D 36, antistatic, curved hand tube D 36 HR-K AS, extension tube, special steel 3-piece D 36 VR-M3x, carpet nozzle, D 36 TD, crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, suction brush D 36 SP, in SYSTAINER SYS 5 T-LOC | D 36 HW-RS-Plus | 203408 |
|  | Cleaning set for the workshop smooth suction hose D 36, antistatic, curved hand tube D 36 HR-K AS, extension tube, special steel 3-piece D 36 VR-M3x, floor nozzle, D 36 BD 370, in SYSTAINER SYS 5 T-LOC | D 36 WB-RS-Plus | 203409 |
|  | Universal cleaning set Suction hose D 36, curved hand tube D 36 HR-K AS, extension pipes D 36 VR-K AS, floor nozzle, D 36 BD 300, crevice nozzle D 36 FD-210, suction brush D 36 SP, upholstery nozzle D 36 PD, in SYSTAINER SYS 5 T-LOC | D 36 UNI-RS-Plus | 203435 |
|  | Cleaning set for industrial use suction hose Ø 50 x 2,5m, extension tubes D50VR-K, floor nozzle D 50 BD370, square nozzle D 50 QD, suction brush D 50 SP, crevice nozzle D 50 FD, in carton | D 50 GS-RS | 454770 |
|  | Floor cleaning set curved hand tube D 36 HR-K AS, extension tube, special steel 3-piece D 36 VR-M3x, floor nozzle, D 36 BD 370, in SYSTAINER SYS 2 T-LOC | D 36 BD 370 RS-Plus | 203432 |

System accessories



Accessories for mobile dust extractors CT and dust extractors SR

CLEANTEC suction hose anti-static version

| | Type | Order no. |
|--|--|---|
|  <p>D 27/32 smooth antistatic suction hose temperature-resistant to +70°C, bleeder resistor (DIN IEC 312) <1 mΩ/m, diameter 27 /32 mm, in carton</p> | for CTL MINI/MIDI, with rotating angle adapter at extractor side, from YOM 09/2013, length 3,5 m | D 27/32x3,5m-AS-90°/CT 500680 |
| | for CT 26/36/48, with rotating adapter and connector, length 3,5 m | D 27/32x3,5m-AS/CT 500677 |
| | for CT 26/36/48, with rotating adapter and connector, length 5 m | D 27/32x5,0m-AS/CT 500678 |
|  <p>D 36 smooth antistatic suction hose for cleaning tasks with CT dust extractors, not suitable for dust extractors with Autoclean, temperature-resistant to +70°C, with rotating adapter and connector, bleeder resistor (DIN IEC 312) <1 mΩ/m, diameter 36 mm, in carton</p> | length 3,5 m | D 36x3,5m-AS/CT 500681 |
| | min. diameter 36 mm, length 5 m | D 36x5,0m-AS/CT 500684 |
| | min. diameter 36 mm, length 7 m | D 36x7,0m-AS/CT 500685 |
|  <p>D 36/32 smooth antistatic suction hose suitable for dust extractors with Autoclean, temperature-resistant to +70°C, for masonry renovation and cleaning work, Conical, bleeder resistor (DIN IEC 312) <1 mΩ/m, diameter 36 /32 mm, length 3,5 m, in carton</p> | D 36/32x3,5m-AS/CT | 500682 |

Accessories for mobile dust extractors CT and dust extractors SR

CLEANTEC suction hose anti-static version

| | Type | Order no. |
|---|----------------------|--|
|  <p>Suction hose plug it D 27/22 antistatic smooth for all power tools with D27 and D36 flange (all Festool power tools) and cleaning accessories, suitable for sanding applications, with rotating adapter and reducing sleeve with bayonet fitting, temperature-resistant to +70°C, bleeder resistor (DIN IEC 312) <1 mΩ/m, diameter 27 /22 mm, in carton</p> | length 3,5 m | D 27/22x3,5m-AS-GQ/CT 200041 |
| | length 5 m | D 27/22x5m-AS-GQ/CT 201758 |
|  <p>Suction hose plug it D 32/22 antistatic smooth for all power tools with D27 and D36 flange (all Festool power tools) and cleaning accessories, suitable for sanding applications, with rotating adapter and reducing sleeve with bayonet fitting, temperature-resistant to +70°C, length 10 m, bleeder resistor (DIN IEC 312) <1 mΩ/m, diameter 32 /22 mm, in carton</p> | D 32/22x10m-AS-GQ/CT | 200051 |

System accessories

CLEANTEC suction hose

**Suction hose D 21,5**

for direct connection (without reducing ring) to hand sanding block with extraction, diameter 21,5 mm, length 5 m, in bag

| Type | Order no. |
|-----------------|-----------|
| D 21,5 x 5m HSK | 495019 |

Accessories for mobile dust extractors CT and dust extractors SR

CLEANTEC hose sleeves

**Antistatic rotating adapter**

hose connector to fit inlet nozzle of dust extractor, external \varnothing 58 mm, in self-service display pack

for antistatic suction hose D 27

| Type | Order no. |
|-------------|-----------|
| D 27 DAG-AS | 452892 |



for D 27/32 antistatic suction hose

| | |
|-------------------|--------|
| D 32/27 DAG-AS/CT | 500672 |
|-------------------|--------|



for antistatic suction hose D 36

| | |
|-------------|--------|
| D 36 DAG-AS | 202860 |
|-------------|--------|



for antistatic suction hose D 50

| | |
|-------------|--------|
| D 50 DAG-AS | 452896 |
|-------------|--------|



for antistatic suction hose plug it D 27/22, smooth

| | |
|-------------------|--------|
| D 36 DAG-AS-GQ/CT | 202931 |
|-------------------|--------|



for antistatic suction hose plug it D 32/22, smooth

| | |
|-------------------|--------|
| D 50 DAG-AS-GQ/CT | 203206 |
|-------------------|--------|

Reducing sleeve, antistatic

in self-service display pack



for suction hose D 27, for all power tools with D27 flange and cleaning accessories, hose connector for electric tool or suction nozzle, the bayonet fitting produces a secure connection between the mobile dust extractor and the power tool

| | |
|---------------|--------|
| D 27 DM-AS/CT | 202346 |
|---------------|--------|



for all power tools with D27 and D36 flange (all Festool power tools) and cleaning accessories, only for the smooth suction hoses with integrated plug it cable, for connection to tools (power tools or suction nozzle), the secure connection between the mobile dust extractor and the power tool thanks to the bayonet fitting

| | |
|------------------|--------|
| D 27/22 DM-AS/CT | 500668 |
|------------------|--------|

**Y-piece, antistatic**




for D 50/D 36/D 27, for connection of two dust extraction hoses, with blanking plug, for extractors that admit hazardous dust, simultaneous operation is not permitted, in self-service display pack

| | |
|-------------------|--------|
| D 50 SV-AS/D 50 V | 452898 |
|-------------------|--------|



System accessories

Accessories for mobile dust extractors CT and dust extractors SR

Tubes





| | | Type | Order no. |
|---|--|-----------------|-----------|
|  | Hand tube for D 27/D 36, antistatic, with sliding air regulator for suction power adjustment, curved, in self-service display pack | D 36 HR-K AS | 203129 |
|  | Extension pipe for D 27/D 36, of stainless steel, 3-piece, length 950 mm, in self-service display pack | D 36 VR-M 3x | 452902 |
|  | for D 27/D 36, antistatic, 3-piece, length 950 mm, in self-service display pack | D 36 VR-K AS 3x | 203137 |

Floor nozzles

| | | Type | Order no. |
|---|--|-------------|-----------|
|  | Floor nozzle for D 27/D 36, high-quality industrial design, aluminium, with 2 castors and 2 brush inserts, width 370 mm, in carton | D 36 BD 370 | 452908 |
|  | for D 27/D 36, plastic, with 2 castors and 2 brush inserts, width 300 mm, in self-service display pack | D 36 BD 300 | 452907 |

Accessories for CT mobile dust extractors




Special nozzles/brushes

| | | Type | Order no. |
|---|--|-------------|-----------|
|  | Crevice nozzle plastic, in self-service display pack for D 27/D 36, length 300 mm | D 36 FD-300 | 452904 |
|  | for D 27/D 36, length 210 mm | D 36 FD-210 | 492391 |
|  | Suction brush Plastic, in self-service display pack for D 27/D 36, diameter 70 mm | D 36 SP | 440404 |
|  | Universal brush nozzle for D 27/D 36, plastic, with brush rim and rotary hinge, in self-service display pack | D 36 UBD | 498527 |





System accessories

Accessories for CT mobile dust extractors

Modules for attachment system CTL/CTM 26/36/48

| | | Type | Order no. |
|---|---|-----------------------------|-----------|
|  | Energy box module for CT 26/36/48, for connecting a CT mobile dust extractor with an energy box or boom arm, not required in LE version, in carton | EAA CT 26/36/48 | 496143 |
|  | Electrical outlet module for CT 26/36/48, in carton | | |
| | electrical outlet with continuous power | Modul-SD CT 26/36/48 | 496142 |
| | electrical outlet with automatic On and Off switch | Modul-SD E/A CT 26/36/48 | 496405 |
|  | Compressed air module for CT 26/36/48, for upgrading E model mobile dust extractors, with additional compressed air automatic On and Off switching mechanism, in carton | DL CT 26/36/48 | 496141 |




CLEANTEC filter

| | | Type | Order no. |
|---|---|------------------|-----------|
|  | Main filter for CTL MINI/MIDI, in self-service display pack | HF-CT-MINI/MIDI | 456790 |
| | For CT 26/36/48 and TURBO II, not suitable for mobile dust extractors with AUTOCLEAN function, in carton | HF-CT 26/36/48 | 496170 |
|  | for CT 11, 22, 33, 44, 55, qty. in pack 2 piece(s), in carton | HF-CT/2 | 452923 |
|  | Long-life main filter for CT 11, 22, 33, 44, 55, used only for extraction of dust types which are not hazardous to health, qty. in pack 2 piece(s), in carton | Longlife-HF-CT/2 | 454869 |
|  | Wet filter for wet extraction | | |
| | for CTL MINI/MIDI, in self-service display pack | NF-CT MINI/MIDI | 456805 |
| | for CT 26/36/48, in self-service display pack | NF-CT 26/36/48 | 496169 |

System accessories


Accessories for CT mobile dust extractors

CLEANTEC filter bags



| | Type | Order no. |
|---|---|---------------------------------------|
|  | SELCLEAN filter bag qty. in pack 5 piece(s), in carton for CTL MIDI, optimum usage of filter bag volume and constantly high suction power thanks to SELFCLEAN filter bag | SC FIS-CT MIDI/5 498411 |
| | for CT 26, optimum usage of filter bag volume and constantly high suction power thanks to SELFCLEAN filter bag | SC FIS-CT 26/5 496187 |
| | for CT 36, optimum usage of filter bag volume and constantly high suction power thanks to SELFCLEAN filter bag | SC FIS-CT 36/5 496186 |
| | for CT 48, optimum usage of filter bag volume and constantly high suction power thanks to SELFCLEAN filter bag | SC FIS-CT 48/5 497539 |
|  | Filter bag in carton for CT 22, qty. in pack 5 piece(s) | FIS-CT 22/5 452970 |
| | for CT 22, qty. in pack 20 piece(s) | FIS-CT 22/20 494631 |
| | for CT 33, qty. in pack 20 piece(s) | FIS-CT 33/20 494632 |
| | for CT 55, qty. in pack 5 piece(s) | FIS-CT 55/5 452973 |
| | for CT 22, with spunbond outer layer, extremely tearproof, for extracting fine dust particles, qty. in pack 5 piece(s) | FIS-CT 22 SP VLIES/5 456870 |
| | for CT 33, with spunbond outer layer, extremely tearproof, for extracting fine dust particles, qty. in pack 5 piece(s) | FIS-CT 33 SP VLIES/5 456871 |
|  | for CT 44, with spunbond outer layer, extremely tearproof, for extracting fine dust particles, qty. in pack 5 piece(s) | FIS-CT 44 SP VLIES/5 456874 |

Accessories for mobile dust extractors CT and dust extractors SR

CT accessories








| | Type | Order no. |
|---|---|---|
|  | Tool holder in carton for CT 26/36, galvanised steel tool holder for sanders, for stable and ergonomic placement of an electrical or compressed air power tool | WHR-CT 496122 |
| | Sealing slide for CT AC / CT 36 AC PLANEX, ensures extreme vacuum in container, the filter undergoes thorough cleaning, in carton | VS-CT AC/SRM45 PLANEX 497926 |

CT compressed air accessories

| | Type | Order no. |
|---|--|---------------------------------|
|  | Compressed air module to convert the CT mobile extractor, model E to LE design with additional automatic on/off switch for air tools, only suitable for CT 22/33/44, in carton | DLM-CT 452829 |
|  | Service unit for LE version of CT 26/36/48, pressure controller, condensate quick discharge, oiler and oil-free compressed air outlet with quick coupling, in carton | VE-CT 26/36/48 495886 |

System accessories

for exhaust turbines TURBO II

| | | Type | Order no. |
|---|--|-------------------------|-----------|
|  | <p>Main filter approved for dust class M, filtration of dust, filter surface area 25.000 cm², in carton</p> | | |
| | for TURBOII-8WP/14WP | HF-TURBOII 8WP/14WP | 499902 |
|  | for TURBOII-8WP/14WP ATEX, filtering dust in Zone 22 | HF-EX-TURBOII 8WP/14WP | 499903 |
|  | <p>Disposable bag for TURBOII-8WP/14WP and TURBOII-8WP/14WP ATEX, for dust-free disposal of hazardous dust, qty. in pack 5 piece(s), filling volume 50 l, in carton</p> | ENS-TURBO II /5 | 499904 |
|  | <p>Dust bag for TURBO 3091, 4001, 7501, for extraction turbine Turbo 3091, 4001, 7501, in bag</p> | STB-TURBO 10X | 492730 |
|  | <p>Boom arm for TURBO 3091, 4001, 7501, double-jointed arm with wall bracket, wall mounting components are not included, connecting cable length 3 m, in carton</p> | | |
| | boom extension 2 x 2,5 m, application area 39 – 58 m ² , weight 92 kg, cutting angle adjustment 39 – 58° | ASA 5000 TURBO-EU | 583856 |
|  | boom extension 2 x 3 m, application area 56 – 84 m ² , weight 105 kg, cutting angle adjustment 56 – 84° | ASA 6000 TURBO-EU | 583857 |
|  | <p>Energy box for Turbo, automatic slide control, automatic energy box without compressed air tools but with pressure reducer, 2 x Abrasive paper holder, energy box with 3 x 230 V connections, compressed air supply unit with 3 compressed air connections (2 x oiled and 1 x not oiled), dimensions (L x W x H) 516 x 580 x 367 mm, pressure range 4 – 8 bar, weight 13,8 kg, in carton</p> | EAA EW/DW TURBO/A-EU | 583831 |



WORKPLACE ORGANISATION

PROFESSIONALS IN ORGANISATION.

| | |
|------------------------------------|------------|
| Complete sets | 124 |
| Sets | |
| Boom arms | 130 |
| ASA | |
| Energy box | 131 |
| EAA | |
| Workcenter | 132 |
| WCR | |
| Multifunction stool | 133 |
| MFH 1000, UCR 1000 | |
| Toolcenter | 134 |
| TC 3000/2 | |
| Work light | 135 |
| SYSLITE KAL II | |
| Construction site radio | 136 |
| SYSROCK BR 10 | |
| Storage systems | 140 |
| SYSTAINER, SORTAINER, ToolBox | |
| Transport systems | 142 |
| SYS-Port, SYS-Roll, SYS-Cart | |
| Accessories and consumables | 137 |

The Festool system

Spot repair set

Set for spot repair process



Sales booster

Eliminating even the smallest of scratches has the potential to further increase customer satisfaction and increase sales. Offer your customers a service at a fixed price when they accept the vehicle and benefit from a competitive advantage. Repair defects, boost sales. That is what spot repair is all about.

Your customers will thank you. And so will your wallet.

| Items included | Order no. |
|--|-----------|
| CTM 26 E mobile dust extractor | 574981 |
| WCR 1000 Workcenter | 497471 |
| ROTEX RO 90 DX geared eccentric sander | 571819 |
| FX-RO 90 polishing pad, 80 mm diameter | 495625 |
| D27/22 smooth suction hose with plug it, 3.50 m, anti-static | 200041 |
| 1x5 CT 26 SELFCLEAN filter bags | 496187 |
| SD-CT 26/36/48 electrical outlet module | 496142 |
| Dry guide coat powder set | 495939 |
| 1x100 GRANAT P120 abrasive, 90 mm diameter | 497367 |
| 1x100 GRANAT P180 abrasive, 90 mm diameter | 497369 |
| 1x100 GRANAT P280 abrasive, 90 mm diameter | 497850 |
| 1x100 GRANAT P400 abrasive, 90 mm diameter | 497373 |
| 1x15 PLATIN 2 S1000 abrasive, 90 mm diameter | 498323 |
| 1x15 PLATIN 2 S2000 abrasive, 90 mm diameter | 498324 |
| Abrasives SYSTAINER RO 90 | 497687 |
| MPA 5010 one-step sanding polish (500 ml) | 202048 |
| Finish cleaner (500 ml) | 202053 |
| 1x5 polishing pads, orange, 80 mm diameter | 201993 |
| Microfibre cloth (green and grey) | 493068 |

EC electric sanding set

Set for sanding process

Power is its strength.

| Items included | Order no. |
|--|-----------|
| CTM 48 E LE EC mobile dust extractor | 575298 |
| Alternative: CTM 36 E LE mobile dust extractor | 574990 |
| WCR 1000 Workcenter | 497471 |
| ETS EC 150/3 electric eccentric sander | 575032 |
| ETS EC 150/5 electric eccentric sander | 575043 |
| WCR 1000 LPH paint gun holder | 498361 |
| D27/22 smooth suction hose with plug it, 3.50 m, anti-static | 200041 |
| 1x5 CT 48 SELFCLEAN filter bags | 497539 |
| Alternative: 1x5 CT 36 SELFCLEAN filter bags | 496186 |
| Dry guide coat powder set | 495939 |
| 2x50 GRANAT P80 abrasive, 150 mm diameter | 575162 |
| 1x100 GRANAT P180 abrasive, 150 mm diameter | 575166 |
| 1x100 GRANAT P280 abrasive, 150 mm diameter | 575169 |
| 1x100 GRANAT P400 abrasive, 150 mm diameter | 575172 |
| 2x15 PLATIN 2 S1000 abrasive, 150 mm diameter | 492370 |
| Four-step economy SYSTAINER D, 150 mm | 497821 |
| 1x200 cleaning cloth, 240x380 mm | 498071 |



Health specialist

The quality has to be right. As does the quality of the air we breathe in. Two priorities for which Festool makes no compromises.

The automatic dust extraction control on the ETS EC electric eccentric sander guarantees that the workplace is completely safe, while the four-step sanding process ensures perfect results.

EC compressed air set

Set for sanding process



Trendsetter

You must be able to work with compressed air. And you must be able to use the LEX 3 Generation with long-life motor technology. This compressed air solution for an even faster sanding process can save you money and keep energy costs to a minimum.

Save with compressed air.

| Items included | Order no. |
|--|-----------|
| CTM 48 E LE EC mobile dust extractor | 575298 |
| Alternative: CTM 36 E LE mobile dust extractor | 574990 |
| WCR 1000 Workcenter | 497471 |
| LEX 3 150/3 compressed air eccentric sander | 574996 |
| LEX 3 150/5 compressed air eccentric sander | 575081 |
| WCR 1000 LPH paint gun holder | 498361 |
| IAS hose IAS 3 light 3500 antistatic | 497478 |
| 1x5 CT 48 SELFCLEAN filter bags | 497539 |
| Alternative: 1x5 CT 36 SELFCLEAN filter bags | 496186 |
| Dry guide coat powder set | 495939 |
| 2x50 GRANAT P80 abrasive, 150 mm diameter | 575162 |
| 2x100 GRANAT P180 abrasive, 150 mm diameter | 575166 |
| 2x100 GRANAT P280 abrasive, 150 mm diameter | 575169 |
| 2x100 GRANAT P400 abrasive, 150 mm diameter | 575172 |
| 2x15 PLATIN 2 S1000 abrasive, 150 mm diameter | 492370 |
| Four-step economy SYSTAINER D, 150 mm | 497821 |
| 1x200 cleaning cloth, 240x380 mm | 498071 |

Safety set

Set for sanding process

The topic of safety should not be sitting and gathering dust.

| Items included | Order no. |
|---|-----------|
| CTM 48 E LE EC/B22 mobile dust extractor | 575286 |
| WCR 1000 Workcenter | 497471 |
| LEX 3 150/3 compressed air eccentric sander | 574996 |
| LEX 3 150/5 compressed air eccentric sander | 575081 |
| IAS hose IAS 3 light 3500 antistatic | 497478 |
| 1x5 CT 48 SELFCLEAN filter bags | 497539 |
| Dry guide coat powder set | 495939 |
| 2x50 GRANAT P80 abrasive, 150 mm diameter | 575162 |
| 2x100 GRANAT P180 abrasive, 150 mm diameter | 575166 |
| 2x100 GRANAT P280 abrasive, 150 mm diameter | 575169 |
| 2x100 GRANAT P400 abrasive, 150 mm diameter | 575172 |
| 2x15 PLATIN 2 S1000 abrasive, 150 mm diameter | 492370 |
| Four-step economy SYSTAINER D, 150 mm | 497821 |
| 1x200 cleaning cloth, 240x380 mm | 498071 |



Bodyguard

The increased use of aluminium, carbon and fibreglass in vehicles warrants extra care when dealing with these materials – or a safety concept which complies with the ATEX Directive 94/9/EC for Zone 22 and simply extracts all dry and flammable dust and collects it in a flame-resistant plastic container.

High-polish set I

Set for the polishing process



Gloss accelerator

Achieve high gloss at high speed in two extremely short steps as part of the standard work process. Work using the Festool set versions is finished in a flash and means that you can have the largely unpaid polishing work done in no time.

In pole position for polishing.

| Items included | Order no. |
|---|-----------|
| UCR 1000 Universalcenter | 498966 |
| SHINEX RAP 150-14 FE rotary polisher | 570809 |
| 2x50 GRANAT P1500 abrasive, 77 mm diameter | 498932 |
| 1x5 premium sheepskin pads, 150 mm diameter | 202046 |
| Spot repair scraper | 497525 |
| 1x5 MPA 5010 one-step sanding polish (500 ml) | 202048 |
| Finish cleaner (500 ml) | 202053 |
| Microfibre cloth (green and grey) | 493068 |
| 1x200 cleaning cloths, 240x380 mm | 498071 |

Swirl mark set

Set for the polishing process

Twinkling in the darkness.

| Items included | Order no. |
|--|-----------|
| ROTEX RO 150 FEQ swirl mark specialist | 575066 |
| PT-STF polishing pad, 150 mm diameter | 496151 |
| MPA 11010 high-gloss polish (500 ml), 6x | 202051 |
| Microfibre cloth (green and grey) | 493068 |
| Pad, white, waffle face, 150 mm diameter, 5x | 202014 |



Swirl mark remover

Microfine grooves in dark clear coats need special handling after polishing. Thanks to the ROTEX rotary motion, these swirl marks smooth out to form a perfect shine across the entire surface in no time at all.

ASA

Boom arm ASA



Workplace changes made easy.

Boom arms are primarily used in locations where workplaces need to be flexible or where a large operating radius is required. Power and dust extraction is supplied where it is needed, while avoiding tripping hazards. This saves you time moving equipment and creates more space in the workshop.


For large working areas.

- ▶ Maximum flexibility, extra safety, no dangerous obstacles
- ▶ For use with Festool CT/SRM mobile dust extractors
- ▶ Integrated compressed air and electrical lines for connection to EAA and CT/Turbo II
- ▶ Saves time, space and increases economic efficiency

| Technical data | ASA 5000 | ASA 6000 |
|------------------------------------|----------|----------|
| Connecting cable length (m) | 3 | 3 |
| Boom extension (m) | 2 x 2,5 | 2 x 3 |
| Application area (m ²) | 39 – 58 | 56 – 84 |
| Weight (kg) | 92 | 105 |
| Cutting angle adjustment (°) | 39 – 58 | 56 – 84 |

| Items included | Order no. |
|--|---------------|
| double-jointed arm with wall bracket, wall mounting components are not included, in carton | |
| ASA 5000 CT/SR-EU cable duct | 583867 |
| ASA 6000 CT/SR-EU cable duct | 583868 |
| ASA 5000 TURBO-EU | 583856 |
| ASA 6000 TURBO-EU | 583857 |

System accessories from page 137



EAA

EAA energy box CT/SR Turbo II



For greater ease of movement.

- ▶ Manual or automatic adjustment of the slide valve provides suction power wherever an electric and/or air tool is in operation
- ▶ Flexible – the EAA can be mounted on a ceiling, wall or boom arm
- ▶ Always ready for use by up to 2 electrical and/or compressed air power tools (depending upon the version of the EW/DW)
- ▶ Better organisation – two hoses can be stored and kept clean in the hose holders on the rear of the EAA

| Technical data | EAA EW CT/SRM/M | EAA EW/DW CT/SRM/M | EAA EW/DW TURBO/A |
|-----------------------------|--------------------|-----------------------|----------------------|
| Dimensions (L x W x H) (mm) | 506 x 580 x 367 | 516 x 580 x 367 | 516 x 580 x 367 |
| Pressure range (bar) | 4 – 8 | 4 – 8 | 4 – 8 |
| Weight (kg) | 10,2 | 13 | 13,8 |

Sophisticated design right down to the smallest detail.

The EAA, with manually or automatically operated sliders for use with CT mobile dust extractors or the TURBO II central exhaust, spares the user from cumbersome handles and travels, and ensures optimal dust extraction. Electric power tools and air tools are ready for use and ready to hand at all times.

| Items included | Order no. |
|--|---------------|
| energy box with 3 x 230 V connections, 2 x Abrasive paper holder, in carton | |
| EAA EW CT/SRM/M-EU | 583820 |
| EAA EW/DW CT/SRM/M-EU compressed air supply unit with 3 compressed air connections (2 x oiled and 1 x not oiled) | 583821 |
| EAA EW/DW TURBO/A-EU compressed air supply unit with 3 compressed air connections (2 x oiled and 1 x not oiled) | 583831 |

System accessories from page 137



WCR 1000

WCR 1000 Workcenter



product design award
2011



Scan the page to discover hidden 3D graphics, videos and images.

Customised configuration.

SYSTEMAINER sizes 1 to 4 or SORTAINERS can be integrated into the Workcenter.

Mobility in the tightest of spaces.

- ▶ Compact and mobile – the WCR can be coupled with any Festool mobile dust extractor with integral SYS-Dock (except CTL MINI/MIDI)
- ▶ Flexible equipment – hooks for hanging two machines with extractor hoses, a universal holder, storage compartment and rotating storage tray for sundries
- ▶ Individual extension – additional storage trays, hooks or holders can be mounted on the perforated plate and profiled groove
- ▶ Work without straining your back – the height of the Workcenter, hooks and storage trays is easy to adjust

Technical data

| | |
|---|-----------|
| Length (mm) | 1.050 |
| Width (mm) | 362 |
| Height adjustable (mm) | 545 – 785 |
| Size of square hole pattern (mm) | 9,2 x 9,2 |
| Inner hole distance of square hole pattern (mm) | 38 |
| Weight (kg) | 10,2 |

Items included

WCR 1000

Storage shelf, storage trough, storage base for pegboard, double tool hook, double universal hook, 6 x standard hooks (125 mm long), 2 x pegboards with square holes, SYSTEMAINER retainer, in carton

Order no.

497471

System accessories from page 138





MFH 1000 / UCR 1000

Multifunction stool MFH 1000
and Universalcenter UCR 1000

Mobile seating arrangement, efficient work.

- ▶ Multifunction stool MFH 1000 + Workcenter WCR 1000 = Universalcenter UCR 1000
- ▶ Use the Universalcenter UCR 1000 in mobile applications and benefit from the advantages of the Workcenter WCR 1000
- ▶ Pleasant working environment – without the Workcenter WCR, the multifunction stool MFH 1000 is a stable, comfortable seat
- ▶ Efficient organisation – hooks and storage trays ensure quick access to machines, accessories and work equipment



Clever, mobile organisation.

Pull-out drawer that can be locked – for storing accessories, work equipment and personal effects.

| Technical data | MFH 1000 | UCR 1000 |
|---|-----------------|---------------|
| Length (mm) | | 695 |
| Dimensions (L x W x H) (mm) | 695 x 436 x 524 | |
| Width (mm) | | 436 |
| Width of roll (mm) | 32 | 32 |
| Height adjustable (mm) | | 1.031 – 1.271 |
| Roll dia. (mm) | 100 | 100 |
| Size of square hole pattern (mm) | 9,2 x 9,2 | 9,2 x 9,2 |
| Inner hole distance of square hole pattern (mm) | 38,1 | 38,1 |
| Weight (kg) | 27 | 37 |

| Items included | Order no. |
|---|---------------|
| in carton | |
| MFH 1000 seat cushion MFH 1000 SK, Assembly set | 498967 |
| UCR 1000 WCR 1000 Workcenter, multifunction stool MFH 1000 (without seat cushion) | 498966 |

System accessories
from page 138



TC 3000/2

Toolcenter TC 3000/2



Scan the page to discover hidden 3D graphics, videos and images.

Safety included.

Locking cabinet compartment for size 3 SYSTAINERS or smaller provides safe storage for machines and accessories.

Flexibility and extra work space.


- ▶ Beneficial organisation – tools, materials and mobile dust extractor are always stored away tidily and close at hand
- ▶ Mobile equipment – simple transportation between different locations in the workshop
- ▶ Secure attachment – the mobile dust extractor is secured safely in the extractor dock
- ▶ More space – machine and hose holders keep storage areas free for working equipment

Technical data

| | |
|----------------------------------|-------------------|
| Dimensions (L x W x H) (mm) | 470 x 1.070 x 960 |
| Storage area (mm) | 460 x 990 |
| Storage area working height (mm) | 925 |
| Weight (kg) | 43 |

| Items included | Order no. |
|--|-----------|
| TC 3000/2 hose holder, anti-slip mat, in carton | 583881 |

System accessories from page 139



SYSLITE KAL II

SYSLITE KAL II working light



product
design award

2012

The light to the tool.

- ▶ Excellent light thanks to 12 high-performance LEDs
- ▶ Long life and robust thanks to shatter-proof housing
- ▶ Continuous use – any Festool battery pack can be attached to supplement the internal battery. The 230 V mains power pack and vehicle charging cable offer additional charging and power supply options
- ▶ Compact design – can be flexibly positioned without cable hazards

Technical data

| | |
|---|----------------|
| Light source (W) | 12 x 1,5 |
| Lumen value 1st/2nd stage (lm) | 310/769 |
| Operating time (internal battery) 1st/2nd stage (min) | 290/110 |
| Li-ion battery capacity (Ah) | 2,9 |
| Li-ion charging time (min) | 200 |
| Permissible operating temperature range (°C) | -5/+ 55 |
| Operation with external Festool battery packs (V) | 10,8 – 18 |
| Hook opening (mm) | 40 |
| Thread size stand (") | 1/4 |
| Dimensions (L x W x H) (mm) | 80 x 100 x 150 |
| Weight (without battery pack) (kg) | 0,7 |

Items included

integrated lithium-ion battery 7.2 V, 230 V adapter, car charger adapter, transport bag, in self-service display pack

KAL II

500721

KAL II-Set

499815

magnetic spherical head with flat disc



Total flexibility.

Five available installation and mounting positions: The SYSLITE KAL II lights up the darkest of corners for up to six hours non-stop. The housing is made from shatter-proof, shock-proof and impact-resistant cast aluminium – durable enough for any construction site. The large light dispersion angle of 170° ensures that the entire work surface is illuminated uniformly.

Magnet spherical head Order No. 499814



SYSROCK

SYSROCK BR 10 and BR 10 DAB+ construction site radios



Light, compact and powerful.

The SYSROCK construction site radios fit on every windowsill and combine compact dimensions with a low weight and impeccable sound. And thanks to the Bluetooth interface, you can listen to your favourite radio stations and tracks from your smartphone with SYSROCK sound quality.

Perfectly formed for perfect sound. Also available as a DAB+ version.


- ▶ Various receiving and playback options via Bluetooth and AUX-IN interfaces – available as analogue or digital radio
- ▶ Integrated USB interface for charging external devices such as mobile devices (with BR 10 DAB+)
- ▶ Excellent sound in a compact, modern and robust design
- ▶ Intuitive operation via large buttons and colour LCD display

| Technical data | BR 10 DAB+ | BR 10 |
|---|--------------------|-------------------|
| Radio reception | DAB+ digital radio | FM analogue radio |
| FM frequency band (VHF) (MHz) | 87,5 – 108 | 87,5 – 108 |
| Speaker (W) | 10 | 10 |
| Operation with Festool slide-in battery packs (V) | 18 | 18 |
| Number of stored stations | 2 x 4 | 4 |
| AUX-IN (mm) | 3,5 | 3,5 |
| Bluetooth standard | 4,1 | 4,1 |
| USB output | 5V/1,2A | – |
| Dimensions (L x W x H) (mm) | 95 x 102 x 149 | 94 x 102 x 149 |
| Weight (kg) | 0,7 | 0,7 |



| Items included | Order no. |
|---|---------------|
| 230 V adapter, aux-in cable, in bag | |
| BR 10 DAB+ DAB+ digital radio | 202111 |
| BR 10 FM analogue radio | 200183 |


System accessories



Accessories for the ASA boom arm, EAA energy box

| Denomination | Explanation | Order no. |
|-------------------------------------|--|-----------|
| 1 Ceiling suspension EAA-D-EU | for energy boxes (models starting in 2009), 2.5 m cable set, 2.5 m compressed air hose, mounting, aluminium tube (1310 mm) with connecting sleeve, in carton | 495890 |
| 2 Wall mounting EAA-W-EU | for energy boxes (models starting in 2009), 4 m cable sets, 4 m compressed air hose, aluminium tube (350 mm) with connecting sleeve, installation set for energy boxes, in carton | 495889 |
| 3 Boom arm ASA 5000 CT/SR-EU | for CT mobile dust extractors and SRM extractors, double-jointed arm with wall bracket, cable duct, wall mounting components are not included, connecting cable length 3 m, boom extension 2 x 2,5 m, application area 39 – 58 m ² , weight 92 kg, cutting angle adjustment 39 – 58°, in carton | 583867 |
| Boom arm ASA 6000 CT/SR-EU | for CT mobile dust extractors and SRM extractors, double-jointed arm with wall bracket, cable duct, wall mounting components are not included, connecting cable length 3 m, boom extension 2 x 3 m, application area 56 – 84 m ² , weight 105 kg, cutting angle adjustment 56 – 84°, in carton | 583868 |
| Boom arm ASA 5000 TURBO-EU | for Turbo 3091, 4001, 7501; double-jointed arm with wall bracket; wall mounting components are not included; in a carton | 583856 |
| Boom arm ASA 6000 TURBO-EU | for Turbo 3091, 4001, 7501; double-jointed arm with wall bracket; wall mounting components are not included; in a carton | 583857 |
| 4 Abrasive paper holder SH-EAA | without mounting hardware, for abrasives up to Ø 150 mm, in carton | 496044 |
| 5 Energy box module EAA CT 26/36/48 | for CT 26/36/48, for connecting a CT mobile dust extractor with an energy box or boom arm, not required in LE version, in carton | 496143 |
| 6 IAS 3 hose | from page 89 | |

System accessories




Accessories for Workcenter WCR 1000, Universalcenter UCR 1000, multifunction stool MFH 1000

| Denomination | Explanation | Order no. |
|-------------------------------------|---|-----------|
| 1 Feather key WCR 1000 PF 2x | for WCR 1000, UCR 1000, The keys enable the attachment of individual accessories to the profiled groove, 2x keys incl. bits, in self-service display pack | 497476 |
| 2 Pegboard hook HSK LWH HSK-A | for WCR 1000, MFH 1000, UCR 1000, for hanging hand sanding blocks HSK-A 80x130, HSK-A 80x200 and HSK-A 115x226, not suitable for hand sanding block HSK-A 80x400, the protective coating prevents damage, dimensions length x width 38,1 x 38,1 mm, in carton | 498968 |
| 3 Tool hook WCR 1000 WH | for WCR 1000, UCR 1000, for hanging two tools, for use as a hose holder, in carton | 497474 |
| 4 Hook WCR 1000 SHQ | for WCR 1000, UCR 1000, Standard hooks for mounting on the pegboard, qty. in pack 6 piece(s), in self-service display pack | 497475 |
| 5 Holder for spray gun WCR 1000 LPH | for WCR 1000 Workcenter, holder for paint gun, for assembly at the profile groove for the WCR 1000 Workcenter, 2x screw, 2x square nut, dimensions [L x W x H] 148 x 76 x 60 mm, weight 0,5 kg, in carton | 498361 |
| 6 Storage surface WCR 1000 AB | for WCR 1000, UCR 1000, Large storage surface for placing sundries, boxes of abrasives or screws, etc., in carton | 497477 |

System accessories











TC 3000/2



Accessories for the TC 3000/2 Toolcenter




| Denomination | Explanation | Order no. |
|---------------------------|---|-----------|
| 1 Rear wall TC 3000 RW | for Toolcenters TC 3000, TC 3000/2 incl. 10 hooks, dimensions length x width 990 x 340 mm, in carton | 452986 |
| 2 Tool holder WHR/D-TC | for the TC 2000, TC 3000, TC 3000/2, for safe, ergonomic storage of two electric and air tools at the same time, in carton | 493415 |
| 3 Hose holder TC-SH | for the TC 2000, TC 3000, TC 3000/2, for retrofitting TC 3000, in carton | 487304 |
| 4 Service unit VE-TC 3000 | for Toolcenter TC 2000, TC 3000, for compressed air supply to mobile dust extractors CT 22/33 and SR 151, SR 200 series dust extractors in LE design, in carton | 454808 |

System accessories



| SYSTAINER T-LOC | | Type | Order no. |
|---|--|---------------|---------------|
|  | SYSTAINER T-LOC 1x cover for label field | | |
| | dimensions [L x W x H] 396 x 296 x 105 mm, dimensions with adjustable legs [L x W x H] 396 x 296 x 112 mm, inner dimensions [L x W x H] 383 x 273 x 75 mm, weight 1,3 kg | SYS 1 TL | 497563 |
|  | dimensions [L x W x H] 396 x 296 x 157,5 mm, dimensions with adjustable legs [L x W x H] 396 x 296 x 164,5 mm, inner dimensions [L x W x H] 383 x 267 x 127,5 mm, weight 1,5 kg | SYS 2 TL | 497564 |
|  | dimensions [L x W x H] 396 x 296 x 210 mm, dimensions with adjustable legs [L x W x H] 396 x 296 x 217 mm, inner dimensions [L x W x H] 382 x 266 x 180 mm, weight 1,8 kg | SYS 3 TL | 497565 |
|  | dimensions [L x W x H] 396 x 296 x 315 mm, dimensions with adjustable legs [L x W x H] 396 x 296 x 322 mm, inner dimensions [L x W x H] 382 x 266 x 285 mm, weight 2,1 kg | SYS 4 TL | 497566 |
|  | dimensions [L x W x H] 396 x 296 x 420 mm, dimensions with adjustable legs [L x W x H] 396 x 296 x 427 mm, inner dimensions [L x W x H] 381 x 265 x 384 mm, weight 2,7 kg | SYS 5 TL | 497567 |
| MIDI-SYSTAINER T-LOC | | Type | Order no. |
|  | MIDI-SYSTAINER T-LOC can be connected to SYS T-LOC, for clear and structured arrangement of small parts, power tools, hand-held tools and accessories, dimensions [L x W x H] 496 x 296 x 210 mm, inner dimensions [L x W x H] 483 x 267 x 180 mm, weight 2 kg | SYS-MIDI 3 TL | 499621 |
| MINI-SYSTAINER T-LOC | | Type | Order no. |
|  | MINI-SYSTAINER T-LOC for clear and structured arrangement of small parts and hand-held tools, cannot be connected to SYS 1, SYS 2, SYS 3, SYS 4, SYS 5, SORTAINER, SYS MINI classic, can be combined with SYS-MINI 1 and 3 TL, weight 0,4 kg | | |
| | dimensions [L x W x H] 265 x 171 x 71 mm, inner dimensions [L x W x H] 255 x 155 x 53 mm | SYS-MINI 1 TL | 499622 |
|  | dimensions [L x W x H] 265 x 171 x 142 mm, inner dimensions [L x W x H] 255 x 155 x 124 mm | SYS-MINI 3 TL | 202544 |

System accessories






SYSTAINER T-LOC with lid compartment

| | | Type | Order no. |
|---|---|-------------|---------------|
|  | SYSTAINER T-LOC DF 1x cover for label field | | |
| | dimensions (L x W x H) 396 x 296 x 105 mm, dimensions with adjustable legs (L x W x H) 396 x 296 x 112 mm, inner dimensions (L x W x H) 383 x 273 x 68 mm, weight 1,5 kg | SYS 1 TL-DF | 497851 |
|  | dimensions (L x W x H) 396 x 296 x 157,5 mm, dimensions with adjustable legs (L x W x H) 396 x 296 x 164,5 mm, inner dimensions (L x W x H) 383 x 267 x 121 mm, weight 1,7 kg | SYS 2 TL-DF | 497852 |
|  | dimensions (L x W x H) 396 x 296 x 210 mm, dimensions with adjustable legs (L x W x H) 396 x 296 x 217 mm, inner dimensions (L x W x H) 382 x 266 x 173 mm, weight 2 kg | SYS 3 TL-DF | 498390 |

SYSTAINER T-LOC SYS-Combi

| | | Type | Order no. |
|---|--|-------------|---------------|
|  | SYSTAINER T-LOC flexibly divisible drawer for accessories, consumables, small parts and sundries, internal dimensions of the drawer (L x W x H) 350 x 255 x 69 mm | | |
| | combination of the classic SYSTAINER size 2 and a spacious drawer, dimensions (L x W x H) 396 x 296 x 263 mm, dimensions with adjustable legs (L x W x H) 396 x 296 x 270 mm, internal dimensions of the top compartment (L x W x H) 383 x 267 x 127 mm, weight 3,2 kg | SYS-Combi 2 | 200117 |
|  | combination of the classic SYSTAINER size 3 and a spacious drawer, dimensions (L x W x H) 396 x 296 x 315 mm, dimensions with adjustable legs (L x W x H) 396 x 296 x 322 mm, internal dimensions of the top compartment (L x W x H) 382 x 266 x 180 mm, weight 3,5 kg | SYS-Combi 3 | 200118 |

SORTAINER



| | | Type | Order no. |
|---|---|-----------------|---------------|
|  | SORTAINER 2 x small drawer (L x W x D) 255x75x30 mm, medium drawer (L x W x D) 255 x 165 x 30 mm, large drawer (L x W x D) 255 x 348 x 85 mm, 2 dividers per drawer, 6 x label holders, 8 x lettering strips, dimensions (L x W x H) 395 x 295 x 210 mm, weight 4 kg | SYS 3-SORT/4 | 491522 |
|  | 6 x medium drawer (L x W x D) 255 x 165 x 30 mm, 2 dividers per drawer, 6 x label holders, 8 x lettering strips, dimensions (L x W x H) 395 x 295 x 210 mm, weight 4,9 kg | SYS 3-SORT/6 | 491984 |
|  | 6 x small drawer (L x W x D) 255x75x30 mm, 3 x medium drawer (L x W x D) 255 x 165 x 30 mm, 2 dividers per drawer, 9 x label holders, 16 x lettering strips, dimensions (L x W x H) 395 x 295 x 210 mm, weight 5,1 kg | SYS 3-SORT/9 | 491985 |
|  | 12 x small drawer (L x W x D) 255x75x30 mm, 2 dividers per drawer, 12 x label holders, 16 x lettering strips, dimensions (L x W x H) 395 x 295 x 210 mm, weight 5,3 kg | SYS 3-SORT/12 | 491986 |
|  | three drawers, each with a capacity of 6.7 litres, can be set up and divided individually with plastic containers and partitions (plastic containers and small partitions are not included), connects to all T-LOC and Classic Systainers, SORTAINERS and CLEANTEC mobile dust extractors, dimensions (L x W x H) 396 x 296 x 322 mm, weight 5,7 kg | SYS 4 TL-SORT/3 | 200119 |

System accessories



| SYS tool box | | Type | Order no. |
|---|--|-----------------|-----------|
|  | SYS tool box for practical transportation of hand tools, consumable materials and accessories, contact surface 396 x 296 mm dimensions [L x W x H] 396 x 296 x 150 mm, height 150 mm, load capacity 7 kg, volume 12,5 l | SYS-TB-1 | 495024 |
|  | dimensions [L x W x H] 396 x 296 x 257 mm, height 257 mm, load capacity 14 kg, volume 20 l | SYS-TB-2 | 499550 |
| SYS-StorageBox | | Type | Order no. |
|  | SYS-StorageBox plastic container, no content, with individually removable plastic containers, can be connected to the entire Systainer range (except SYS-Mini), 2 x Box 60x60x71 SYS-SB, 2 x Box 60x120x71 SYS-SB, 1 x Box 180x120x71 SYS-SB, dimensions [L x W x H] 396 x 296 x 167 mm, height including handle 240 mm, weight 2,5 kg | SYS-SB | 499901 |
| Systainer-Port | | Type | Order no. |
|  | Systainer-Port no admission for assembly in car, stable full metal body, 5 x labels for drawers, with 5 SYSTAINER telescopic drawers, 4 ball bearing-mounted swivel castors (2 with locking brakes), without SYSTAINER, dimensions [L x W x H] 400 x 500 x 1.100 mm, weight 33 kg, in carton | SYS-PORT 1000/2 | 491922 |
|  | Set of castors for SYS port, for assembly on SYS-Port, diameter 75 mm, in carton | SYS-PORT R/2 | 491932 |
|  | Telescopic drawer in carton | SYS-PORT/TA/2 | 491923 |
| Systainer pull-out | | Type | Order no. |
|  | Pull-out drawer for all Systainers (Classic and T-LOC), for constructing an individual shelf system, in 32 hole grid, dimensions [L x W x H] 425 x 376 x 57 mm, max. load 20 kg, in carton | SYS-AZ | 500692 |
| | qty. in pack 5 piece(s) | SYS-AZ-Set | 500767 |
|  | Lock for SYS-AZ, simultaneous lock, for subsequent installation in the pull-out drawer SYS-AZ, locks the individual pull-out drawer on the side of the body (simultaneous), in carton | S-AZ | 500693 |

System accessories


Means of transport for SYSTAINER

| | | Type | Order no. |
|---|---|--------------|-----------|
|  | SYS-Cart for easy transportation of SYSTAINER sizes 1-5 and SORTAINERS., robust handles, 4 steering rollers, 2 of which can be locked, base 360 x 520 mm, load capacity 100 kg, roll dia. 100 mm, weight 2,8 kg, in carton | RB-SYS | 495020 |
|  | SYS roller transportation of SYS Classic and SYS T-LOC, extra large wheels (D 200 mm) for easy transportation up and down steps, rotating lockable front rollers – manoeuvre in all directions, incl. safety belt, dimensions (L x W x H) 440 x 600 x 1.100 mm, total load capacity 100 kg, drawer load capacity 5 kg, front roll dia. 75 mm, rear roll dia. 200 mm, weight 6,5 kg, in carton | SYS-Roll 100 | 498660 |





SYSTAINER T-LOC with inlays for abrasives

| | | Type | Order no. |
|---|--|-----------------------|-----------|
|  | SYSTAINER T-LOC | | |
| | with insert for abrasives Ø 125 mm, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | SYS-STF D125 | 497685 |
| | with insert for abrasives 80x133 mm, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 6, SYSTAINER size SYS 1 T-LOC | SYS-STF 80x133 | 497684 |
| | with insert for abrasives STF Delta 100x150, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 5, SYSTAINER size SYS 1 T-LOC | SYS-STF Delta 100x150 | 497686 |
| | with insert for Ø 90 mm abrasives and 93V abrasives, dimensions (L x W x H) 396 x 296 x 105 mm, number of compartments 8, SYSTAINER size SYS 1 T-LOC | SYS-STF-D77/D90/93V | 497687 |
|  | with insert for abrasives Ø 150 mm, dimensions (L x W x H) 396 x 296 x 210 mm, number of compartments 10, SYSTAINER size SYS 3 T-LOC | SYS-STF D150 | 497690 |

SYSTAINER with universal insert

| | | Type | Order no. |
|---|--|-----------|-----------|
|  | SYSTAINER T-LOC with individual removable plastic containers, plastic container, no content, dimensions (L x W x H) 396 x 296 x 105 mm, SYSTAINER size SYS 1 T-LOC | SYS 1 BOX | 497694 |

Plastic containers and inserts for SYS-StorageBox, SYS 1 BOX, SYS-Combi, SYS 4 TL-SORT/3



| | | Type | Order no. |
|---|---|----------------------------|-----------|
|  | Plastic containers | | |
| | for SYS-Storage Box SYS-SB, qty. in pack: 6, dimensions (L x W x H) 60 x 60 x 71 mm, qty. in pack 6 piece(s), in carton | Box 60x60x71/6 SYS-SB | 500066 |
|  | for SYS-Storage Box SYS-SB, qty. in pack: 4, dimensions (L x W x H) 60 x 120 x 71 mm, qty. in pack 4 piece(s), in carton | Box 60x120x71/4 SYS-SB | 500067 |
|  | for SYS-Storage Box SYS-SB, qty. in pack: 2, dimensions (L x W x H) 180 x 120 x 71 mm, qty. in pack 2 piece(s), in carton | Box 180x120x71/2 SYS-SB | 500068 |
|  | for SYS-Combi 2, SYS-Combi 3 and SYS 4 TL-SORT/3, plastic containers and compartment dividers for individual drawer partitions, 8 x box of plastic containers 60 x 60 x 71 mm, 4 x box of plastic containers 60 x 120 x 71 mm, 3 x compartment dividers, 2 x cover pads, in bag | Set 60x60/120x71 3xFT | 201124 |

System accessories

Plastic containers and inserts for SYS-StorageBox, SYS 1 BOX, SYS-Combi, SYS 4 TL-SORT/3



| | | Type | Order no. |
|---|---|----------------------|---------------|
|  | for SYS 1 T-LOC box, in carton Plastic containers red, boxes excl. content, for clear storage and organisation, dimensions (L x W x H) 49 x 49 x 71 mm, qty. in pack 12 piece(s) | Box 49x49/12 SYS1 TL | 498038 |
|  | Plastic containers yellow, boxes excl. content, for clear storage and organisation, dimensions (L x W x H) 49 x 98 x 71 mm, qty. in pack 6 piece(s) | Box 49x98/6 SYS1 TL | 498039 |
|  | Plastic containers blue, boxes excl. content, for clear storage and organisation, dimensions (L x W x H) 98 x 98 x 71 mm, qty. in pack 3 piece(s) | Box 98x98/3 SYS1 TL | 498040 |
|  | Plastic containers green, boxes excl. content, for clear storage and organisation, dimensions (L x W x H) 98 x 147 x 71 mm, qty. in pack 2 piece(s) | Box 98x147/2 SYS1 TL | 498041 |
|  | Plastic containers orange, boxes excl. content, for clear storage and organisation, dimensions (L x W x H) 49 x 245 x 71 mm, qty. in pack 2 piece(s) | Box 49x245/2 SYS1 TL | 498042 |
|  | Deep-drawer insert for SYS 1 T-LOC box, insert for fixing and positioning boxes, plastic containers are not included in the scope of delivery, in carton | Box TZE-SYS 1 TL | 498043 |

Foam inserts for SYSTAINER

| | | Type | Order no. |
|---|--|----------------|---------------|
|  | Foam insert for SYS 1-5 T-LOC, dimpled insert (for lid), base insert and diced insert, qty. in pack 3 piece(s), in bag | SYS-VARI SE TL | 497877 |
|  | Diced foam insert set for SYS 1-5 T-LOC, diced sections can be pushed out to produce any desired aperture, qty. in pack 2 piece(s), in bag | SYS-VARI RM TL | 497878 |

System accessories


Lids and bottoms for Systainers

| | | Type | Order no. |
|---|---|-------------------|-----------|
|  | Cover pad in bag | | |
| | for SYS 1-5 T-LOC, with knobs, dimensions (L x W x H) 355 x 245 x 30 mm | SE-DP SYS 1-5 TL | 498044 |
| | for SYS MAXI, with knobs, dimensions (L x W x H) 560 x 340 x 30 mm | SE-DP SYS-MAXI | 491633 |
| | for SYS MIDI 3 TL, dimensions (L x W x H) 472 x 247 x 30 mm | SE-DP SYS-MIDI | 499617 |
| | for SYS MINI TL, dimensions (L x W x H) 247 x 134 x 15 mm | SE-DP SYS-MINI TL | 499619 |
|  | Base pad in bag | | |
| | for SYS 1-5 T-LOC, protects the content | SE-BP SYS 1-5 TL | 498045 |
| | for SYS MIDI 3 TL, dimensions (L x W x H) 480 x 278 x 30 mm | SE-BP SYS-MIDI | 499618 |




Inlays and inserts for SYSTAINER

| | | Type | Order no. |
|---|--|---------------------|-----------|
|  | Multi-purpose insert for SYS MINI TL, dimensions (L x W x H) 258 x 163 x 45 mm, in bag | TZE-UNI SYS MINI TL | 499620 |

Other accessories

| | | Type | Order no. |
|--|---|-----------------------------|-----------|
|  | Cover cover for labelling panels SYS T-LOC, protects the labelling panels on the SYSTAINER T-LOC from damage and moisture, qty. in pack 10 piece(s), in self-service display pack | AB-BF SYS TL 55x85mm /10 | 497855 |

Plug it accessories

| | | Type | Order no. |
|---|--|---------------|-----------|
|  | plug it-cable in self-service display pack | | |
| | rubber insulated cable 240V plug it, length 4 m | H05 RN-F/4 | 489421 |
| | rubber insulated cable 240V plug it, length 4 m, qty. in pack 3 piece(s) | H05 RN-F/4 3x | 499851 |
|  | rubber insulated cable 240V plug it, length 5,5 m | H05 RN-F/5,5 | 201884 |
| | rubber insulated cable 240V plug it, length 7,5 m | H05 RN-F/7,5 | 489661 |
| | rubber insulated cable 240V plug it, length 10 m | H05 RN-F/10 | 500636 |
|  | green rubber-insulated cable, length 4 m | H05 BQ-F/4 | 489662 |
| | green rubber-insulated cable, length 7,5 m | H05 BQ-F/7,5 | 489663 |

Index

1/4"-CE RA-Set 37 42, 56

A

Abrasives

Cloth 94-95, 98
 Granat 92-98
 Granat Net 92, 94-96
 Platin 2 92, 94-95
 Saphir 92, 94-96
 Aluminium sanding workplaces 26, 127
 ASA 121, 130, 137
 Assembly 42
 Assembly set 42

B

Base pad

SYSTAINER 145

Battery pack

BP 18 5.2 Ah Li-Ion 54
 BP 18 6.2 Ah Li-Ion 54
 BP-XS 2.6 Ah Li-Ion 53

Bits and bit holders 55-57

Body manufacture 42, 44

Bodyshop optimisation 7

Boom arm

ASA 5000 CT/SR-EU 130, 137
 ASA 5000 CT/SR-EU 130, 137
 ASA 5000 TURBO-EU 121, 130, 137
 ASA 6000 TURBO-EU 121, 130, 137

Brush strip

RAS 180 85

C

C 18 51

Ceiling suspension EAA 131, 137

CENTROTEC 53-54, 56

Charger

MXC 53
 SCA 8 54
 TLC 6 54

Chuck

CXS, TXS 42

Circular brush RB

RAS 115, RAS 180 85

Clamping nut SM

RAS 115, RAS 180 85

Cleaning and lubricating oil

LEX 3, LRS 87

Cleaning cloth 100, 125-128

Cleaning sets 115, 118

CLEANTEC

Cleaning sets 115

CLEANTEC accessories 120

CLEANTEC compressed air accessories 129

CT 26/CT 36 18, 44, 110, 124-126

CT 48 111

CT 48 EC 22, 24, 112, 125-126

CT 48 EC/B22 26, 113, 127

CTL MIDI 109

Filters and filter bags 119-120

Hose sleeves 117

Pipes and nozzles 118

Suction hose 90, 117

Suction hose, anti-static 89, 116

Cloth 94-96

Coating

preparation 20, 22, 24, 26, 28, 60, 125-127

Compressed air eccentric sander

LEX 3 77 36, 70, 128

LEX 3 125 71

LEX 3 150 24, 26, 72, 126, 127

Compressed air orbital sander

LRS 93 73

LRS 400 74

Compressed air set 24, 126

Conversion kit

plug it 145

Cordless drills

C18 51, 54

CXS, TXS 42, 50, 53

T18+3 52, 54

Cover pad

SYSTAINER 145

CT 26/CT 36 44, 18, 110, 124-126

CT 48 111

CT 48 EC 22, 24, 112, 125-126

CT 48 EC/B22 26, 113, 127

CT accessories 116-120

Compressed air 120

CTL MIDI 109

Cup brush, TB

RAS 115, RAS 180 85

CXS 50, 53

D

Deep-drawn insert

SYS 1 Box T-LOC 144

deNibber 128

Disposal bag

TURBO II DC-TEC 121

Drilling and Fastening Accessories and

Consumables 53

Drilling and Fastening Product

Overview 48

Dust Extraction Accessories and

Consumables 115

E

EAA 121, 131, 137

EAA-W wall mounting 131, 137

EC compressed air set 24, 126

EC electric sanding set 22, 125

Eccentric sander

ETS EC 125 64, 81

ETS EC 150 22, 65, 82, 125

ETSC 125 63, 81

EC-TEC 22, 24, 26, 51-52, 63-65,

67, 112-113, 125-127

Elbow adapter

C 18, T 18+3 54

CXS, TXS 53

Electric sanding set 22, 125

Energy box 32-33, 89, 119, 121, 123, 131, 137

EAA EW CT/SRM/M-EU 131, 137

EAA EW/DW CT/SRM/M-EU 131, 137

EAA EW/DW TURBO/A-EU 121, 131, 137

EAA CT/SR 131, 137

ETS EC 125 64, 81

ETS EC 150 22, 65, 82, 125

Exhaust turbines

Turbo II DC-TEC 30-33, 114

F

FastFix 50-52, 54, 60-62, 76-80

FastFix eccentric attachment 54

FastFix polishing pad PT-STF

RO 90 DX 78

RO 125, RO 150 79-80

FastFix polishing pad ST-STF

RO 90 DX 78

RO 125, RO 150 79-80

Feather key

WCR 1000, UCR 1000 138

Filter

Filter elements 119-121

Turbo II DC-TEC 121

Wet filter 119

Filter bags

Disposal bag TURBO II DC-TEC 121

SELF-CLEAN 120

Finish cleaner 100, 124, 128

Floor nozzles 118

Foam inserts

SYSTAINER 144

G

Geared eccentric sander

ROTEX RO 90 DX 18, 60, 78, 124

ROTEX RO 125 61, 79

ROTEX RO 150 38, 44, 56, 62, 80, 129

Granat abrasive 93-98

Grinding process 20

Guide control black powder 87, 124-127

H

Hand abrasives

Cloth 98

Granat abrasive 98

Hand-sanding block HSK 28, 90, 117

Hand-sanding block set 28, 90, 117

High-gloss set I 36, 128

Hole punch

LRS 93 73, 88

Hooks

WCR 1000, UCR 1000 138

Hose holder 139

Hose sleeves 117

HSS twist drill bit 57

I

IAS 3 hose

LEX 3, LRS 87-88

IAS 3 system

LEX 3 77, LEX 3 125, LEX 3 150 87, 89

LRS 93, LRS 400 88-89

IAS adapter 87

IAS double adapter 87

- Inserts and inlays
 SYSTAINER144-145
- Interface pad IP-STF
 ETS EC 12581
 ETS EC 15082
 ETSC 12581
 LEX 3 77, LEX 3 125, LEX 3 15086
 RO 90 DX78
 RO 12579
 RO 15080
- K**
- KAL II135
- Keyless chuck
 FastFix53-54
- L**
- Level 2Add number
- LEX 3
 LEX 3 7770, 86
 LEX 3 12571, 86
 LEX 3 15072, 86
- LRS 9373, 88
 LRS 40074, 88
- M**
- MA KAL magnetic spherical head135
- Main filter for TURBO II exhaust turbines121
- MAXI-SYSTAINER140
- MFH 1000133, 138
- Microfibre cloth100, 124, 128-129
- MIDI-SYSTAINER T-LOC140
- MINI-SYSTAINER T-LOC140
- Mobile dust extractor
 CLEANTEC CT 26/CT 3618, 44, 110, 124-126
 CLEANTEC CT 48111
 CLEANTEC CT 48 EC22, 24, 112, 125-126
 CLEANTEC CT 48 EC/B2226, 113, 127
 CLEANTEC CTL MIDI109
- Modules
 CTL/CTM 26/36/48119
- Multifunction stool
 MFH 1000133, 138
- Multi-purpose insert145
- MULTI-JETSTREAM 262, 72, 80, 82, 86, 91-92
- MXC charging unit53
- O**
- Old paint set44
- ORBITAL SANDER
 RS 10066, 83
 RTSC 40067, 84
- Organise workplace Product overview123
- P**
- Paint gun holder
 WCR 1000, UCR 1000124-126, 138
- Painted finish34, 36, 99-100, 102-105
- Pegboard hook
 WCR 1000, UCR 1000, MFH 1000138
- Plastic boxes and inlays144-145
- Platin 293-95
- Plug it accessories145
- Plug it cable18, 22, 44, 116
- Polishing34, 36, 38, 76-77, 99, 128-129
- Polishing agent
 MPA 5010, MPA 9010, MPA 11010100
- Polishing pad
 RAP 150, POLLUX 18099
- Polishing process34
- Polishing sponge
 PoliStick102-105
- PoliStick102-105
- POLLUX 18077, 99
- Potential analysis7
- Process surfaces Accessories and consumables78
- Process surfaces Product overview58
- Processes7, 16, 20, 34
 Polishing process34
 Sanding process20
 Spot repair process16
- Profit zone6-7
- Protector
 RO 90 DX60, 78
 RO 12561, 79
 RO 15062, 80
- Q**
- Quality System Partner12
- R**
- Radio
 SYSROCK BR 10136
- RAP 150-14 FE36, 76, 99, 128
- RAP 150-21 FE76, 99
- Rapid charger MXC53
- RAS 11585
- RAS 18068, 85
- Ratchet set56
- 1/4"-CE RA-Set 3742, 56
- Reducing sleeve
 IAS-387
- RO 90 DX18, 60, 78, 124
- RO 12561, 79
- RO 15038, 44, 62, 80, 129
- Rotary polisher
 POLLUX 18077, 89
 SHINEX RAP 150-14 FE36, 76, 99, 128
 SHINEX RAP 150-14 FE Set
 Automotive76
 SHINEX RAP 150-21 FE76, 99
 SHINEX RAP 150-21 FE Set
 Automotive76
- Rotary sanders
 RAS 11585
 RAS 18068, 85
- ROTEX
 RO 90 DX18, 60, 78, 124
 RO 12561, 79
 RO 15038, 44, 62, 80, 129
- RS 10066, 83
- RTSC 40067, 84
- S**
- Safety set26, 127
- Sanding20, 58, 91
- Sanding block HSK28, 90, 117
- Sanding pad StickFix ST-STF, SSH-STF
 LRS 93, LRS 40088
 RO 90 DX78
 RS 10083
 RTSC 40084
- Sanding pad ST-STF
 ETS EC 12581
 ETS EC 15082
 LEX 3 77, LEX 3 125, LEX 3 15086
 RAS 115, RAS 18085
- Sandpaper holder137
- Saphir94-96
- Scraper101
- Sealant100
- Sealing slider120
- Self-adhesive sanding discs101
- Service unit
 TC 2000, TC 3000120
- Sets
 Assembly set42
 Compressed air set24, 126
 EC compressed air set24, 126
 EC electric sanding set26, 125
 Electric sanding set26, 125
 High-gloss set I36, 128
 Old paint set44
 Safety set26, 127
 Spot repair set18, 124
 Swirl mark set38, 129
- Sheepskin102-105, 128
- Shelf
 WCR 1000, UCR 1000138
- SHINEX RAP 150-14 FE36, 76, 99, 128
- SHINEX RAP 150-14 FE Set Automotive76
- SHINEX RAP 150-21 FE76, 99
- SHINEX RAP 150-21 FE Set Automotive76
- SORTAINER141
- Special nozzles/brushes118
- Spot repair process16
- Spot repair set18, 124
- Spot sander101
- Spray sealant100
- Standard work process
 Polishing process34
 Sanding process20
 Spot repair process16
- Suction hose90, 117
- Suction hose, anti-static89, 116
- Suction hose, plug it18, 22, 44, 116, 124-125
- Suction Product overview106
- Swirl mark set38, 129
- SYS-Cart143
- SYS-Combi141
- SYS-LITE KAL II135
- SYS-Port142
- SYSROCK BR 10136
- SYS-Roll143
- SYS-StorageBox142
- Systainer pull-out142

Index

| | |
|--|-----|
| SYSTAINER T-LOC | |
| Base pad | 145 |
| Cover pad | 145 |
| Foam inserts | 144 |
| Plastic containers, inserts and inlays | 144 |
| SYSTAINER with inlay for abrasives | 143 |
| SYSTAINER with universal insert | 143 |
| SYSTAINER without inserts | 140 |
| Systainer-Port | 142 |
| SYS-ToolBox | 142 |

T


| | |
|-----------------------------|----------|
| T 18+3 | 52, 54 |
| TC 3000/2 | 134, 139 |
| TLC 6 | 54 |
| Tool chuck | |
| CENTROTEC | 50-54 |
| Tool holder | |
| TC 2000, TC 3000, TC 3000/2 | 139 |
| Tool hook | |
| WCR 1000, UCR 1000 | 138 |
| Toolcenter | |
| TC 3000/2 | 134, 139 |
| Tubes | 118 |
| Turbo filter bag TF | 121 |
| TURBO II DC-TEC | |
| TURBO II M-14WP ATEX | 32, 114 |
| TURBO II M-8WP ATEX | 32, 114 |
| Twist drill bits | 57 |
| TXS | 50, 53 |

U

| | |
|--------------------|----------|
| Universal hook | |
| WCR 1000, UCR 1000 | 138 |
| Universalcenter | |
| URC 1000 | 133, 138 |
| URC 1000 | 133, 138 |

W

| | |
|--|--------------|
| Waffle face pad | 102-105, 129 |
| WCR 1000 | 132, 138 |
| Wet filter | 119 |
| Workcenter | 132, 138 |
| Working light | |
| Kal II | 42, 135 |
| Workplace organisation: Accessories and consumables | 137 |



General notes on the catalogue:

1. Please remember to fit appropriate protective devices or wear personal protective equipment when using Festool products such as compressed air and electric power tools with accessories and consumable materials or when machining hazardous materials. For further information, please refer to the relevant safety documentation or consult the relevant regulating authority if you have questions.
2. Machine specifications included in the catalogue, such as quantity specifications, time savings, coverage capacities, etc., are average values and may deviate significantly, depending on the material being processed. The manufacturer does not guarantee that the values will be achieved in each individual case. Your Festool specialist dealer will be glad to answer any queries you may have concerning this matter.
3. The machine weights specified in the catalogue usually refer to the weight of a machine ready for use and with a standard tool, but without a cable, accessories or consumables. Please note that the weights stated may deviate from the specifications in the catalogue, depending on the tool, battery pack, accessories or other additional parts used.
4. All trademark rights, patent rights and other commercial property rights mentioned in this catalogue remain the property of the relevant beneficiary, even in cases where this is not explicitly stated. The reproduction in particular of common names, trade names, goods designations, etc. in this catalogue (even if not identified as such) does not render these names exempt from trademark or brand protection legislation and does not therefore authorise anyone to use them.
5. We reserve the right to make modifications, especially to technical data or specifications, without prior notification. Individual features may vary depending on country-specific conditions.
6. Products may differ from those shown and the images may at times present components or parts that are not included as standard with the tools. If you have any questions, please contact your Festool specialist retailer.
7. Safety: All power tools and compressed air tools listed in this catalogue conform to the valid and applicable IEC or EN safety standards, depending on the type of tool (e.g. IEC/EN 61 029, IEC/EN 60 745, IEC/EN 62 841, IEC/EN 60 335, EN ISO 11 148, IEC/CISPR/EN 55 014, IEC/EN 61 000).
8. Insulation: The power tools listed in this catalogue are insulated in accordance with regulations.
9. CE conformity: All power tools and compressed air tools listed in this catalogue comply with the provisions of the relevant applicable EU directives (e.g. Machinery Directive 2006/42/EC, Low Voltage Directive 2014/35/EU, EMC Directive 2014/30/EU, RoHS Directive 2011/65/EU).
10. ISO certification: All the power tools and compressed air tools listed in this catalogue are manufactured in our production plants which are DIN EN ISO 9001 certified.



Antistatic function

Mobile dust extractors and tools with the antistatic function to prevent static charge from accumulating when working.



AUTOCLEAN for TURBO II

Automatic main filter cleaning system guarantees 100% suction power.



AUTOCLEAN

AUTOCLEAN automatic main filter cleaning system with infinitely adjustable cleaning intervals.



Torque shut-off

Intelligent technology ensures the optimum screwdriving force for every material.



FlowDetect

Health protection: The flow sensor checks for a minimum air speed of 20 m/sec and issues a warning if the air speed falls below this value.



Electronic

Speed control for adjusting to all types of materials.



MMC electronics

"Multi Material Control" power electronics with constant adjustable speed and temperature monitor for work on all types of material.



MMC digital electronics

Processor controlled "Multi Material Control" power electronics provide adjustable and constant speeds as well as temperature monitoring for work on all types of material.



PoliStick

Fast fixing concept for attaching polishing felt, polishing sponges or sheepskins – for greater efficiency.



IAS 3 system

Hose system incorporates compressed air, dust extraction and exhaust air.



IAS 3 light

Dust extraction, compressed air with external exhaust air dissipation.



IAS 3-SD

For connecting a Festool compressed air sander directly to a compressed air line (without dust extraction).



IAS 2 system

Combines three functions in one hose: compressed air supply, exhaust air extraction and dust extraction.



Smooth suction hose

With a smooth exterior which allows it to slide over surfaces perfectly.



Standard connection

Standard connection for dust extractors.



EC-TEC

The EC-TEC drive concept generates an extraordinary amount of power while consuming extremely low amounts of energy.



StickFix

Quick, economical fastening system for abrasives – no adhesives, no clamping.



MPE sanding pad

Sanding pads and sanding discs made from extremely durable materials for long service life.



Lithium-ion (Li)

Fitted with high-performance lithium ion battery pack.



Jetstream principle

The 9-hole principle for reduced dust accumulation, less heat and less clogging. Up to a 30% longer service life.



MULTI-JETSTREAM 2 principle

Sanding system with integral dust conveying concept. With the patented MULTI-JETSTREAM 2 principle.



SDS-plus

Tool holder for quick tool changes.



AIRSTREAM battery

Faster charging of battery packs thanks to AIRSTREAM technology (cooling function for faster charging) and significantly increased charging capacity.



High torque

Tool with high torque.



Protector

Protects the sanding pad and material when working close to edges.



Electronic monitoring

Electronic monitoring of the coil temperature protects against damage to the motor.



Safety sliding clutch

Mechanical sliding clutch provides protection if the tool suddenly seizes or tilts.



Start/stop function

AUTO mode, also without having to press the main switch.



ErgoFix adapter

For holding a M14 stirring rod.



FastFix

Makes changing routing, sawing, planing, sanding, drilling and screwdriving tools easier.



Starting current limiter

Simple start for household fuses.



plug it

Removable, replaceable mains cable with safety lock for quick conversion.



CLEANTEC dust extraction

Standard connector (27/36/50 mm) for dust extraction to safeguard the operator and the environment.



CLEANTEC connecting system

Integrated bayonet fitting as the connecting element between the extractor and the tool.



Electronic overload protection

Protects the motor with blocking tool.



Vibration stop

Patented VS balancing so that tools run smoothly during sanding, which makes working less hazardous.



Turbo dust extraction

Turbo dust extraction ensures clean, dust-free air and a clear view of the workpiece.



Bluetooth interface

Use of mobile devices via the Bluetooth standard.



Hands-free function

Telephone conversations (in full duplex) via feedback.



USB port

For charging external devices.



DAB +

Playback with the DAB+ standard.



Forward/Reverse rotation

For screwing and unscrewing screws.

**New Zealand**

Hindin Marquip Ltd.
1012 Great South Road
1061 Penrose - Auckland
Tel. 0064 9 9131661
hamish@hml.co.nz
www.hml.co.nz

**Norway**

MOTEK AS
Alf Bjerkesvei 22 B
BOX 81 Oekern
0508 Oslo
Tel. 0047 23 05 25 00
Fax 0047 22 64 00 63
odd-arve.rygh@motek.no
www.motek.no

**Panama**

Formica Distribution Center, S.A.
City of Panama, Panama, street
85, Urb. Ind. Los Angeles
0832-2532 WTC PANAMA
Tel. 00507 260 5503
Fax 00507 260 1440
grettel.amores@bacosa.com
www.renpar.com.py

**Paraguay**

Renpar S.A.
Juan Leopardi N° 1879 c/ Pedro Peña
2160 San Lorenzo
Tel. 00595 21 51 13 29
Fax 00595 21 51 13 29
nlopes@renpar.com.py
www.formicadistributioncenter.com

**Peru**

EURO TOOLS MASCHINEN E.I.R.L.
Costa Rica N° 513
J. Hunter, Arequipa
Tel. 0051 54 65 7454 / 0051 54 65 7455
Mob. 958370884 / 997375706
euroimportacion@hotmail.com
eurotoolsmaschinen@hotmail.com
www.euro-importacion.com

**Saudi Arabia**

Equipment plus sarl
Mkates street 41
Beirut
Libanon
Tel. 00961 1 692136
bejaniziad@equipment-plus.com
www.equipment-plus.com

**Russia**

TTS Tooltechnic Systems 000
Russia, Moscow region
Noginsk district, 142400 Noginsk,
Noginsk-Technopark area, 13
Tel. 007 49 57 75 83 54
Fax 007 49 56 41 23 72
info@festool.ru
www.festool.ru

**Serbia**

MAKSAL LINE D.O.O.
Pavla Pavlovica 11
office: Radojke Lakić 6
11000 BEOGRAD
Mob. 00381 64 127 7581
Tel. 00381 11 407 8421
Fax 00381 11 2412 266
maksal.bg@gmail.com
www.maksal-line.rs

**Singapore**

Hiap Huat Chemicals & Industrials Co.
19 Tanjong Penjuru
609021 Singapore
Tel.: 0065 67 45 4111
Fax: 0065 67 46 29 77
chem@hiaphuat.com.sg
www.hiaphuat.com.sg

**Slovenia**

MAJO D.O.O.
Goričica pri Ihanu 2
1230 Domžale
Tel. 00386-17 248 216
Fax 00386-17 241 107
majo.doo@siol.net
www.majo.si

**South Africa**

Vermont Sales (Pty) Ltd
192 Tsesebe Crescent,
Corporate Park South, Old Pretoria Road,
Randjespark, Midrand, South Africa
PO Box 264, Halfway House, 1685
Tel. 0027 (0)11 314 7711
Fax 0027 (0) 866 88 66 33
orders@vermontsales.co.za
www.festool-powertools.co.za

**Taiwan**

Bestor Trading Corp.
No.12, Chung-Yang Lane
Kuang-Fu Village Shetou
Hsiang Chang-Hua Hsien
Tel. 00886 48 72 66 97
Fax 00886 48 72 52 09
bestor.steven@msa.hinet.net
www.bestor.com.tw

**Thailand**

Häfele (Thailand) Ltd.
57 Soi Sukhumvit 64
Bangjak Prakhonong
10260 Bangkok
Tel. 0066 27 41 71 71
Fax 0066 27 41 72 72
festool@hafele.co.th
www.hafele.com/th/en

**Turkey**

www.festool.com.tr

**Ukraine**

UAB „TTS Tooltechnic Systems“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@tts-company.lt
www.festool.ua

**Uruguay**

Luganer S.A.
Martín C. Martínez 2126
Montevideo 11800
Tel. 00598 24 090 100
centroventas@luganer.com.uy
www.luganer.com.uy

**Venezuela**

Materiales Manzanillo c. a
Juan Baustista arismendi
001 Portlamar. Isla de Margarita
Tel. 0058 295 2744 601
Fax 0058 295 2744 783
Jou37@hotmail.com

**United Arab Emirates**

POLIMAR
Unit D-8 Sharjah Furniture Complex
Al Wahda Street
P.O. Box 433 Sharjah
Tel. 00971 65 33 41 47
Fax 00971 65 33 00 09
polimar@emirates.net.ae
www.polimar.com

**Belarus**

UAB „TTS Tooltechnic Systems“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@tts-company.lt
www.festool.by

**Cyprus**

K and S Industrial Supplies Ltd.
31, Vasilissis Frederikis street
P.O. Box 27147
1642 - Nicosia
Tel. 00357 22 67 46 64
Fax 00357 22 67 22 40
seraphim@cytanet.com.cy
www.festool.com



Egypt

Equipment plus sarl
Mkales street 41
Beirut
Tel. 00961 16 92 136
Fax 00961 99 25 993
info@equipment-plus.com
www.equipment-plus.com



Algeria

PRO' DISTRIBUTEUR sarl
NIF 099909080287849
LOTISSEMENT AIDJA BOUFARIK ALGERIE
Tel. 00213 25 28 39 12/13
Fax 00213 25 28 39 14
info@pro-dist.com
www.pro-dist.com



Azerbaijan

Alman Texnikalari Evi MMC
A. Molla Cuma kuc. 32
1072 Baku, Azerbaijan
Tel. 0099 4 12 565 23 23
Fax 0099 4 12 565 23 30
ale_mmc@yahoo.com
www.atemmc.com



Australia

Tooltechnic Systems Australia Pty Ltd
21-27 Evolution Drive
Postal address: PO Box 4401
Dandenong South VIC 3164
Tel. 1300 063 900
Fax 03 8845 7079
customer@tooltechnic.com.au
www.festool.com.au



Bosnien-Herzegovina

MAJO D.O.O.
Goričica pri Ihanu 2
1230 Domžale (Slovenija)
Tel. 00386 17 24 82 16
Fax 00386 17 24 11 07
majo.doo@siol.net
www.majo.si



Brazil

W&S Saura Ltda.
Av. José Fortunato Santon 580
Distrito Industrial Abdo Najara
13474-750 Americana/ São Paulo
Tel. 0055 19 3469-9889
Fax 0055 19 3469-9888
ws@wsequipamentos.com.br
www.wsequipamentos.com.br



Bulgaria

Tooltechnic Systems E00D
9, Christopher Columbus Blvd.
1592 Sofia
Bulgaria
Tel. 00359 888574208, 00359 888989917
office@festool.bg
www.festool.bg



Chile

SOCIEDAD RHEKO LTDA.
Victoria 984, Villa Llacolen
San Pedro de la Paz
4130000 Concepcion
Tel.: 0056 41 2372 060
Info@reko.cl
www.reko.cl



China

Festool China
1159 Kangqiao East Rd, No.91-Buildg 1
Kangqiao Industrial Zone
201315 Shanghai (Pudong)
Tel. 0086 21 68 18 28 00
Fax 0086 21 68 18 26 90
info@festool.cn
www.festool.cn



Estonia

UAB „TTS Tooltechnic Systems“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@tts-company.lt
www.festool.ee



Georgia

LTD Electron
Agladze str. 7/a
0154 Tbilisi
Tel. 00995 32 2911121
Mobil: 00995 599 291122
contact@rcheuli.com
khaduri@gmail.com
www.rcheuli.com



India

Caple Industrial Solutions,
WEH, Malad E, Mumbai 97.
Delhi +91 9999394047
Mumbai +91 9930069906
Bengaluru +91 9148788500
Kolkata +91 9599487490
festool.cat@caple.in
www.caple.in



Iceland

ISOL Ltd.
P.O. Box 8436
Armuli 17
128 Reykjavik
Tel. 00354 53 31 234
Fax 00354 56 80 499
isol@isol.is
www.isol.is



Iceland

Husasmidjan Ehf
Holtvegur 10
104 Reykjavik
Tel. 00354 525 3000
jono@husa.is
www.husa.is



Israel

A. Sherizly & Son Ltd.
Shderot Hamiktsoot, 15
Einav Center
Modiin - 7177849
Tel. 00972 89 23 37 77
Fax 00972 89 23 44 77
sherizly@sherizly.com
www.festool.com



Japan

Häfele Japan K.K.
14-17, Kami-Shinano, Totsuka-ku
244-0806 Yokohama
Tel. 0081 45 82 83 111
Fax 0081 45 82 83 110
festool@hafele.co.jp
www.festool.jp



Jordan

Equipment plus sarl
Mkales street 41
Beirut
Tel. 00961 16 92 136
Fax 00961 99 25 993
info@equipment-plus.com
www.equipment-plus.com



Kazakhstan

Voronin I.V.
Mikrorayon Aksay 3 a, dom 80
050031 Almaty
Tel. 007 727 242 94 55
ritm@ritm.asia
www.ritm.ltd.kz



Qatar

Equipment plus sarl
Mkales street 41
Beirut
Tel. 00961 16 92 136
Fax 00961 99 25 993
info@equipment-plus.com
www.equipment-plus.com



Columbia

Ferreteria Al-Diaz
Cra. 50 No. 71C-31
Bogotá, D.C.
Tel. 0057 1 660 0083
Fax 0057 231 4350
gerencia@ferreteriadiaz.com
www.ferreteriadiaz.com



Croatia

ALAGO d.o.o.
Horvati 112
10436 Rakov Potok
Tel. 00385 1 653 93 92
Fax 00385 1 653 93 93
info@alago.hr
www.alago.hr



Latvia

UAB „TTS Tooltechnic Systems“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@tts-company.lt
www.festool.lv



Lebanon

Equipment plus sarl
Mkales Street 41
Beirut, Lebanon
Tel. 00961 1 692136
Mobile 00961 71 861234
info@equipment-plus.com
www.equipment-plus.com



Lithuania

UAB „Festool LT“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@festool.lt
www.festool.lt



Malta

PIOVE HOLDINGS Ltd.
C&C Technik
Prof's Carmelo Coliero Street
Handaq Industrial Estate
Handaq
QRM4005 Qormi
Tel. 00356 21 44 67 98
Info@cctechnikmalta.com
www.cctechnikmalta.com



Macedonia

Rosa Doool
st. Jadranska Magistrala 90
1000 Skopje
Tel. 00389 022 602 092
Fax 00389 022 602 093
info@rosa.com.mk
contact@rosa.com.mk
www.rosa.com.mk



Moldova

UAB „TTS Tooltechnic Systems“
Ašigalio g. 6
LT-49142, Kaunas, Lietuva
Tel. 00370 37 308 414
Fax 00370 37 323 848
info@tts-company.lt
www.tts-company.lt



Mexico

Fijaciones Industriales Mariscal, S.A.
Avenida Colon No. 2220 PTE. (ESQ. Edison)
Col. Talleres
C.P. 64480 Monterrey N.L.
México
Phone: (81) 81234447
servicio2@fijacionesindustriales.com.mx
www.fijacionesindustriales.com.mx